Research Article

Parametric Approach to Trajectory Tracking Control of Robot Manipulators

Shijie Zhang and Yi Ning

Research Institute of Robotics, Henan University of Technology, Zhengzhou 450001, China

Correspondence should be addressed to Shijie Zhang; zhangshijie1@gmail.com

Received 7 July 2013; Revised 8 September 2013; Accepted 9 September 2013

Academic Editor: Weihai Zhang

Copyright © 2013 S. Zhang and Y. Ning. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

The mathematic description of the trajectory of robot manipulators with the optimal trajectory tracking problem is formulated as an optimal control problem, and a parametric approach is proposed for the optimal trajectory tracking control problem. The optimal control problem is first solved as an open loop optimal control problem by using a time scaling transform and the control parameterization method. Then, by virtue of the relationship between the optimal open loop control and the optimal closed loop control along the optimal trajectory, a practical method is presented to calculate an approximate optimal feedback gain matrix, without having to solve an optimal control problem involving the complex Riccati-like matrix differential equation coupled with the original system dynamics. Simulation results of 2-link robot manipulator are presented to show the effectiveness of the proposed method.

1. Introduction

Trajectory tracking problem is the most significant and fundamental task in control of robotic manipulator. Motivated by requirements such as a high degree of automation and fast speed operation from industry, various control methods are used such as PID control, adaptive control, variable structure control, neural networks control, and fuzzy control [1–5].

In the past two decades, the optimal control schemes for manipulator arms have been actively researched because the optimal motions that minimize energy consumption, error trajectories, or motion time yield high productivity, efficiency, smooth motion, durability of machine parts, and so forth [6–11]. Various types of methods have been developed to solve the robotic manipulator optimal control schemes.

By the application of the optimal control theory, Pontryagin's maximum principle leads to a two-point boundary value problem. Although this theory and its solutions are rigorous, it has been used to solve equations for the motions of 2-link or at most 3-link planar manipulators due to the complexity and the nonlinearity of the manipulator dynamics [6]. Approximation methods have been studied to obtain the solutions for three or more DOF spatial manipulators. However, the solutions obtained have not been proved to be

optimal. These approximation methods are roughly divided into two groups depending on whether or not they utilize gradients [11]. Recently, the applications of intelligent control techniques (such as fuzzy control or neural network control) with optimal algorithm to the motion control of robot manipulators have received considerable attention [12–17]. But sometimes these methods take quite a long time to find a coefficient that satisfies the requirement of the controlling task. In addition, lack of theoretical analysis and stability security makes industrialists wary of using the results in real industrial environments.

This paper is concerned with the nonlinear optimal feedback control of robot manipulator trajectory tracking. The energy consumption and error trajectories are minimized as performance index in the optimal control problem. An optimal open loop control is first obtained by using a time scaling transform [18] and the control parameterization technique [19]. Then, we derive the form of the optimal closed loop control law, which involves a feedback gain matrix, for the optimal control problem. The optimal feedback gain matrix is required to satisfy a Riccati-like matrix differential equation. Then, the third order B-spline function, which has been proved to be very efficient for solving optimal approximation and optimal control problems, is employed

FIGURE 1: Two-link (RR) robot manipulator.

to construct the components of the feedback gain matrix. By virtue of the relationship between the optimal open loop control and the optimal closed loop control along the optimal trajectory, a practical computational method is presented for finding an approximate optimal feedback gain matrix, without having to solve an optimal control problem involving the complex Riccati-like matrix differential equation coupled with the original system dynamics [20].

2. Robot Manipulators Dynamics

2.1. Models of Robot Dynamics. Consider the dynamic equation of a robot manipulator

$$M(q)\ddot{q} + C(q, \dot{q})\dot{q} + g(q) = u(t), \quad (1)$$

where $q, \dot{q}, \ddot{q} \in \mathbb{R}^n$ are the vectors of the generalized joint coordinates, velocity, and acceleration; $M(q) \in \mathbb{R}^{n \times n}$ denotes a symmetric positive definite inertia matrix; $C(q, \dot{q}) \in \mathbb{R}^{n \times n}$ stands for the Coriolis and centrifugal torques; $g(q) \in \mathbb{R}^n$ models the gravity forces; and $u(t) \in \mathbb{R}^n$ is the torque input. Some useful properties of robot dynamic are as follows.

Property 1. Matrix $M(q)$ is symmetric and positive definite.

Property 2. Matrix $\dot{M}(q) - 2C(q, \dot{q})$ is skew symmetric and satisfies that

$$\dot{q}^T [\dot{M}(q) - 2C(q, \dot{q})] \dot{q} = 0. \quad (2)$$

Property 3. The robot dynamics are passive in open loop, from torque input to velocity output, with the Hamiltonian as its storage function. If viscous friction was considered, the energy dissipates and the system is strictly passive.

The two-link revolute (RR) robot manipulator is shown in Figure 1. The masses of both links and actuators are denoted by m_1 and m_2 with I_1 and I_2 as mass moment of inertia. a_1 and a_2 denote the length; u_1 and u_2 are joints torques. The joints positions of the two links are defined by θ_1 and θ_2 .

The dynamic equations of 2-link RR robot are written in state space form as

$$\dot{x} = f(x) + B(x)u(t), \quad (3)$$

where $x = [q^T, \dot{q}^T]^T$ is the system state, $q = [\theta_1, \theta_2]^T$, and

$$\begin{aligned} f(x) &= \begin{bmatrix} -M^{-1}(q)(C(q, \dot{q})\dot{q} + g(q)) \\ 0 \end{bmatrix}, \\ B(x) &= \begin{bmatrix} 0 \\ M^{-1}(q) \end{bmatrix}, \end{aligned} \quad (4)$$

where

$$\begin{aligned} M(q) &= \begin{bmatrix} c_{11} & c_{12} \\ c_{21} & c_{22} \end{bmatrix}, \\ c_{11} &= (m_1 + m_2)a_1^2 + m_2a_2^2 + 2m_2a_1a_2\cos\theta_2, \\ c_{12} = c_{21} &= m_2a_1a_2\cos\theta_2, \\ c_{22} &= m_2a_2^2, \end{aligned} \quad (5)$$

$$C(q, \dot{q})\dot{q} = \begin{bmatrix} -m_2a_1a_2(2\dot{\theta}_1\dot{\theta}_2 + \dot{\theta}_2^2)\sin\theta_2 \\ m_2a_1a_2\dot{\theta}_1^2\sin\theta_2 \end{bmatrix},$$

$$g(q) = \begin{bmatrix} (m_1 + m_2)ga_1\cos\theta_1 + m_2ga_2\cos(\theta_1 + \theta_2) \\ m_2ga_2\cos(\theta_1 + \theta_2) \end{bmatrix}.$$

Define

$$\begin{aligned} N(q, \dot{q}) &= C(q, \dot{q})\dot{q} + g(q) = \begin{bmatrix} N_1(q, \dot{q}) \\ N_2(q, \dot{q}) \end{bmatrix}, \\ M^{-1}(q) &= \begin{bmatrix} M_{11} & M_{12} \\ M_{21} & M_{22} \end{bmatrix}; \end{aligned} \quad (6)$$

then,

$$f(x) = \begin{bmatrix} \theta_2 \\ \dot{\theta}_2 \\ \Theta\dot{\theta}_1 \\ \Xi\dot{\theta}_1 \end{bmatrix}, \quad B(x) = \begin{bmatrix} 0 & 0 \\ 0 & 0 \\ M_{11} & M_{12} \\ M_{21} & M_{22} \end{bmatrix}; \quad (7)$$

here

$$\begin{aligned} \Theta &= \frac{M_{22}(-N_2(q, \dot{q})) + M_{12}(-N_1(q, \dot{q}))}{x_1(t)}, \\ \Xi &= \frac{M_{22}(-N_2(q, \dot{q})) + M_{11}(-N_1(q, \dot{q}))}{x_2(t)}. \end{aligned} \quad (8)$$

2.2. Problem Statement. The purpose of control is to determine an optimal closed loop control signal so that the robot manipulator tracks the desired trajectory with minimal energy consumption. The optimal control problem can be formulated as follows.

Given system (3), find a closed loop control $u(t) \in \mathbb{R}^n$ such that the cost function

$$J = \alpha_1 \Phi_0(x(T)) + \alpha_2 \int_0^T u^T R u dt \quad (9)$$

is minimized, where $\Phi_0(x(T)) = (x(T) - x_d)^T Q (x(T) - x_d)$, T is the free terminal time, x_d is the desired trajectory, α_1 and α_2

are the weighting parameters, and $Q \in \mathbb{R}^{2n \times 2n}$ and $R \in \mathbb{R}^{n \times n}$ are symmetric positive semidefinite and symmetric positive definite weighting matrices, respectively.

We refer to the above problem as problem (P). This optimal close loop control problem is very difficult to be solved directly. In this paper, we derive the form of the optimal closed loop control law after obtaining an optimal open loop control by using a time scaling transform and the control parameterization technique. Then the difficulty of the problem is transformed to find a feedback gain matrix which is involved in the optimal closed loop control law. A practical computational method is presented in [20] for finding an approximate optimal feedback gain matrix, without having to solve an optimal control problem involving the complex Riccati-like matrix differential equation coupled with the original system dynamics.

3. Parametric Approach to the Optimal Controller Design

By using a time scaling transform and the control parameterization technique, the above problem is solved as an optimal open loop control problem firstly. An optimal open loop control and the corresponding optimal trajectory will be provided.

Let the time horizon $[0, T]$ be partitioned into p subintervals as follows:

$$0 = t_0 \leq t_1 \leq \dots \leq t_p = T. \quad (10)$$

The switching times t_i , $1 \leq i \leq p$, are regarded as decision variables. Employing the time scaling transform introduced in [19] to map these switching times into a set of fixed time points $\theta_i = i/p$, $i = 1, \dots, p$, on a new time horizon $[0, 1]$. Then the following differential equation is achieved:

$$\frac{dt(s)}{ds} = v^p(s), \quad s \in [0, 1], \quad (11)$$

where

$$v^p(s) = \sum_{i=1}^p \xi_i \chi_{[\theta_{i-1}, \theta_i]}(s), \quad (12)$$

where $\chi_I(s)$ denotes the indicator function of I defined by

$$\chi_I(s) = \begin{cases} 1, & s \in I, \\ 0, & \text{elsewhere,} \end{cases} \quad (13)$$

and $\xi_i \geq 0$, $\sum_{i=1}^p \xi_i = T$.

For $s \in [\theta_{l-1}, \theta_l]$, we have

$$t(s) = \sum_{i=1}^{l-1} \xi_i + \xi_l (s - \theta_{l-1}) p, \quad (14)$$

where $l = 1, \dots, p$. Clearly,

$$t(1) = \sum_{i=1}^p \xi_i = T. \quad (15)$$

Then after the time scaling transform, system (3) can be converted into the following form:

$$\dot{\hat{x}}(s) = v^p(s) [f(\hat{x}(s)) + B(\hat{x}(s), s) \tilde{u}(s)], \quad (16)$$

where $\hat{x}(s) = [\tilde{x}(s)^T, t(s)]^T$, $\tilde{x}(s) = x(t(s))$, and $\tilde{u}(s) = u(t(s))$.

Now we apply the control parameterization technique to approximate the control $\tilde{u}(s)$ as follows:

$$\tilde{u}_i^p(s) = \sum_{k=1}^{p+1} \sigma_k^i \Omega\left(\left(\frac{1}{p}\right)s - k\right), \quad i = 1, \dots, n, \quad (17)$$

where

$$\Omega(\kappa) = \begin{cases} 0, & |\kappa| > 2, \\ -\frac{1}{6}|\kappa|^3 + \kappa^2 - 2|\kappa| + \frac{4}{3}, & 1 \leq |\kappa| \leq 2, \\ \frac{1}{2}|\kappa|^3 - \kappa^2 + \frac{2}{3}, & |\kappa| < 1, \end{cases} \quad (18)$$

is the cubic spline basis function.

Define $\sigma^i = [\sigma_{-1}^i, \dots, \sigma_{p+1}^i]^T$, $i = 1, \dots, n$, and $\sigma = [(\sigma^1)^T, \dots, (\sigma^n)^T]^T$; let Π denote the set containing all σ . Then $\tilde{u}^p(s) = [\tilde{u}_1^p(s), \dots, \tilde{u}_n^p(s)]^T$ is determined uniquely by the switching vector $\sigma \in \Pi$. Thus, it can be written as $\tilde{u}^p(\cdot | \sigma)$. Now the optimal parameterization selection problem, which is an approximation of problem (P), can be stated as follows.

Problem (Q). Given system (16), find a combined vector (σ, ξ) , such that the cost function

$$J(\sigma) = \alpha_1 \widehat{\Phi}_0(\hat{x}(1 | \sigma)) + \alpha_2 \int_0^1 v^p(s | \xi) \tilde{u}^p(s | \sigma)^T R \tilde{u}^p(s | \sigma) ds \quad (19)$$

is minimized, where $\widehat{\Phi}_0(\hat{x}(1 | \sigma)) = (\hat{x}(1 | \sigma) - \hat{x}_d)^T \widehat{S}(\hat{x}(1 | \sigma) - \hat{x}_d)$ and $\hat{x}_d$ is the desired trajectory.

Now problem (P) is approximated by a sequence of optimal parameter selection problems, each of which can be viewed as a mathematical programming problem and hence can be solved by existing gradient-based optimization methods. Here, our controls are approximated in terms of cubic spline basis functions, and thus they are smooth. problem (Q) can be solved easily by the use of the optimal control software package MISER 3.3 [21].

Suppose that $(\tilde{u}^{p*}, \hat{x}^*)$ is the optimal solution of problem (Q). Then it follows that the optimal solution to problem (P) is (u^*, x^*, T^*) , where u^* is the optimal open loop control, x^* is the corresponding optimal state vector, and T^* is the optimal terminal time. For the computation of the optimal closed loop control problem, we have the following theorem.

Theorem 1. The optimal closed loop control $\tilde{u}^*$ for problem (P) is given by

$$\tilde{u}^*(t) = \frac{1}{2\alpha_2} R^{-1} B^T K(t) f(x^*(t), t), \quad (20)$$

FIGURE 2: Position tracking of the end joint.

where x^* is the optimal state and $K(t)$ is the solution of the following Riccati-like differential equation

$$\left(\dot{K} + KF + F^T K + \frac{1}{2} K F B R^{-1} B^T K \right) f + KD = 0, \quad (21)$$

where

$$F = \frac{\partial f}{\partial x}, \quad D = \frac{\partial f}{\partial t},$$

$$K(T) f(x(T), T) = \alpha_1 \frac{\partial \Phi_0(x(T))}{\partial x(T)} = 2\alpha_1 (x(T) - x_d) S. \quad (22)$$

The proof is similar to that given for Theorem 3.1 in [22]. Details can refer to this literature.

Problem (R). Subject to the dynamical system (1), with $\bar{u}$ given by Theorem 1, find a $K(t)$ such that the cost function (17) also with $\bar{u}$ is minimized.

By Theorem 1, although the form of the optimal closed loop control law is given, the matrix function $K(t)$ is still required to be obtained. The solving process involves solving a new optimal control problem denoted as follow. Using the method proposed in [20], problem (R) could be solved well.

In [15], an alternative approach was proposed to construct an approximate optimal matrix function $K^*(t)$ without having to solve this complicated optimal control problem (R). The basic idea is explained as follows. Suppose that u^* is an optimal open loop control of problem (P) and that x^* is the corresponding optimal state. We now consider problem (P) with $x = x^*$, that is, along the optimal open loop path, and our task is to find a $K^*(t)$ such that $\tilde{u}^* = (1/2\alpha_2)R^{-1}B^T K^*(t)f(x^*(t), t)$ best approximates the control $\bar{u}^*$ in the mean square sense. Then $\tilde{u}^*$ can be regarded as a good approximate optimal feedback control for problem (P).

The calculation steps of solving $K^*(t)$ are as follows.

Step 1. The time horizon $[0, T^*]$ is partitioned into p equal subintervals:

$$0 = t_0 \leq t_1 \leq \dots \leq t_p \leq t_{p+1} = T^*. \quad (23)$$

Step 2. Let

$$[K(t)_{i,j}] \approx \sum_{k=-1}^{p+1} (c_{i,j,k}) \Omega\left(\left(\frac{T^*}{p}\right)t - k\right), \quad (24)$$

where $c_{i,j,k}$, $i, j = 1, 2, \dots, n$, $k = -1, 0, \dots, p+1$, are real constant coefficients that are to be determined. p is the number of equality subintervals on $[0, T^*]$, and $p+3$ is the total number of cubic spline basis functions used in the approximation of each $[K(t)_{i,j}]$.

Step 3. Let

$$Y(K) = \int_0^{T^*} \|u^*(t) - \tilde{u}(t)\| dt, \quad (25)$$

where

$$\tilde{u}(t) = \frac{1}{2\alpha_2} R^{-1} B^T K(t) f(x^*(t), t). \quad (26)$$

Step 4. Find coefficients $c_{i,j,k}$ such that the cost function (25) is minimized. These optimal coefficients can be obtained by solving the following optimality conditions:

$$\Lambda = \frac{\partial Y(K)}{\partial c_{i,j,k}} = 0. \quad (27)$$

We can see that these are linear equations and hence are easy to solve.

4. Simulation

In this section, the simulations of the nonlinear optimal control for the 2-link RR-robot manipulator are performed to show the efficiency of the proposed method.

Assuming that the friction is negligible, two-link robot manipulators is simulated with following parameters:

$$\begin{aligned} m_1 &= 1 \text{ Kg}, \\ m_2 &= 1 \text{ Kg}, \\ a_1 &= 1 \text{ m}, \\ a_2 &= 1 \text{ m}, \\ g &= 9.8 \text{ m/s}^2, \\ x_0 &= [1, 1]^T, \\ \dot{x}_0 &= [1, 1]^T. \end{aligned} \quad (28)$$

FIGURE 3: Velocity tracking of the end joint.

FIGURE 4: The control inputs of the end joint.

The control objective is to track the desired trajectory given by

$$\begin{aligned} q_{1d} &= 1 + 0.2 \cos(\pi t), \\ q_{2d} &= 1 + 0.2 \sin(\pi t). \end{aligned} \quad (29)$$

The evolution of tracking errors are as follows

$$e = [e_1 \ e_2]^T = [q_1 - q_{1d} \ q_2 - q_{2d}]^T. \quad (30)$$

In the simulation, the time horizon $[0, T]$ is partitioned into 20 subintervals. $\alpha_1 = 3$, $\alpha_2 = 1$, and S and R are unit matrices of proper dimension. We first use the time scaling transform and the control parameterization method to construct the corresponding approximated problem (Q). Then, MISER 3.3 is utilized to solve it, giving rise to an optimal open loop control and the corresponding optimal trajectory. Then the feedback gain matrix $K^*(t)$ is obtained by the above calculation steps.

Simulation results are shown in Figures 2 to 4. The position tracking and the velocity tracking of the end joint are shown in Figures 2 and 3, and the control input of the end joint is shown in Figure 4.

5. Conclusions

A parametric approach to trajectory tracking control of robot manipulators is studied in this paper, in which an optimal open loop control is obtained firstly by using the control parametrization method and the time scaling transform. Then, we obtained the form of the optimal closed loop control law, where the feedback gain matrix is required to satisfy a Riccati-like matrix differential equation, and a practical method was proposed to calculate the feedback gain matrix. The simulation results demonstrate the validity of the proposed method.

Acknowledgments

This work was supported by the National Natural Science Foundation of China (61075083), the Natural Science Foundation of Henan Education Department (13A120204), the Technology Innovation Talents Plan of Henan University of Technology (2012CXRC14), and the Science Foundation of Henan University of Technology (2012BS043).

References

- [1] S. Mahmoudzadeh and H. Mojallali, "An optimized PID for legless capsubots using modified imperialist competitive algorithm," in *Proceedings of the 1st RSI/ISM International Conference on Robotics and Mechatronics*, pp. 194–199, 2013.
- [2] J. P. Ferreira, M. M. Crisóstomo, and A. P. Coimbra, "Adaptive PD controller modeled via support vector regression for a biped robot," *IEEE Transactions on Control Systems Technology*, vol. 21, no. 3, pp. 941–949, 2013.
- [3] J. Kasac, B. Novakovic, D. Majetic, and D. Brezak, "Passive finite-dimensional repetitive control of robot manipulators," *IEEE Transactions on Control Systems Technology*, vol. 16, no. 3, pp. 570–576, 2008.
- [4] M. Asgari and M. A. Ardestani, "Dynamics and control of a novel 3-DoF spatial parallel robot," in *Proceedings of the 1st RSI/ISM International Conference on Robotics and Mechatronics*, pp. 183–188, 2013.
- [5] R.-J. Wai and R. Muthusamy, "Fuzzy-neural-network inherited sliding-mode control for robot manipulator including actuator dynamics," *IEEE Transactions on Neural Networks and Learning Systems*, vol. 24, pp. 274–287, 2013.
- [6] E.-B. Meier and A. E. Bryson Jr., "Efficient algorithm for time-optimal control of a two-link manipulator," *Journal of Guidance, Control, and Dynamics*, vol. 13, no. 5, pp. 859–866, 1990.

- [7] D. Constantinescu and E. A. Croft, "Smooth and time-optimal trajectory planning for industrial manipulators along specified paths," *Journal of Robotic Systems*, vol. 17, pp. 233–249, 2000.
- [8] M. Galicki and D. Uciński, "Time-optimal motions of robotic manipulators," *Robotica*, vol. 18, no. 6, pp. 659–667, 2000.
- [9] C. W. J. Hol, L. G. Van Willigenburg, E. J. Van Henten, and G. Van Straten, "A new optimization algorithm for singular and non-singular digital time-optimal control of robots," in *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA '01)*, pp. 1136–1141, May 2001.
- [10] J.-K. Park and J. E. Bobrow, "Reliable computation of minimum-time motions for manipulators moving in obstacle fields using a successive search for minimum-overload trajectories," *Journal of Robotic Systems*, vol. 22, no. 1, pp. 1–14, 2005.
- [11] Z. Shiller, "On singular time-optimal control along specified paths," *IEEE Transactions on Robotics and Automation*, vol. 10, no. 4, pp. 561–566, 1994.
- [12] E. Bobașu and D. Popescu, "On modelling and multivariable adaptive control of robotic manipulators," *WSEAS Transactions on Systems*, vol. 5, no. 7, pp. 1579–1586, 2006.
- [13] F. M. Raimondi and M. Melluso, "A neuro fuzzy controller for planar robot manipulators," *WSEAS Transactions on Systems*, vol. 3, pp. 2991–2996, 2004.
- [14] D. Popescu, "Neural control of manipulators using a supervisory algorithm," in *Proceedings of the International Conference on Automation and Quality Control*, pp. A576–A581, Cluj-Napoca, Romania, 1998.
- [15] S.-J. Huang and J.-S. Lee, "A stable self-organizing fuzzy controller for robotic motion control," *IEEE Transactions on Industrial Electronics*, vol. 47, no. 2, pp. 421–428, 2000.
- [16] Y. H. Kim and F. L. Lewis, "Optimal design of CMAC neural-network controller for robot manipulators," *IEEE Transactions on Systems, Man and Cybernetics Part C*, vol. 30, no. 1, pp. 22–31, 2000.
- [17] F. L. Lewis, A. Yesildirek, and K. Liu, "Multilayer neural-net robot controller with guaranteed tracking performance," *IEEE Transactions on Neural Networks*, vol. 7, pp. 388–396, 1996.
- [18] K. L. Teo, L. S. Jennings, H. W. J. Lee, and V. Rehbock, "The control parameterization enhancing transform for constrained optimal control problems," *Australian Mathematical Society B*, vol. 40, no. 3, pp. 314–335, 1999.
- [19] K. L. Teo, C. J. Goh, and K. H. Wong, *A Unified Computational Approach to Optimal Control Problems*, John Wiley and Sons Press, New York, NY, USA, 1991.
- [20] J. Zhou, D. Zhou, K. L. Teo, and G. Zhao, "Nonlinear optimal feedback control for lunar module soft landing," in *Proceedings of the IEEE International Conference on Automation and Logistics (ICAL '09)*, pp. 681–685, Shenyang, China, August 2009.
- [21] L. S. Jennings, M. E. Fisher, K. L. Teo, and C. J. Goh, *MISER3. 3 Optimal Control Software Version 3. 3: Theory and User Manual*. Centre for Applied Dynamics and Optimization, The University of Western Australia, 1996.
- [22] H. W. J. Lee, K. L. Teo, and W. Y. Yan, "Nonlinear optimal feedback control law for a class of nonlinear systems," *Neural, Parallel & Scientific Computations*, vol. 4, no. 2, pp. 157–178, 1996.