

Breaking strength (gf)					
con	0	3	6	12	24
	494	1045	1188	1237	1059
	361	991	1232	1327	1739
	405	811	1153	1315	1438
	322	986		1374	1397
	497	832	1199	1206	1191
	496	908	1170		1385
avg.	429	929	1188	1292	1368
std.	70	86	27	61	212
1st F-T	0	3	6	12	24
	356	718	912	1029	1106
	423	656	626	990	1273
	387	717	724	989	1223
	415	746	816	1176	949
	427	643	700	875	981
	362		827	988	1401
avg.	395	696	767	1008	1156
std.	29	40	94	89	160
2nd F-T	0	3	6	12	24
	352	694	633	1056	1194
	344	622	901	1034	1281
	362	601	967		971
	349	596	923		1203
	394	699	712	1125	1053
	328	614	837	1020	1237
avg.	355	637	829	1059	1157
std.	20	43	119	40	109

error value

Breaking strain (mm)					
con	0	3	6	12	24
	11.5	16.1	15.7	16.8	14.4
	9.14	16.2	16.7	16.6	17.4
	10.1	14.7	16.0	15.7	15.7
	9.06	15.8		17.1	15.6
	11.6	14.5	16.6	15.9	14.2
	11.3	15.6	17.5		15.2
avg.	10.4	15.5	16.5	16.4	15.4
std.	1.1	0.6	0.6	0.5	1.0
1st F-T	0	3	6	12	24
	8.80	12.6	15.4	15.9	14.7
	9.74	12.3	13.4	15.1	16.2
	9.14	13.2	13.3	14.3	15.4
	9.48	13.2	14.2	15.9	14.1
	9.56	12.4	13.1	14.1	14.5
	9.38		14.0	14.8	17.4
avg.	9.35	12.8	13.9	15.0	15.4
std.	0.31	0.4	0.8	0.7	1.1
2nd F-T	0	3	6	12	24
	8.68	13.2	13.4	15.7	15.8
	8.50	12.8	14.9	15.6	16.6
	8.82	12.0	15.1		13.9
	8.90	11.7	15.1		15.7
	9.26	12.8	13.8	15.7	14.7
	8.20	11.8	15.0	15.4	15.7
avg.	8.73	12.4	14.6	15.6	15.4
std.	0.33	0.6	0.7	0.1	0.9

Gel stiffness (gf/cm)					
con	0	3	6	12	24
	430	650	759	738	737
	395	613	738	798	999
	401	550	720	840	916
	356	626		805	893
	430	575	724	760	838
	439	583	669		909
	408	599	722	788	882
avg.	408	599	722	788	882
std.	28	34	30	36	80
1st F-T	0	3	6	12	24
	404	569	592	645	751
	434	532	469	657	788
	424	544	545	692	794
	438	564	575	738	675
	447	517	534	621	678
	386		589	667	807
	422	545	551	670	749
avg.	422	545	551	670	749
std.	21	19	42	37	54
2nd F-T	0	3	6	12	24
	405	527	472	671	758
	404	486	605	665	772
	410	501	640		697
	392	509	611		768
	425	545	516	716	719
	400	519	557	663	788
	406	514	567	679	750
avg.	406	514	567	679	750
std.	10	19	58	22	32