Research Article

H_∞ Filtering for a Class of Piecewise Homogeneous Markovian Jump Nonlinear Systems

Yucai Ding,¹ Hong Zhu,¹ Shouming Zhong,²
Yuping Zhang,¹ and Yong Zeng¹

¹ School of Automation Engineering, University of Electronic Science and Technology of China,
Chengdu 611731, China

² School of Mathematical Sciences, University of Electronic Science and Technology of China,
Chengdu 611731, China

Correspondence should be addressed to Yucai Ding, dycyer@163.com

Received 14 June 2012; Revised 15 August 2012; Accepted 28 August 2012

Academic Editor: Xing-Gang Yan

Copyright © 2012 Yucai Ding et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

H_∞ filtering problem for a class of piecewise homogeneous Markovian jump nonlinear systems is investigated. The aim of this paper is to design a mode-dependent filter such that the filtering error system is stochastically stable and satisfies a prescribed H_∞ disturbance attenuation level. By using a new mode-dependent Lyapunov-Krasovskii functional, mixed mode-dependent sufficient conditions on stochastic stability are formulated in terms of linear matrix inequalities (LMIs). Based on this, the mode-dependent filter is obtained. A numerical example is given to illustrate the effectiveness of the proposed main results.

1. Introduction

The filtering problem has received significant attention in the past decade. Current efforts on this topic can be divided into two classes: the Kalman filtering approach and the H_∞ filtering approach. As we all know, Kalman filtering approach is based on the assumption that the system is exactly known, and its disturbances are stationary Gaussian noises with known statistics. These assumptions limit the application scope of the Kalman filtering technique when there are uncertainties in either the exogenous input signals or the system model [1]. To overcome the restriction described above, H_∞ filtering has been introduced as an alternative filtering technique [2–6].

On the other hand, Markovian jump systems are an active area of research. It switches from one mode to another in a random way, and the switching between the modes is governed by a Markovian process with discrete and finite state space. These models serve as convenient tools for analyzing plants that are subjected to random abrupt parameter changes due

to, for instance, component and/or interconnection failures, sudden environmental changes, or change of the operating point of a linearized model of a nonlinear plant. A wide class of industrial system applications experience time delays due to various reasons including inherent physical properties (mass transport flow, recycling), data transmission delays or finite capabilities of information exchange [7]. When considering the continuous systems with time-varying delay, the systems can be clarified into two types, one is slow time-varying delay systems, that is, the derivative of the time delay is less than one, for example, [2, 8, 9], and the other is fast time-varying delay systems, that is, there are no constraints on the derivative of the time delay. Both Lyapunov-Krasovskii and Lyapunov-Razumikhin approaches are fundamental for time-delay systems, and some existing work usually do not require the derivative of the time delay to be less than one, see, for example, [10, 11]. Due to their extensive practical applications, considerable attention has been devoted to Markovian jump systems with time delays. The issues of stability and control have been well investigated; see, for example, [9, 11–29] and references therein. In [30–32], the sliding mode control of Markovian jump singular systems was studied, and, new integral-type sliding surface functions were designed. Moreover, strict LMI conditions of the stochastic stability were proposed in [30, 31], which are easy to be checked by Matlab LMI toolbox. In [32], a suitable switching surface function and a sliding mode control law were designed to ensure the attraction of the sliding surface when the system changes from one mode to another under Markovian switching, and the slack matrix approach was used to derive less conservative LMI conditions assuring stochastic admissibility. The filtering problem for Markovian jump time-delay systems was reported in [8, 33–40]. Many nonlinear physical systems can be represented as a connection of a linear dynamical system and a nonlinear element. Filtering for Markovian jump nonlinear system is an important research area that has attracted considerable interest [41–43]. It should be pointed out that the above-mentioned references assume that the Markovian processes are homogeneous, that is, the considered transition probabilities (TPs) in Markovian process are assumed to be time invariant. However, the assumption cannot always be satisfied in real applications, and the ideal assumption on TPs inevitably limits the applications of the established results to some extent [44]. Therefore, it is important and necessary to pay attention to the study of Markovian jump systems with time-varying TPs. Recently, the problem of H_∞ estimation for discrete-time Markovian jump linear system with time-varying TPs has been investigated in [44]. The H_∞ control problem has been conducted for a class of discrete-time Markovian jump systems with time-varying TPs in [45], where the average dwell-time switching is used to describe the variation among the TPs. The stochastic stability analysis of piecewise homogeneous Markovian jump neural networks with mixed time delays has been studied in [46]. But, the time-varying delays in [46] are independent of jump mode. To the best of our knowledge, no results have been given for piecewise homogeneous Markovian jump nonlinear systems with mode-dependent time-varying delays. With the appearance of time-varying TPs and mode-dependent time-varying discrete and distributed delays, the main difficulties are as follows: (1) the new Lyapunov functional should be constructed to deal with above problem; (2) since the system involves joint jump processes and mode-dependent time-varying delays, the calculation of derivative of the Lyapunov functional and the using of inequality techniques become more complicated. Moreover, the Lyapunov matrix P_i is assumed to be diagonal matrix in some existing literature, which leads to some conservativeness. Therefore, the key problems in this research are: (1) how to choose a Lyapunov function to derive a sufficient stochastic stability condition for the considered systems; (2) how to use the inequality techniques and calculate the parameters of the filter such that the resulting sufficient conditions are less conservative? Which has motivated this paper.

In this study, we are concerned to develop an efficient approach for H_∞ filtering problem of piecewise homogeneous Markovian jump system. The system under study involves mode-dependent time-varying discrete and distributed delays and inherent sector-like nonlinearities. By using a novel Lyapunov-Krasovskii functional, mixed mode-dependent sufficient condition on stochastic stability with an H_∞ performance is derived in terms of LMIs. Based on this, the existence condition of the desired filter which guarantees stochastic stability and an H_∞ performance of the corresponding filtering error system is presented. A numerical example is provided to show the effectiveness of the proposed results.

Notation. Throughout this paper, $\mathbb{R}^n$ denotes the n -dimensional Euclidean space. $(\Omega, \mathcal{F}, \mathcal{P})$ is a probability space, Ω is the sample space, $\mathcal{F}$ is the σ -algebra of subsets of the sample space, and $\mathcal{P}$ is the probability measure on $\mathcal{F}$. $\mathcal{E}\{\cdot\}$ refers to the expectation operator with respect to some probability measure $\mathcal{P}$. We use $\text{diag}\{\cdot, \cdot, \cdot\}$ as a block diagonal matrix. $A > 0$ (< 0) means A is a symmetric positive (negative) definite matrix. A^T denotes the transpose of matrix A , I is the identity matrix with compatible dimension.

2. System Description and Definitions

Fix a probability space $(\Omega, \mathcal{F}, \mathcal{P})$ and consider the following stochastic Markovian jump system with mode-dependent time-varying delays:

$$\begin{aligned} \dot{x}(t) &= A(r_t)x(t) + A_1(r_t)x(t - \tau(t, r_t)) + A_2(r_t) \int_{t-\tau(t, r_t)}^t x(s)ds + B(r_t)f(x(t)) + D_1(r_t)\omega(t), \\ y(t) &= C(r_t)x(t) + C_1(r_t)x(t - \tau(t, r_t)) + C_2(r_t) \int_{t-\tau(t, r_t)}^t x(s)ds + E(r_t)g(x(t)) + D_2(r_t)\omega(t), \\ z(t) &= H(r_t)x(t), \\ x(t) &= \phi(t), \quad t \in [-\tau, 0], \end{aligned} \tag{2.1}$$

where $x(t) \in \mathbb{R}^n$ is the state vector; $\omega(t)$ is the exogenous disturbance input which belongs to $L_2[0, \infty)$; $y(t) \in \mathbb{R}^p$ is the measured output; $z(t) \in \mathbb{R}^q$ is the signal to be estimated; $\phi(t)$ is a compatible vector-valued initial function defined on $[-\tau, 0]$; $A(r_t)$, $A_1(r_t)$, $A_2(r_t)$, $B(r_t)$, $D_1(r_t)$, $C(r_t)$, $C_1(r_t)$, $C_2(r_t)$, $E(r_t)$, $D_2(r_t)$ and $H(r_t)$ are real constant matrices with appropriate dimensions. $\tau(t, r_t)$ is the mode-dependent time-varying delay. The process $\{r_t, t \geq 0\}$ is described by a Markov chain with finite state space $S_1 = \{1, 2, \dots, N\}$, and its transition probability matrix, $\Pi^{(\sigma_{t+\Delta})} = [\pi_{il}^{(\sigma_{t+\Delta})}]_{N \times N}$ ($i, l \in S_1$), is governed by

$$\Pr\{r_{t+\Delta} = l \mid r_t = i\} = \begin{cases} \pi_{il}^{(\sigma_{t+\Delta})} \Delta + o(\Delta), & l \neq i, \\ 1 + \pi_{ii}^{(\sigma_{t+\Delta})} \Delta + o(\Delta), & l = i, \end{cases} \tag{2.2}$$

where $\Delta > 0$ and $\lim_{\Delta \rightarrow 0} (o(\Delta)/\Delta) = 0$; $\pi_{il}^{(\sigma_{t+\Delta})} \geq 0$ for $l \neq i$ is the transition rate from mode i at time t to mode l at time $t + \Delta$ and $\pi_{ii}^{(\sigma_{t+\Delta})} = -\sum_{l=1, l \neq i}^N \pi_{il}^{(\sigma_{t+\Delta})}$. In this study, we assume that σ_t vary in another finite set $S_2 = \{1, 2, \dots, M\}$, and the variations are considered as the

stochastic variation. The variation of σ_t is governed by a higher-level transition probability (HTP) matrix $\Lambda = [\lambda_{jk}]_{M \times M}$ ($j, k \in S_2$) and the TPs of Markov chain satisfy

$$\Pr\{\sigma_{t+\Delta} = k \mid \sigma_t = j\} = \begin{cases} \lambda_{jk}\Delta + o(\Delta), & k \neq j, \\ 1 + \lambda_{jj}\Delta + o(\Delta), & k = j, \end{cases} \quad (2.3)$$

where $\lambda_{jk} \geq 0$ for $k \neq j$ is the transition rate from mode j at time t to mode k at time $t + \Delta$ and $\lambda_{jj} = -\sum_{k=1, k \neq j}^M \lambda_{jk}$. The stochastic processes r_t and σ_t are assumed to be independent throughout this paper. For vector-valued functions $f(x(t))$ and $g(x(t))$, we assume:

$$\begin{aligned} [f(x) - f(y) - M_1(x - y)]^T [f(x) - f(y) - M_2(x - y)] &\leq 0, \\ [g(x) - g(y) - L_1(x - y)]^T [g(x) - g(y) - L_2(x - y)] &\leq 0, \end{aligned} \quad (2.4)$$

where for all $x, y \in \mathbb{R}^n$ and $M_1, M_2, L_1, L_2 \in \mathbb{R}^{n \times n}$ are the known constant matrices. In what follows, for implicity of presentations and without loss of generality, we always assume that $f(0) = 0$ and $g(0) = 0$.

For simplicity, a matrix $R(r_t)$ will be denoted by R_i . For example, $A(r_t)$ is denoted by A_i , $A_1(r_t)$ is denoted by A_{1i} and $\tau(r_t, t)$ is denoted by $\tau_i(t)$, ($i \in S_1$). When the mode is in $r_t = i$, the mode-dependent time-varying delay satisfies

$$0 \leq \tau_i(t) \leq \tau_i \leq \tau, \quad \dot{\tau}_i(t) \leq \mu_i, \quad (2.5)$$

where $\tau = \max\{\tau_i\}$.

In this study, the following full-order linear filter is proposed to estimate the signal $z(t)$:

$$\begin{aligned} \dot{\hat{x}}(t) &= A_{F_{ij}} \hat{x}(t) dt + B_{F_{ij}} y(t), \\ \hat{z}(t) &= C_{F_{ij}} \hat{x}(t), \\ \hat{x}(0) &= 0, \end{aligned} \quad (2.6)$$

where $\hat{x}(t)$ is the filter state vector, and $(A_{F_{ij}} \ B_{F_{ij}} \ C_{F_{ij}})$ are appropriately dimensioned filter matrices to be determined.

Define the estimation error by $e(t) = z(t) - \hat{z}(t)$, we obtain the following filtering error system:

$$\begin{aligned} \dot{\xi}(t) &= \bar{A}_{ij} \xi(t) + \bar{A}_{1ij} K \xi(t - \tau_i(t)) + \bar{A}_{2ij} K \int_{t-\tau_i(t)}^t \xi(s) ds + \bar{B}_{ij} f(K \xi(t)) + \bar{E}_{ij} g(K \xi(t)) + \bar{D}_{ij} \omega(t), \\ e(t) &= \bar{H}_{ij} \xi(t), \\ \tilde{x}(t) &= \tilde{\phi}(t), \quad \forall t \in [-\tau, 0], \end{aligned} \quad (2.7)$$

where $\xi(t) = [x^T(t) \ \hat{x}^T(t)]^T$, $\tilde{\phi}(t) = [\phi^T(t) \ 0^T]^T$, and

$$\begin{aligned} \bar{A}_{ij} &= \begin{bmatrix} A_i & 0 \\ B_{F_{ij}} C_i & A_{F_{ij}} \end{bmatrix}, & \bar{A}_{1ij} &= \begin{bmatrix} A_{1i} \\ B_{F_{ij}} C_{1i} \end{bmatrix}, & \bar{A}_{2ij} &= \begin{bmatrix} A_{2i} \\ B_{F_{ij}} C_{2i} \end{bmatrix}, & \bar{B}_{ij} &= \begin{bmatrix} B_i \\ 0 \end{bmatrix}, \\ \bar{E}_{ij} &= \begin{bmatrix} 0 \\ B_{F_{ij}} E_i \end{bmatrix}, & \bar{D}_{ij} &= \begin{bmatrix} D_{1i} \\ B_{F_{ij}} D_{2i} \end{bmatrix}, & \bar{H}_{ij} &= \begin{bmatrix} H_i & -C_{F_{ij}} \end{bmatrix}, & K &= [I \ 0]. \end{aligned} \quad (2.8)$$

Remark 2.1. According to the definitions of homogeneous Markovian chain and nonhomogeneous Markovian chain in [44, 47], one can see that the Markovian chain σ_t in this paper is homogeneous, while the Markovian chain r_t is neither homogeneous nor nonhomogeneous, but a state between them, which can be called the finite piecewise homogeneous Markovian chain.

Remark 2.2. In this paper, the nonlinear functions $f(x(t))$ and $g(x(t))$ are said to belong to sectors, which means that the nonlinearities are bounded by sectors. The nonlinear descriptions in (2.4) are quite general that include the usual Lipschitz conditions as a special case [2].

The following lemma and definitions are introduced, which will be used in the proof of the main results.

Lemma 2.3 (see [48]). *For any matrix $M > 0$, scalar $\gamma > 0$, vector function $\omega : [0, \gamma] \rightarrow \mathbb{R}^n$ such that the integrations concerned are well defined, the following inequality holds:*

$$\left[\int_0^\gamma \omega^T(s) ds \right] M \left[\int_0^\gamma \omega(s) ds \right] \leq \gamma \int_0^\gamma \omega^T(s) M \omega(s) ds. \quad (2.9)$$

Definition 2.4. The filtering error system (2.7) with $\omega(t) = 0$ is said to be stochastically stable, if for any initial $\varphi(t) \in \mathbb{R}^n$ defined on $[-\tau, 0]$ and modes r_t and σ_t , the following relation holds: [7]

$$\lim_{T \rightarrow \infty} \mathcal{E} \left\{ \int_0^T \|\xi(s, r_0, \sigma_0, \varphi)\|^2 ds \right\} < \infty. \quad (2.10)$$

Definition 2.5. Given a scalar $\gamma > 0$, the filtering error system (2.7) is said to be stochastically stable with an H_∞ performance γ , if for every system mode r_t , the filtering error system (2.7) with $\omega(t) = 0$ is stochastically stable and, under zero initial condition, it satisfies $\|e\|_2 \leq \gamma \|\omega\|_2$ for any nonzero $\omega(t) \in L_2[0, \infty]$.

3. Main Results

In this section, we first propose a delay-dependent sufficient condition for stochastic stability with the H_∞ performance of filtering error system (2.7). Now, consider the following Lyapunov-Krasovskii functional for systems (2.7):

$$V(\xi_t, t, i, j) = \sum_{n=1}^6 V_n(\xi_t, t, i, j), \quad (3.1)$$

where

$$\begin{aligned} V_1(\xi_t, t, i, j) &= \xi^T(t) P(r_t, \sigma_t) \xi(t), \\ V_2(\xi_t, t, i, j) &= \int_{t-\tau(r_t)}^t \xi^T(s) K^T Q_1(r_t, \sigma_t) K \xi(s) ds + \int_{t-\tau(r_t)}^t \xi^T(s) K^T Q_2(r_t, \sigma_t) K \xi(s) ds, \\ V_3(\xi_t, t, i, j) &= \int_{t-\tau(r_t)}^t \left[\int_{\theta}^t \xi^T(s) K^T ds \right] R_1(r_t, \sigma_t) \left[\int_{\theta}^t K \xi(s) ds \right] d\theta, \\ V_4(\xi_t, t, i, j) &= \tau \int_{-\tau}^0 \int_{t+\theta}^t \xi^T(s) K^T Z K \xi(s) ds d\theta, \\ V_5(\xi_t, t, i, j) &= \int_{-\tau}^0 \int_{t+\theta}^t \xi^T(s) K^T R_2 K \xi(s) ds d\theta + \int_{-\tau(r_t)}^0 \int_{t+\theta}^t \xi^T(s) K^T G_1(r_t) K \xi(s) ds d\theta, \\ V_6(\xi_t, t, i, j) &= \int_0^\tau \int_{-\theta}^0 \int_{t+s}^t \xi^T(\alpha) K^T R_3 K \xi(\alpha) d\alpha ds d\theta + \int_0^\tau \int_{t-\theta}^t (s-t+\theta) \xi^T(s) K^T G_2 K \xi(s) ds d\theta. \end{aligned} \quad (3.2)$$

Let $\mathcal{L}$ be the weak infinitesimal generator of the random process $\{\xi_t, r_t, \sigma_t\}$. Then, for each $i \in S_1, j \in S_2$, the stochastic differential of $V_1(\xi_t, t, i, j)$ along the trajectory of system (2.7) is given by

$$\begin{aligned} \mathcal{L}V_1(\xi_t, t, i, j) &= 2\xi^T(t) P_{ij} \\ &\quad \times \left[\bar{A}_{ij} \xi(t) + \bar{A}_{1ij} K \xi(t - \tau_i(t)) + \bar{A}_{2ij} K \int_{t-\tau_i(t)}^t \xi(s) ds + \bar{B}_{ij} f(K \xi(t)) \right. \\ &\quad \left. + \bar{E}_{ij} g(K \xi(t)) + \bar{D}_{ij} \omega(t) \right] + \xi^T(t) \left[\sum_{l \in S_1} \pi_{il}^{(j)} P_{lj} + \sum_{k \in S_2} \lambda_{jk} P_{ik} \right] \xi(t), \\ \mathcal{L}V_2(\xi_t, t, i, j) &= \mathcal{L} \int_{t-\tau(r_t)}^t \xi^T(s) K^T Q_1(r_t, \sigma_t) K \xi(s) ds + \mathcal{L} \int_{t-\tau(r_t)}^t \xi^T(s) K^T Q_2(r_t, \sigma_t) K \xi(s) ds \end{aligned}$$

$$\begin{aligned}
&= \lim_{\Delta \rightarrow 0^+} \frac{1}{\Delta} E \left\{ \int_{t+\Delta-\tau(r_{t+\Delta}, t+\Delta)}^{t+\Delta} \xi^T(s) K^T Q_1(r_{t+\Delta}, \sigma_{t+\Delta}) K \xi(s) ds \right. \\
&\quad \left. - \int_{t-\tau_i(t)}^t \xi^T(s) K^T Q_{1ij} K \xi(s) ds \right\} \\
&+ \lim_{\Delta \rightarrow 0^+} \frac{1}{\Delta} E \left\{ \int_{t+\Delta-\tau(r_{t+\Delta})}^{t+\Delta} \xi^T(s) K^T Q_2(r_{t+\Delta}, \sigma_{t+\Delta}) K \xi(s) ds \right. \\
&\quad \left. - \int_{t-\tau_i(t)}^t \xi^T(s) K^T Q_{2ij} K \xi(s) ds \right\} \\
&= \xi^T(t) K^T Q_{1ij} K \xi(t) - (1 - \dot{\tau}_i(t)) \xi^T(t - \tau_i(t)) K^T Q_{1ij} K \xi(t - \tau_i(t)) \\
&\quad + \xi^T(t) K^T Q_{2ij} K \xi(t) \\
&\quad - \xi^T(t - \tau_i) K^T Q_{2ij} K \xi(t - \tau_i) + \sum_{l \in S_1} \pi_{il}^{(j)} \int_{t-\tau_i(t)}^t \xi^T(s) K^T Q_{1lj} K \xi(s) ds \\
&\quad + \sum_{k \in S_2} \lambda_{jk} \int_{t-\tau_i(t)}^t \xi^T(s) K^T Q_{1ik} K \xi(s) ds + \sum_{l \in S_1} \pi_{il}^{(j)} \int_{t-\tau_i}^t \xi^T(s) K^T Q_{2lj} K \xi(s) ds \\
&\quad + \sum_{k \in S_2} \lambda_{jk} \int_{t-\tau_i}^t \xi^T(s) K^T Q_{2ik} K \xi(s) ds \\
&\leq \xi^T(t) K^T Q_{1ij} K \xi(t) - (1 - \mu_i) \xi^T(t - \tau_i(t)) K^T Q_{1ij} K \xi(t - \tau_i(t)) \\
&\quad + \xi^T(t) K^T Q_{2ij} K \xi(t) \\
&\quad - \xi^T(t - \tau_i) K^T Q_{2ij} K \xi(t - \tau_i) + \pi_{ii}^{(j)} \int_{t-\tau_i(t)}^t \xi^T(s) K^T Q_{1ij} K \xi(s) ds \\
&\quad + \int_{t-\tau}^t \xi^T(s) K^T \left(\sum_{l \in S_1, l \neq i} \pi_{il}^{(j)} Q_{1lj} \right) K \xi(s) ds \\
&\quad + \int_{t-\tau_i(t)}^t \xi^T(s) K^T \left(\sum_{k \in S_2} \lambda_{jk} Q_{1ik} \right) K \xi(s) ds \\
&\quad + \pi_{ii}^{(j)} \int_{t-\tau_i}^t \xi^T(s) K^T Q_{2ij} K \xi(s) ds + \int_{t-\tau}^t \xi^T(s) K^T \left(\sum_{l \in S_1, l \neq i} \pi_{il}^{(j)} Q_{2lj} \right) K \xi(s) ds \\
&\quad + \int_{t-\tau_i}^t \xi^T(s) K^T \left(\sum_{k \in S_2} \lambda_{jk} Q_{2ik} \right) K \xi(s) ds. \\
\mathcal{L}V_3(\xi_t, t, i, j) &= - (1 - \dot{\tau}_i(t)) \int_{t-\tau_i(t)}^t \xi^T(s) K^T ds R_{1ij} \int_{t-\tau_i(t)}^t K \xi(s) ds \\
&\quad + 2 \int_{t-\tau_i(t)}^t \xi^T(t) K^T R_{1ij} \int_{\theta}^t K \xi(s) ds d\theta
\end{aligned}$$

$$\begin{aligned}
& + \sum_{l \in S_1} \pi_{il}^{(j)} \int_{t-\tau_l(t)}^t \left(\int_{\theta}^t \xi^T(s) K^T ds \right) R_{1lj} \left(\int_{\theta}^t K \xi(s) ds \right) d\theta \\
& + \sum_{k \in S_2} \lambda_{jk} \int_{t-\tau_i(t)}^t \int_{\theta}^t \xi^T(s) K^T R_{1ik} K \xi(s) ds d\theta.
\end{aligned} \tag{3.3}$$

Using Lemma 2.3 and considering (2.5), it can be deduced that

$$\begin{aligned}
\mathcal{L}V_3(\xi_t, t, i, j) & \leq - (1 - \mu_i) \left(\int_{t-\tau_i(t)}^t \xi^T(s) K^T ds \right) R_{1ij} \left(\int_{t-\tau_i(t)}^t K \xi(s) ds \right) \\
& + \xi^T(t) K^T \left(\frac{1}{2} \tau_i^2 R_{1ij} \right) K \xi(t) + \int_{t-\tau_i(t)}^t \int_{\theta}^t \xi^T(s) K^T R_{1ij} K \xi(s) ds d\theta \\
& + \sum_{l \neq i} \pi_{il}^{(j)} \int_{t-\tau_l(t)}^t (t - \theta) \int_{\theta}^t \xi^T(s) K^T R_{1lj} K \xi(s) ds d\theta \\
& + \sum_{k \neq j} \lambda_{jk} \int_{t-\tau_i(t)}^t (t - \theta) \int_{\theta}^t \xi^T(s) K^T R_{1ik} K \xi(s) ds d\theta \\
& \leq - (1 - \mu_i) \left(\int_{t-\tau_i(t)}^t \xi^T(s) K^T ds \right) R_{1ij} \left(\int_{t-\tau_i(t)}^t K \xi(s) ds \right) \\
& + \xi^T(t) K^T \left(\frac{1}{2} \tau_i^2 R_{1ij} \right) K \xi(t) + \int_{t-\tau_i(t)}^t \int_{\theta}^t \xi^T(s) K^T R_{1ij} K \xi(s) ds d\theta \\
& + \sum_{l \neq i} \pi_{il}^{(j)} \int_{t-\tau_l(t)}^t \xi^T(s) K^T R_{1lj} K \xi(s) \int_{t-\tau_l(t)}^t (t - \theta) d\theta ds \\
& + \sum_{k \neq j} \lambda_{jk} \int_{t-\tau_i(t)}^t \xi^T(s) K^T R_{1ik} K \xi(s) \int_{t-\tau_i(t)}^t (t - \theta) d\theta ds \\
& \leq - (1 - \mu_i) \left(\int_{t-\tau_i(t)}^t \xi^T(s) K^T ds \right) R_{1ij} \left(\int_{t-\tau_i(t)}^t K \xi(s) ds \right) \\
& + \xi^T(t) K^T \left(\frac{1}{2} \tau_i^2 R_{1ij} \right) K \xi(t) + \int_{t-\tau}^t \int_{\theta}^t \xi^T(s) K^T R_{1ij} K \xi(s) ds d\theta \\
& + \sum_{l \neq i} \frac{1}{2} \tau_l^2 \pi_{il}^{(j)} \int_{t-\tau}^t \xi^T(s) K^T R_{1lj} K \xi(s) ds \\
& + \frac{1}{2} \sum_{k \neq j} \tau_i^2 \lambda_{jk} \int_{t-\tau_i(t)}^t \xi^T(s) K^T R_{1ik} K \xi(s) ds.
\end{aligned} \tag{3.4}$$

In addition, it is not difficult to get

$$\mathcal{L}V_4(\xi_t, t, i, j) = \tau^2 \dot{\xi}^T(t) K^T Z K \dot{\xi}(t) - \tau \int_{t-\tau}^t \dot{\xi}^T(s) K^T Z K \dot{\xi}(s) ds, \quad (3.5)$$

$$\begin{aligned} \mathcal{L}V_5(\xi_t, t, i, j) &\leq \tau \dot{\xi}^T(t) K^T R_2 K \dot{\xi}(t) - \int_{t-\tau}^t \dot{\xi}^T(s) K^T R_2 K \dot{\xi}(s) ds \\ &\quad + \tau_i \dot{\xi}^T(t) K^T G_{1i} K \dot{\xi}(t) - \frac{1}{\tau} \int_{t-\tau_i(t)}^t \dot{\xi}^T(s) K^T ds G_{1i} \int_{t-\tau_i(t)}^t K \dot{\xi}(s) ds \\ &\quad + \int_{-\tau}^0 \int_{t+\theta}^t \dot{\xi}^T(s) K^T \left(\sum_{l \in S_1, l \neq i} \pi_{il}^{(j)} G_{1i} \right) K \dot{\xi}(s) ds d\theta, \end{aligned} \quad (3.6)$$

$$\begin{aligned} \mathcal{L}V_6(\xi_t, t, i, j) &= \frac{1}{2} \tau^2 \dot{\xi}^T(t) K^T R_3 K \dot{\xi}(t) - \int_{t-\tau}^t \int_{\theta}^t \dot{\xi}^T(s) K^T R_3 K \dot{\xi}(s) ds d\theta \\ &\quad + \frac{1}{2} \tau^2 \dot{\xi}^T(t) K^T G_2 K \dot{\xi}(t) - \int_{-\tau}^0 \int_{t+\theta}^t \dot{\xi}^T(s) K^T G_2 K \dot{\xi}(s) ds d\theta. \end{aligned} \quad (3.7)$$

Next, following a similar method of [46], to (3.5), denote

$$\delta_1(t) = \int_{t-\tau_i(t)}^t K \dot{\xi}(s) ds, \quad \delta_2(t) = \int_{t-\tau}^{t-\tau_i(t)} K \dot{\xi}(s) ds. \quad (3.8)$$

When $0 < \tau_i(t) < \tau$, according to Jensen's inequality, we have that

$$\begin{aligned} \tau \int_{t-\tau}^t \dot{\xi}^T(s) K^T Z K \dot{\xi}(s) ds &= \tau \int_{t-\tau_i(t)}^t \dot{\xi}^T(s) K^T Z K \dot{\xi}(s) ds + \tau \int_{t-\tau}^{t-\tau_i(t)} \dot{\xi}^T(s) K^T Z K \dot{\xi}(s) ds \\ &\geq \frac{\tau}{\tau_i(t)} \delta_1(t)^T Z \delta_1(t) + \frac{\tau}{\tau - \tau_i(t)} \delta_2(t)^T Z \delta_2(t) \\ &= \delta_1(t)^T Z \delta_1(t) + \frac{\tau - \tau_i(t)}{\tau_i(t)} \delta_1(t)^T Z \delta_1(t) \\ &\quad + \delta_2(t)^T Z \delta_2(t) + \frac{\tau_i(t)}{\tau - \tau_i(t)} \delta_2(t)^T Z \delta_2(t). \end{aligned} \quad (3.9)$$

It is clear that [49]

$$\begin{bmatrix} \sqrt{\frac{\tau - \tau_i(t)}{\tau_i(t)}} \delta_1(t) \\ -\sqrt{\frac{\tau_i(t)}{\tau - \tau_i(t)}} \delta_2(t) \end{bmatrix}^T \begin{bmatrix} Z & S \\ * & Z \end{bmatrix} \begin{bmatrix} \sqrt{\frac{\tau - \tau_i(t)}{\tau_i(t)}} \delta_1(t) \\ -\sqrt{\frac{\tau_i(t)}{\tau - \tau_i(t)}} \delta_2(t) \end{bmatrix} \geq 0, \quad (3.10)$$

which implies

$$\frac{\tau - \tau_i(t)}{\tau_i(t)} \delta_1(t)^T Z \delta_1(t) + \frac{\tau_i(t)}{\tau - \tau_i(t)} \delta_2(t)^T Z \delta_2(t) \geq \delta_1(t)^T S \delta_2(t) + \delta_2(t)^T S^T \delta_1(t)^T. \quad (3.11)$$

Then, we can get from (3.9) and (3.11) that

$$\begin{aligned} \tau \int_{t-\tau}^t \xi^T(s) K^T Z K \xi(s) ds &\geq \delta_1(t)^T Z \delta_1(t) + \delta_2(t)^T Z \delta_2(t) + \delta_1(t)^T S \delta_2(t) + \delta_2(t)^T S^T \delta_1(t) \\ &= \begin{bmatrix} \delta_1(t) \\ \delta_2(t) \end{bmatrix}^T \begin{bmatrix} Z & S \\ * & Z \end{bmatrix} \begin{bmatrix} \delta_1(t) \\ \delta_2(t) \end{bmatrix}. \end{aligned} \quad (3.12)$$

Note that when $\tau_i(t) = 0$ or $\tau_i(t) = \tau$, we have $\delta_1(t) = 0$ or $\delta_2(t) = 0$, respectively. So relation (3.12) still holds. It is clear that (3.12) implies

$$-\tau \int_{t-\tau}^t \xi^T(s) K^T Z K \xi(s) ds \leq \chi^T(t) \Omega \chi(t), \quad (3.13)$$

where $\chi(t) = [\xi^T(t) \quad \xi^T(t - \tau_i(t)) K^T \quad \xi^T(t - \tau) K^T]^T$

$$\Omega = \begin{bmatrix} -K^T Z K & K^T (Z - S) & K^T S \\ * & -2Z + S + S^T & Z - S \\ * & * & -Z \end{bmatrix}. \quad (3.14)$$

The following equation is true for any matrix N with appropriate dimensions:

$$\begin{aligned} 0 &= 2\xi^T(t) K^T N \\ &\times \left[-K \xi(t) + K \bar{A}_{ij} \xi(t) + K \bar{A}_{1ij} K \xi(t - \tau_i(t)) + K \bar{A}_{2ij} K \int_{t-\tau_i(t)}^t \xi(s) ds + K \bar{B}_{ij} f(K \xi(t)) \right. \\ &\quad \left. + K \bar{E}_{ij} g(K \xi(t)) + K \bar{D}_{ij} w(t) \right]. \end{aligned} \quad (3.15)$$

From (2.4), it is clear that [2]

$$\begin{bmatrix} \xi(t) \\ f(K \xi(t)) \end{bmatrix}^T \begin{bmatrix} K^T \widehat{M}_1 K & K^T \widehat{M}_2 \\ * & I \end{bmatrix} \begin{bmatrix} \xi(t) \\ f(K \xi(t)) \end{bmatrix} \leq 0 \quad (3.16)$$

$$\begin{bmatrix} \xi(t) \\ g(K \xi(t)) \end{bmatrix}^T \begin{bmatrix} K^T \widehat{L}_1 K & K^T \widehat{L}_2 \\ * & I \end{bmatrix} \begin{bmatrix} \xi(t) \\ g(K \xi(t)) \end{bmatrix} \leq 0, \quad (3.17)$$

where $\widehat{M}_1 = (1/2)(M_1^T M_2 + M_2^T M_1)$, $\widehat{M}_2 = (-1/2)(M_1^T + M_2^T)$, $\widehat{L}_1 = (1/2)(L_1^T L_2 + L_2^T L_1)$, $\widehat{L}_2 = -(1/2)(L_1^T + L_2^T)$. It implies from (3.17) and (3.18) that there exist $\varepsilon_1 > 0$ and $\varepsilon_2 > 0$ such that

$$-\varepsilon_1 \begin{bmatrix} \xi(t) \\ f(K\xi(t)) \end{bmatrix}^T \begin{bmatrix} K^T \widehat{M}_1 K & K^T \widehat{M}_2 \\ * & I \end{bmatrix} \begin{bmatrix} \xi(t) \\ f(K\xi(t)) \end{bmatrix} \geq 0, \quad (3.18)$$

$$-\varepsilon_2 \begin{bmatrix} \xi(t) \\ g(K\xi(t)) \end{bmatrix}^T \begin{bmatrix} K^T \widehat{L}_1 K & K^T \widehat{L}_2 \\ * & I \end{bmatrix} \begin{bmatrix} \xi(t) \\ g(K\xi(t)) \end{bmatrix} \geq 0. \quad (3.19)$$

We define

$$\eta_i(t) = \begin{bmatrix} \xi^T(t) & \xi^T(t - \tau_i(t))K^T & \xi^T(t - \tau_i)K^T & \xi^T(t)K^T & \xi^T(t - \tau)K^T \\ \int_{t-\tau_i(t)}^t \xi^T(s)K^T ds & f^T(K\xi(t)) & g^T(K\xi(t)) \end{bmatrix}^T. \quad (3.20)$$

From the above discussion, we have

$$\begin{aligned} \mathcal{L}V(\xi_t, i, j) &\leq \begin{bmatrix} \eta_i(t) \\ w(t) \end{bmatrix}^T \begin{bmatrix} \Sigma_{ij} & \Phi_{1ij} \\ * & 0 \end{bmatrix} \begin{bmatrix} \eta_i(t) \\ w(t) \end{bmatrix} \\ &+ \int_{t-\tau_i(t)}^t \xi^T(s)K^T \left(\sum_{k \in S_2} \lambda_{jk} Q_{1ik} + \frac{\tau_i^2}{2} \sum_{k \neq j} \lambda_{jk} R_{1ik} + \pi_{ii}^{(j)} Q_{1ij} \right) K \xi(s) ds \\ &+ \int_{t-\tau}^t \xi^T(s)K^T \left[\sum_{l \in S_1, l \neq i} \pi_{il}^{(j)} \left(Q_{1lj} + Q_{2lj} + \frac{\tau_l^2}{2} R_{1lj} \right) - R_2 \right] K \xi(s) ds \\ &+ \int_{t-\tau_i}^t \xi^T(s)K^T \left(\sum_{k \in S_2} \lambda_{jk} Q_{2ik} + \pi_{ii}^{(j)} Q_{2ij} \right) K \xi(s) ds \\ &+ \int_{t-\tau}^t \int_{\theta}^t \xi^T(s)K^T (R_{1ij} - R_3) K \xi(s) ds d\theta \\ &+ \int_{-\tau}^0 \int_{t+\theta}^t \xi^T(s)K^T \left(\sum_{l \in S_1, l \neq i} \pi_{il}^{(j)} G_{1i} - G_2 \right) K \xi(s) ds d\theta, \end{aligned} \quad (3.21)$$

where

$$\Sigma_{ij} = \begin{bmatrix} \Sigma_{11} & \Sigma_{12} & 0 & (NK\bar{A}_{ij})^T & K^T S & P_{ij}\bar{A}_{2ij} & \Sigma_{17} & \Sigma_{18} \\ * & \Sigma_{22} & 0 & (NK\bar{A}_{1ij})^T & Z - S & 0 & 0 & \\ * & * & -Q_{2ij} & 0 & 0 & 0 & 0 & 0 \\ * & * & * & \Sigma_{44} & 0 & NK\bar{A}_{2ij} & NK\bar{B}_{ij} & NK\bar{E}_{ij} \\ * & * & * & * & -Z & 0 & 0 & 0 \\ * & * & * & * & * & \Sigma_{66} & 0 & 0 \\ * & * & * & * & * & * & -\varepsilon_1 I & 0 \\ * & * & * & * & * & * & * & -\varepsilon_2 I \end{bmatrix},$$

$$\Sigma_{11} = P_{ij}\bar{A}_i + \bar{A}_i^T P_{ij} + \sum_{l \in S_1} \pi_{il}^{(j)} P_{lj} + \sum_{k \in S_2} \lambda_{jk} P_{ik} \quad (3.22)$$

$$+ K^T \left(Q_{1ij} + Q_{2ij} + \tau R_2 - Z + \frac{1}{2} \tau_i^2 R_{1ij} + \frac{1}{2} \tau^2 R_3 + \tau_i G_{1i} + \frac{1}{2} \tau^2 G_2 \right)$$

$$\times K - \varepsilon_1 K^T \widehat{M}_1 K - \varepsilon_2 K^T \widehat{L}_1 K,$$

$$\Sigma_{12} = P_{ij}\bar{A}_{1ij} + K^T (Z - S), \quad \Sigma_{17} = P_{ij}\bar{B}_{ij} - \varepsilon_1 K^T \widehat{M}_2, \quad \Sigma_{18} = P_{ij}\bar{E}_{ij} - \varepsilon_2 K^T \widehat{L}_2,$$

$$\Sigma_{22} = -(1 - \mu_i) Q_{1ij} - 2Z + S + S^T, \quad \Sigma_{44} = \tau^2 Z - N - N^T,$$

$$\Sigma_{66} = -(1 - \mu_i) R_{1ij} - \frac{1}{\tau} G_{1i}, \quad \Phi_{1ij} = [\bar{D}_{ij}^T P_{ij} \ 0 \ 0 \ \bar{D}_{ij}^T K^T N^T \ 0 \ 0 \ 0 \ 0]^T.$$

Therefore, we have the following result for the H_∞ performance analysis.

Theorem 3.1. *Given scalars τ , τ_i , and μ_i , the filtering error system (2.7) is stochastically stable with an H_∞ performance γ for any time delay $\tau_i(t)$ satisfying (2.5), if there exist matrices $P_{ij} > 0$, $Q_{1ij} > 0$, $Q_{2ij} > 0$, $R_{1ij} > 0$, $R_2 > 0$, $R_3 > 0$, $Z > 0$, $G_{1i} > 0$, $G_2 > 0$, and matrices S , N such that for each $i \in S_1$, $j \in S_2$*

$$\begin{bmatrix} \Sigma_{ij} & \Phi_{1ij} & \Phi_{2ij} \\ * & -\gamma^2 I & 0 \\ * & * & -I \end{bmatrix} < 0, \quad (3.23)$$

$$\sum_{k \in S_2} \lambda_{jk} Q_{1ik} + \frac{\tau_i^2}{2} \sum_{k \neq j} \lambda_{jk} R_{1ik} + \pi_{ii}^{(j)} Q_{1ij} < 0, \quad (3.24)$$

$$\sum_{l \in S_1, l \neq i} \pi_{il}^{(j)} \left(Q_{1lj} + Q_{2lj} + \frac{\tau_l^2}{2} R_{1lj} \right) - R_2 < 0, \quad (3.25)$$

$$\sum_{k \in S_2} \lambda_{jk} Q_{2ik} + \pi_{ii}^{(j)} Q_{2ij} < 0, \quad (3.26)$$

$$R_{1ij} < R_3, \quad (3.27)$$

$$\sum_{l \in S_1, l \neq i} \pi_{il}^{(j)} G_{1i} < G_2, \quad (3.28)$$

where

$$\Phi_{2ij} = \begin{bmatrix} \bar{H}_i & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}^T. \quad (3.29)$$

Proof. Using the Schur complement formula to (3.23), it can be seen that inequality (3.23) is equivalent to

$$\begin{bmatrix} \Sigma_{ij} + \Phi_{2ij} \Phi_{2ij}^T & \Phi_{1ij} \\ * & -\gamma^2 I \end{bmatrix} < 0, \quad (3.30)$$

which implies $\Sigma_{ij} < 0$. Now, we show that the filtering error system (2.7) with $\omega(t) = 0$ is stochastically stable. If $\omega(t) = 0$, from (3.1), (3.21), (3.24)–(3.28), and $\Sigma_{ij} < 0$, there exists a scalar $\lambda > 0$ such that

$$\mathcal{L}V(\xi_t, t, i, j) \leq -\lambda \|x(t)\|^2. \quad (3.31)$$

Therefore, for any $T > 0$, by Dynkin's formula, we have

$$\mathcal{E}V(\xi_t, t, i, j) - \mathcal{E}V(\xi_0, 0, 0, 0) \leq -\lambda \mathcal{E} \int_0^T \|x(s)\|^2 ds, \quad (3.32)$$

which yields

$$\mathcal{E} \int_0^T \|x(s)\|^2 ds \leq \frac{1}{\lambda} \mathcal{E}V(\xi_0, 0, 0, 0) < \infty. \quad (3.33)$$

Thus, the filtering error system (2.7) with $\omega(t) = 0$ is stochastically stable by Definition 2.4.

In the sequel, we will deal with the H_∞ performance of the filtering error system (2.7). Using (3.30) and H_∞ performance, we have

$$\begin{aligned} & \mathcal{E} \left\{ \mathcal{L}V(\xi_t, t, i, j) + e^T(t)e(t) - \gamma^2 \omega^T(t)\omega(t) \right\} \\ & \leq \begin{bmatrix} \eta_i(t) \\ \omega(t) \end{bmatrix}^T \begin{bmatrix} \Sigma_{ij} + \Phi_{2ij} \Phi_{2ij}^T & \Phi_{1ij} \\ * & -\gamma^2 I \end{bmatrix} \begin{bmatrix} \eta_i(t) \\ \omega(t) \end{bmatrix} < 0. \end{aligned} \quad (3.34)$$

Noting that the zero initial condition, then it follows from (3.34) that

$$\begin{aligned} J &= \mathcal{E} \left\{ \int_0^\infty \left[e^T(t) e(t) - \gamma^2 \omega^T(t) \omega(t) \right] dt \right\} \\ &\leq \mathcal{E} \left\{ \int_0^\infty \left[e^T(t) e(t) - \gamma^2 \omega^T(t) \omega(t) + \mathcal{L}V(\xi_t, t, i, j) \right] dt \right\} < 0. \end{aligned} \quad (3.35)$$

Hence, if (3.23)–(3.28) hold, $J < 0$ can be guaranteed. That is, $\|e\|_2 \leq \gamma \|\omega\|_2$ for all nonzero $\omega(t)$. Therefore, the filtering error system (2.7) is stochastically stable with the H_∞ performance γ by Definition 2.5. This completes the proof. $\square$

Remark 3.2. A new stochastic stability criterion is obtained in Theorem 3.1 by constructing a novel mode-dependent Lyapunov functional. The Lyapunov functional in this paper uses all information about r_t , σ_t and $\tau(t, r_t)$. The Lyapunov matrices $P(r_t, \sigma_t)$, $Q_1(r_t, \sigma_t)$, $Q_2(r_t, \sigma_t)$, and $R_1(r_t, \sigma_t)$ depend on both the system mode r_t and the higher-level Markovian chain σ_t . Compared with the mode-independent Lyapunov matrices [40, 42], the mode-dependent Lyapunov matrices can reduce the conservativeness since they provide additional degrees of freedom which are very important for deriving LMIs solutions in general. Hence, the Lyapunov functional in this paper is more general and the condition on stability is more applicable.

Remark 3.3. It should be pointed out that the aim of the introduction of $V_3(\xi_t, t, i, j)$ is to propose a stability condition which depends not only on the delay upper bound τ , but also on the subsystems' delay upper bounds τ_i , in other words, if $V_3(\xi_t, t, i, j)$ is not considered, the obtained stability condition only depends on the delay upper bound τ . Hence, the introduction of $V_3(\xi_t, t, i, j)$ may reduce some conservativeness.

Based on Theorem 3.1, the H_∞ filter synthesis problem can be developed in terms of LMIs for the system (2.1) with higher-level Markovian chain.

Theorem 3.4. Consider the systems (2.1). Given scalars τ , τ_i and μ_i , the filtering error system (2.7) is stochastically stable with an H_∞ performance γ for any time delay $\tau_i(t)$ satisfying (2.5), if there exist matrices $P_{1ij} > 0$, $Q_{1ij} > 0$, $Q_{2ij} > 0$, $R_{1ij} > 0$, $R_2 > 0$, $R_3 > 0$, $Z > 0$, $G_{1i} > 0$, $G_2 > 0$, $S_{ij} > 0$, $U_{lij} > 0$, $V_{kij} > 0$, S_{lij} , T_{kij} , $\bar{A}_{Fij}$, $\bar{B}_{Fij}$, $\bar{C}_{Fij}$, and matrices S , N such that for each $i \in S_1$, $j \in S_2$

$$\begin{bmatrix} \bar{\Sigma}_{11} & \bar{\Sigma}_{12} & \bar{\Sigma}_{13} & 0 & (NA_i)^T & S & \bar{\Sigma}_{14} & \bar{\Sigma}_{15} & \bar{\Sigma}_{16} & \bar{\Sigma}_{17} & H_i^T \\ * & \bar{\Sigma}_{22} & \bar{\Sigma}_{23} & 0 & 0 & 0 & \bar{\Sigma}_{24} & S_{ij}B_i & \bar{B}_{Fij}E_i & \bar{\Sigma}_{25} & -\bar{C}_{Fij}^T \\ * & * & \bar{\Sigma}_{33} & 0 & (N\bar{A}_{1i})^T & Z-S & 0 & 0 & 0 & 0 & 0 \\ * & * & * & -Q_{2ij} & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & \bar{\Sigma}_{55} & 0 & NA_{2i} & NB_i & 0 & ND_{1i} & 0 \\ * & * & * & * & * & -Z & 0 & 0 & 0 & 0 & 0 \\ * & * & * & * & * & * & \bar{\Sigma}_{77} & 0 & 0 & 0 & 0 \\ * & * & * & * & * & * & * & -\varepsilon_1 I & 0 & 0 & 0 \\ * & * & * & * & * & * & * & * & -\varepsilon_2 I & 0 & 0 \\ * & * & * & * & * & * & * & * & * & -\gamma^2 I & 0 \\ * & * & * & * & * & * & * & * & * & * & -I \end{bmatrix} < 0, \quad (3.36)$$

$$\sum_{k \in S_2} \lambda_{jk} Q_{1ik} + \frac{\tau_i^2}{2} \sum_{k \neq j} \lambda_{jk} R_{1ik} + \pi_{ii}^{(j)} Q_{1ij} < 0, \quad (3.37)$$

$$\sum_{l \in S_1, l \neq i} \pi_{il}^{(j)} \left(Q_{1lj} + Q_{2lj} + \frac{\tau_l^2}{2} R_{1lj} \right) - R_2 < 0, \quad (3.38)$$

$$\sum_{k \in S_2} \lambda_{jk} Q_{2ik} + \pi_{ii}^{(j)} Q_{2ij} < 0, \quad (3.39)$$

$$R_{1ij} < R_3, \quad (3.40)$$

$$\sum_{l \in S_1, l \neq i} \pi_{il}^{(j)} G_{1i} < G_2, \quad (3.41)$$

where

$$\begin{aligned} \bar{\Sigma}_{11} &= P_{1ij} A_i + A_i^T P_{1ij} + \bar{B}_{Fij} C_i + C_i^T \bar{B}_{Fij}^T + \sum_{l \in S_1} \pi_{il}^{(j)} P_{1lj} + \sum_{k \in S_2} \lambda_{jk} P_{1ik} + Q_{1ij} + Q_{2ij} \\ &\quad + \frac{1}{2} \tau_i^2 R_{1ij} + \tau R_2 + \frac{1}{2} \tau^2 R_3 - Z + \tau_i G_{1i} + \frac{1}{2} \tau^2 G_2 - \varepsilon_1 \widehat{M}_1 - \varepsilon_2 \widehat{L}_1, \\ \bar{\Sigma}_{12} &= \bar{A}_{Fij} + A_i^T S_{ij}^T + C_i^T \bar{B}_{Fij}^T + \left(\pi_{ii}^{(j)} + \lambda_{jj} \right) S_{ij} + \sum_{l \neq i} \pi_{il}^{(j)} S_{lij} + \sum_{k \neq j} \lambda_{jk} T_{kij}, \\ \bar{\Sigma}_{13} &= P_{1ij} A_{1i} + \bar{B}_{Fij} C_{1i} + Z - S, \quad \bar{\Sigma}_{14} = P_{1ij} A_{2i} + \bar{B}_{Fij} C_{2i}, \quad \bar{\Sigma}_{15} = P_{1ij} B_i - \varepsilon_1 \widehat{M}_2, \\ \bar{\Sigma}_{16} &= \bar{B}_{Fij} E_i - \varepsilon_2 \widehat{L}_2, \quad \bar{\Sigma}_{17} = P_{1ij} D_{1i} + \bar{B}_{Fij} D_{2i}, \\ \bar{\Sigma}_{22} &= \bar{A}_{Fij} + \bar{A}_{Fij}^T + \left(\pi_{ii}^{(j)} + \lambda_{jj} \right) S_{ij} + \sum_{l \in S_1, l \neq i} \pi_{il}^{(j)} U_{lij} + \sum_{k \in S_2, k \neq j} \lambda_{jk} V_{kij}, \\ \bar{\Sigma}_{23} &= S_{ij} A_{1i} + \bar{B}_{Fij} C_{1i}, \quad \bar{\Sigma}_{24} = S_{ij} A_{2i} + \bar{B}_{Fij} C_{2i}, \quad \bar{\Sigma}_{25} = S_{ij} D_{1i} + \bar{B}_{Fij} D_{2i}, \\ \bar{\Sigma}_{33} &= - (1 - \mu_i) Q_{1ij} - 2Z + S + S^T, \quad \bar{\Sigma}_{55} = \tau^2 Z - N - N^T, \quad \bar{\Sigma}_{77} = - (1 - \mu_i) R_{1ij} - \frac{1}{\tau} G_{1i}. \end{aligned} \quad (3.42)$$

In this case, the parameters of the desired filter can be chosen by

$$A_{Fij} = S_{ij}^{-1} \bar{A}_{Fij}, \quad B_{Fij} = S_{ij}^{-1} \bar{B}_{Fij}, \quad C_{Fij} = \bar{C}_{Fij}. \quad (3.43)$$

Proof. For each $r_t = i \in S_1$, $\sigma_t = j \in S_2$, we define a matrix $P_{ij} > 0$ by $P_{ij} = \begin{bmatrix} P_{1ij} & P_{2ij} \\ * & P_{3ij} \end{bmatrix}$. By invoking a small perturbation, if necessary, we can assume that P_{2ij} and P_{3ij} are nonsingular. Thus, we can introduce the following invertible matrix $J = \begin{bmatrix} I & 0 \\ 0 & P_{3ij}^{-1} P_{2ij}^T \end{bmatrix}$. Pre- and

postmultiplying (3.23) by $\text{diag}[J^T, I, I, I, I, I, I, I, I, I]$ and its transpose, respectively. Then, we define

$$\begin{aligned} S_{ij} &= P_{2ij} P_{3ij}^{-1} P_{2ij}^T, & \bar{A}_{Fij} &= P_{2ij} A_{Fij} P_{3ij}^{-1} P_{2ij}^T, & \bar{B}_{Fij} &= P_{2ij} B_{Fij}, & \bar{C}_{Fij} &= C_{Fij} P_{3ij}^{-1} P_{2ij}^T, \\ S_{lij} &= P_{2lj} P_{3ij}^{-1} P_{2ij}^T \quad (l \neq i), & T_{kij} &= P_{2ik} P_{3ij}^{-1} P_{2ij}^T \quad (k \neq j), & U_{lij} &= P_{2ij} P_{3ij}^{-T} P_{3lj} P_{3ij}^{-1} P_{2ij}^T \quad (l \neq i), \\ V_{kij} &= P_{2ij} P_{3ij}^{-T} P_{3ik} P_{3ij}^{-1} P_{2ij}^T \quad (k \neq j). \end{aligned} \quad (3.44)$$

It is easy to obtain (3.36).

On the other hand, according to (3.44), we have

$$A_{Fij} = P_{2ij}^{-1} \bar{A}_{Fij} P_{2ij}^{-T} P_{3ij}, \quad B_{Fij} = P_{2ij}^{-1} \bar{B}_{Fij}, \quad C_{Fij} = \bar{C}_{Fij} P_{2ij}^{-T} P_{3ij}. \quad (3.45)$$

From (2.6), the transfer function from measured output $y(t)$ to estimated signal $\hat{z}(t)$ can be described by

$$\begin{aligned} T_{\hat{z}y} &= C_{Fij} \left(sI - A_{Fij} \right)^{-1} B_{Fij} \\ &= \bar{C}_{Fij} P_{2ij}^{-T} P_{3ij} \left(sI - P_{2ij}^{-1} \bar{A}_{Fij} P_{2ij}^{-T} P_{3ij} \right)^{-1} P_{2ij}^{-1} \bar{B}_{Fij} \\ &= \bar{C}_{Fij} \left(sI - S_{ij}^{-1} \bar{A}_{Fij} \right)^{-1} S_{ij}^{-1} \bar{B}_{Fij}. \end{aligned} \quad (3.46)$$

Therefore, we can conclude from (3.46) that the parameters of the filter in (2.6) can be constructed by (3.43). This completes the proof. $\square$

Remark 3.5. It should be pointed out that some existing work in control and filter design of Markovian jump systems, the Lyapunov matrix P_i is assumed to be diagonal matrix, for example, see [42]. It is well known that such assumption can lead to much more conservative result. Although the first diagonal element Σ_{11} in (3.23) includes P_{ij} , P_{lj} , and P_{ik} in this paper, P_{ij} is not assumed to be diagonal matrices.

Remark 3.6. In [30–32, 38], the authors have achieved some excellent work of Markovian jump singular systems. Due to the presence of the singular matrix E , the issues of stability and control of such systems are more difficult and complicated. However, there is no results on piecewise homogeneous Markovian jump singular systems in the existing work, and the problem of control for such system is an interesting issue.

Remark 3.7. Theorem 3.4 solves the filtering problem of a class of piecewise homogeneous Markovian jump nonlinear systems. The obtained conditions are formulated in terms of LMIs, which could be easily checked by using the LMI toolbox in Matlab. The feasible solutions to the conditions presented in Theorem 3.4 will depend on both the mode r_t and the higher-level Markovian chain σ_t , which ensure that the error system is stochastically stable. A numerical example verifies the validity of the designed filter in Section 4.

4. A Numerical Example

In this section, a numerical example will be presented to show the validity of the main results derived above.

Example 4.1. Let us consider the stochastic system (2.1) with the following system of matrices:

$$\begin{aligned}
 A(1) &= \begin{bmatrix} -8 & 0 \\ 1 & -12 \end{bmatrix}, & A_1(1) &= \begin{bmatrix} 1 & 0.3 \\ 1 & 1 \end{bmatrix}, & A_2(1) &= \begin{bmatrix} 0.4 & 0 \\ 0 & -0.4 \end{bmatrix}, \\
 B(1) &= \begin{bmatrix} 0.7 & 0.8 \\ 0.1 & 0.6 \end{bmatrix}, & D_1(1) &= \begin{bmatrix} 0.7 \\ 0.1 \end{bmatrix}, & M_1 = L_1 &= \begin{bmatrix} 0.01 & 0.01 \\ 0.01 & 0.02 \end{bmatrix}, \\
 M_2 = L_2 &= \begin{bmatrix} -0.01 & 0.01 \\ -0.03 & -0.02 \end{bmatrix}, & C(1) &= [1.9 \quad -2.1], & C_1(1) &= [1.5 \quad 0], \\
 C_2(1) &= [1 \quad 1], & E(1) &= [0.8 \quad 0.6], & D_2(1) &= 0.8, & H(1) &= [0.4 \quad 0.2], \\
 A(2) &= \begin{bmatrix} -9 & 0 \\ 0 & -9 \end{bmatrix}, & A_1(2) &= \begin{bmatrix} 0.8 & 0.6 \\ 1 & 0.8 \end{bmatrix}, & A_2(2) &= \begin{bmatrix} -0.8 & 0 \\ 0 & -0.6 \end{bmatrix}, \\
 B(2) &= \begin{bmatrix} 0.9 & 1 \\ 2.3 & 0.6 \end{bmatrix}, & D_1(2) &= \begin{bmatrix} 0.2 \\ 0.2 \end{bmatrix}, & M_1 = L_1 &= \begin{bmatrix} 0.01 & 0.01 \\ 0.01 & 0.02 \end{bmatrix}, \\
 M_2 = L_2 &= \begin{bmatrix} -0.01 & 0.01 \\ -0.03 & -0.02 \end{bmatrix}, & C(2) &= [1.8 \quad -2.2], & C_1(2) &= [1.2 \quad 0.1], \\
 C_2(2) &= [1 \quad -0.8], & E(2) &= [0.8 \quad 0.6], & D_2(2) &= 1, & H(2) &= [0.9 \quad 0.1].
 \end{aligned} \tag{4.1}$$

The piecewise homogeneous TP matrices are given as

$$\Pi^1 = \begin{bmatrix} -0.5 & 0.5 \\ 0.6 & -0.6 \end{bmatrix}, \quad \Pi^2 = \begin{bmatrix} -0.7 & 0.7 \\ 0.4 & -0.4 \end{bmatrix}, \quad \Pi^3 = \begin{bmatrix} -0.8 & 0.8 \\ 0.6 & -0.6 \end{bmatrix}. \tag{4.2}$$

The HTP matrix for the Markovian chain is considered as follows:

$$\Lambda = \begin{bmatrix} -0.8 & 0.4 & 0.4 \\ 0.4 & -0.9 & 0.5 \\ 0.7 & 0.8 & -1.5 \end{bmatrix}. \tag{4.3}$$

Figure 1: Variation of TP matrices subject to HTP.

In this example, we assume $\tau_1 = \tau_2 = 1$, $\mu_1 = 0.8$, $\mu_2 = 0.5$. For $\gamma = 1.2$. By solving LMIs (3.36)–(3.41), the filter matrices are obtained as

$$\begin{aligned}
 A_{F_{11}} &= \begin{bmatrix} -7.6750 & -2.3822 \\ -3.7133 & -4.8336 \end{bmatrix}, & B_{F_{11}} &= \begin{bmatrix} 0.0496 \\ 0.3182 \end{bmatrix}, & C_{F_{11}} &= [0.0037 \quad 1.3061], \\
 A_{F_{12}} &= \begin{bmatrix} -10.9509 & -3.4284 \\ -2.9982 & -4.2265 \end{bmatrix}, & B_{F_{12}} &= \begin{bmatrix} 0.7322 \\ 0.1760 \end{bmatrix}, & C_{F_{12}} &= [-0.0053 \quad -0.0017], \\
 A_{F_{13}} &= \begin{bmatrix} -11.2973 & -4.8499 \\ -5.0689 & -5.7131 \end{bmatrix}, & B_{F_{13}} &= \begin{bmatrix} 1.0209 \\ 0.7196 \end{bmatrix}, & C_{F_{13}} &= [-0.0041 \quad -0.0029], \\
 A_{F_{21}} &= \begin{bmatrix} -5.5850 & -6.2702 \\ -4.3917 & -15.3643 \end{bmatrix}, & B_{F_{21}} &= \begin{bmatrix} 0.4144 \\ 0.9799 \end{bmatrix}, & C_{F_{21}} &= [0.0002 \quad 1.2670], \\
 A_{F_{22}} &= \begin{bmatrix} -6.2896 & -4.2309 \\ -4.7375 & -10.6039 \end{bmatrix}, & B_{F_{22}} &= \begin{bmatrix} -0.0779 \\ -0.3519 \end{bmatrix}, & C_{F_{22}} &= [-0.0142 \quad -0.0107], \\
 A_{F_{23}} &= \begin{bmatrix} -7.9621 & -6.4413 \\ -6.1046 & -16.3128 \end{bmatrix}, & B_{F_{23}} &= \begin{bmatrix} -0.0841 \\ -0.3711 \end{bmatrix}, & C_{F_{23}} &= [-0.0150 \quad -0.0117].
 \end{aligned} \tag{4.4}$$

For simulation purposes, we assume the initial condition $x(0) = [0.1 \quad 0.1]^T$ and $\omega(t) = 1/(0.5 + 1.2t)$. The time delays are $\tau_1(t) = 0.2 + 0.8 \sin(t)$, $\tau_2(t) = 0.5 + 0.5 \cos(t)$. The nonlinear functions $f(x(t))$ and $g(x(t))$ are selected as

$$f(x(t)) = g(x(t)) = \begin{bmatrix} 0.02x_1(t)\sin^2(x_1(t)) - 0.01(x_1(t) - x_2(t)) \\ -0.01x_1(t) \end{bmatrix}, \tag{4.5}$$

Figures 1–5 illustrate the simulation results. A case for stochastic variation with HTP matrix is shown in Figure 1, and possible realizations of the Markov jumping mode of system

Figure 2: System jumping mode.

Figure 3: The state responses of $x_1(t)$ and $\hat{x}_1(t)$.

and delay are plotted in Figure 2, where the initial modes are assumed to be $r_0 = 1$ and $\sigma_0 = 1$. Figure 3 shows the state responses of real states $x_1(t)$ and its estimate $\hat{x}_1(t)$. Figure 4 shows the state responses of real states $x_2(t)$ and its estimate $\hat{x}_2(t)$. Figure 5 is the simulation result of the estimation error response of $e(t)$. The simulation results demonstrate that the designed H_∞ filters are feasible and effective.

Figure 4: The state responses of $x_2(t)$ and $\hat{x}_2(t)$.

Figure 5: The estimation error response of $e(t)$.

5. Conclusion

The problem of H_∞ filtering for a class of Markovian jump nonlinear systems is investigated in this paper. The piecewise homogeneous Markovian chain and mode-dependent time-varying delays are considered in the model. By using the Lyapunov-Krasovskii functional, mixed mode-dependent sufficient conditions are developed to design stable filters. A numerical example demonstrates the effectiveness of the given method.

Acknowledgments

This work was supported by the fund of Sichuan Provincial Key Laboratory of signal and INFORMATION PROCESSING, Xihua University (SZJJ2009-002), the Fundamental Research Funds for the Central Universities (103.1.2E022050205), and the National Basic Research Program of China (2010CB732501).

References

- [1] Z. Wang and K. Burnham, "Robust filtering for a class of stochastic uncertain nonlinear timedelay systems via exponential state estimation," *IEEE Transactions on Signal Process*, vol. 49, pp. 794–804, 2001.
- [2] Z. Wang, Y. Liu, and X. Liu, " H_∞ filtering for uncertain stochastic time-delay systems with sector-bounded nonlinearities," *Automatica*, vol. 44, no. 5, pp. 1268–1277, 2008.
- [3] D. Zhang and L. Yu, " H_∞ filtering for linear neutral systems with mixed time-varying delays and nonlinear perturbations," *Journal of the Franklin Institute*, vol. 347, no. 7, pp. 1374–1390, 2010.
- [4] M. S. Mahmoud, "New filter design for linear time-delay systems," *Linear Algebra and Its Applications*, vol. 434, no. 4, pp. 1080–1093, 2011.
- [5] C. E. de Souza and D. F. Coutinho, "Parameter-dependent robust H_∞ filtering for linear systems with time-varying delay and rational parameter uncertainty," *IMA Journal of Mathematical Control and Information*, vol. 28, no. 2, pp. 203–224, 2011.
- [6] X.-G. Guo and G.-H. Yang, "Delay-dependent reliable H_∞ filtering for sector-bounded nonlinear continuous-time systems with time-varying state delays and sensor failures," *International Journal of Systems Science*, vol. 43, no. 1, pp. 117–131, 2012.
- [7] M. S. Mahmoud and P. Shi, *Methodologies for Control of Jump Time-Delay Systems*, Kluwer Academic Publishers, Dordrecht, the Netherlands, 2003.
- [8] H. Shao, "Delay-range-dependent robust H^∞ filtering for uncertain stochastic systems with mode-dependent time delays and Markovian jump parameters," *Journal of Mathematical Analysis and Applications*, vol. 342, no. 2, pp. 1084–1095, 2008.
- [9] Q. X. Zhu and J. D. Cao, "Exponential stability of stochastic neural networks with both Markovian jump parameters and mixed time delays," *IEEE Transactions on Systems, Man, and Cybernetics B*, vol. 41, pp. 341–353, 2011.
- [10] X.-G. Yan, S. K. Spurgeon, and C. Edwards, "Sliding mode control for time-varying delayed systems based on a reduced-order observer," *Automatica*, vol. 46, no. 8, pp. 1354–1362, 2010.
- [11] K. Ramakrishnan and G. Ray, "Robust stability criterion for Markovian jump systems with nonlinear perturbations and mode-dependent time delays," *International Journal of General Systems*, vol. 41, pp. 373–393, 2012.
- [12] X. Mao, "Exponential stability of stochastic delay interval systems with Markovian switching," *IEEE Transactions on Automatic Control*, vol. 47, no. 10, pp. 1604–1612, 2002.
- [13] L. Hu, P. Shi, and B. Huang, "Stochastic stability and robust control for sampled-data systems with Markovian jump parameters," *Journal of Mathematical Analysis and Applications*, vol. 313, no. 2, pp. 504–517, 2006.
- [14] L. Zhang and E.-K. Boukas, "Stability and stabilization of Markovian jump linear systems with partly unknown transition probabilities," *Automatica*, vol. 45, no. 2, pp. 463–468, 2009.
- [15] W. Han, Y. Liu, and L. Wang, "Robust exponential stability of Markovian jumping neural networks with mode-dependent delay," *Communications in Nonlinear Science and Numerical Simulation*, vol. 15, no. 9, pp. 2529–2535, 2010.
- [16] X. Zhao, M. Ling, and Q. Zeng, "Delay-dependent stability criterion and H_∞ analysis for Markovian jump systems with time-varying delays," *Asian Journal of Control*, vol. 13, no. 2, pp. 232–239, 2011.
- [17] Z. Fei, H. Gao, and P. Shi, "New results on stabilization of Markovian jump systems with time delay," *Automatica*, vol. 45, no. 10, pp. 2300–2306, 2009.
- [18] H. Li, Q. Zhou, B. Chen, and H. Liu, "Parameter-dependent robust stability for uncertain Markovian jump systems with time delay," *Journal of the Franklin Institute*, vol. 348, no. 4, pp. 738–748, 2011.
- [19] S. Xu, J. Lam, and X. Mao, "Delay-dependent H_∞ control and filtering for uncertain Markovian jump systems with time-varying delays," *IEEE Transactions on Circuits and Systems. I*, vol. 54, no. 9, pp. 2070–2077, 2007.

- [20] J. Dong and G. Yang, "Fuzzy controller design for Markovian jump nonlinear systems," *International Journal of Control, Automation and Systems*, vol. 5, pp. 712–717, 2007.
- [21] Y. Guo and F. Zhu, "New results on stability and stabilization of Markovian jump systems with partly known transition probabilities," *Mathematical Problems in Engineering*, vol. 2012, Article ID 869842, 11 pages, 2012.
- [22] P. Balasubramaniam, V. Vembarasan, and R. Rakkiyappan, "Delay-dependent robust exponential state estimation of Markovian jumping fuzzy Hopfield neural networks with mixed random time-varying delays," *Communications in Nonlinear Science and Numerical Simulation*, vol. 16, no. 4, pp. 2109–2129, 2011.
- [23] Z. Shu, J. Lam, and J. Xiong, "Static output-feedback stabilization of discrete-time Markovian jump linear systems: a system augmentation approach," *Automatica*, vol. 46, no. 4, pp. 687–694, 2010.
- [24] Z. Wang, L. Huang, and X. Yang, " H_∞ performance for a class of uncertain stochastic nonlinear Markovian jump systems with time-varying delay via adaptive control method," *Applied Mathematical Modelling*, vol. 35, no. 4, pp. 1983–1993, 2011.
- [25] J. Xia, C. Sun, and B. Zhang, "New robust H_∞ control for uncertain stochastic Markovian jumping systems with mixed delays based on decoupling method," *Journal of the Franklin Institute*, vol. 349, no. 3, pp. 741–769, 2012.
- [26] G. Chen and Y. Shen, "Robust Reliable H_∞ control for nonlinear stochastic Markovian jump systems," *Mathematical Problems in Engineering*, vol. 2012, Article ID 431576, 16 pages, 2012.
- [27] H. Zhao, Q. Chen, and S. Xu, " H_∞ guaranteed cost control for uncertain Markovian jump systems with mode-dependent distributed delays and input delays," *Journal of the Franklin Institute*, vol. 346, no. 10, pp. 945–957, 2009.
- [28] H. R. Karimi, "Robust delay-dependent H_∞ control of uncertain time-delay systems with mixed neutral, discrete, and distributed time-delays and Markovian switching parameters," *IEEE Transactions on Circuits and Systems. I*, vol. 58, no. 8, pp. 1910–1923, 2011.
- [29] Z. Wu, P. Shi, H. Su, and J. Chu, "Passivity analysis for discrete-time stochastic Markovian jump neural networks with mixed time-delays," *IEEE Transactions on Neural Networks*, vol. 22, pp. 1566–1575, 2011.
- [30] L. Wu, P. Shi, and H. Gao, "State estimation and sliding-mode control of Markovian jump singular systems," *IEEE Transactions on Automatic Control*, vol. 55, no. 5, pp. 1213–1219, 2010.
- [31] L. Wu and D. W. C. Ho, "Sliding mode control of singular stochastic hybrid systems," *Automatica*, vol. 46, no. 4, pp. 779–783, 2010.
- [32] L. Wu, X. Su, and P. Shi, "Sliding mode control with bounded L_2 gain performance of Markovian jump singular time-delay systems," *Automatica*, vol. 48, no. 8, pp. 1929–1933, 2012.
- [33] S. K. Nguang, W. Assawinchaichote, and P. Shi, " H_∞ filter for uncertain Markovian jump nonlinear systems: an LMI approach," *Circuits, Systems, and Signal Processing*, vol. 26, no. 6, pp. 853–874, 2007.
- [34] Z. Wu, H. Su, and J. Chu, "Delay-dependent H_∞ filtering for singular Markovian jump time-delay systems," *Signal Process*, vol. 90, pp. 1815–1824, 2010.
- [35] L. Wu, P. Shi, H. Gao, and C. Wang, " H_∞ filtering for 2D Markovian jump systems," *Automatica*, vol. 44, no. 7, pp. 1849–1858, 2008.
- [36] H. Liu, D. W. C. Ho, and F. Sun, "Design of H_∞ filter for Markov jumping linear systems with non-accessible mode information," *Automatica*, vol. 44, no. 10, pp. 2655–2660, 2008.
- [37] X. M. Yao, L. G. Wu, and W. X. Zheng, "Quantized H_∞ filtering for Markovian jump LPV systems with intermittent measurements," *International Journal of Robust and Nonlinear Control*. In press.
- [38] X. Yao, L. Wu, and W. X. Zheng, "Fault detection filter design for Markovian jump singular systems with intermittent measurements," *IEEE Transactions on Signal Processing*, vol. 59, no. 7, pp. 3099–3109, 2011.
- [39] Y. Ding, H. Zhu, S. Zhong, and Y. Zhang, " $L_2 - L_\infty$ filtering for Markovian jump systems with time-varying delays and partly unknown transition probabilities," *Communications in Nonlinear Science and Numerical Simulation*, vol. 17, pp. 3070–3081, 2012.
- [40] G. Wang, "Partially mode-dependent design of H_∞ filter for stochastic Markovian jump systems with mode-dependent time delays," *Journal of Mathematical Analysis and Applications*, vol. 383, no. 2, pp. 573–584, 2011.
- [41] Z. Lin, Y. Lin, and W. Zhang, " H_∞ filtering for non-linear stochastic Markovian jump systems," *IET Control Theory & Applications*, vol. 4, no. 12, pp. 2743–2756, 2010.
- [42] H. Yan, M. Q.-H. Meng, H. Zhang, and H. Shi, "Robust H_∞ exponential filtering for uncertain stochastic time-delay systems with Markovian switching and nonlinearities," *Applied Mathematics and Computation*, vol. 215, no. 12, pp. 4358–4369, 2010.

- [43] H. Shen, S. Xu, J. Zhou, and J. Lu, "Fuzzy H_∞ filtering for nonlinear Markovian jump neutral systems," *International Journal of Systems Science*, vol. 42, no. 5, pp. 767–780, 2011.
- [44] L. Zhang, " H_∞ estimation for discrete-time piecewise homogeneous Markov jump linear systems," *Automatica*, vol. 45, no. 11, pp. 2570–2576, 2009.
- [45] L. J. Chen, Y. Leng, H. F. Guo, P. Shi, and L. X. Zhang, " H_∞ control of a class of discrete-time Markov jump linear systems with piecewise-constant TPs subject to average dwell time switching," *Journal of The Franklin Institute*, vol. 349, pp. 1989–2003, 2012.
- [46] Z. Wu, J. Park, H. Su, and J. Chu, "Stochastic stability analysis of piecewise homogeneous Markovian jump neural networks with mixed time-delays," *Journal of The Franklin Institute*, vol. 349, pp. 2136–2150, 2012.
- [47] M. Iosifescu, *Finite Markov Processes and Their Applications*, John Wiley & Sons, Chichester, UK, 1980, Wiley Series in Probability and Mathematical Statistics.
- [48] K. Q. Gu, "An integral inequality in the stability problem of time-delay systems," in *Proceedings of the 39th IEEE Conference on Decision Control*, pp. 2805–2810, Sydney, Australia, 2000.
- [49] P. Park, J. W. Ko, and C. Jeong, "Reciprocally convex approach to stability of systems with time-varying delays," *Automatica*, vol. 47, no. 1, pp. 235–238, 2011.