Research Article

Syngas Production from Pyrolysis of Nine Composts Obtained from Nonhybrid and Hybrid Perennial Grasses

Adéla Hlavsová,¹ Agnieszka Corsaro,¹ Helena Raclavská,^{1,2} Dagmar Juchelková,^{1,3}
Hana Škrobánková,² and Jan Frydrych⁴

¹ ENET-Energy Units for Utilization of Non-Traditional Energy Sources, VŠB-Technical University of Ostrava, 17. listopadu 15/2172, 708 33 Ostrava-Poruba, Czech Republic

² Institute of Geological Engineering, Faculty of Mining and Geology, VŠB-Technical University of Ostrava, 17. listopadu 15/2172, 708 33 Ostrava-Poruba, Czech Republic

³ Department of Energy, Faculty of Mechanical Engineering, VŠB-Technical University of Ostrava, 17. listopadu 15/2172, 708 33 Ostrava-Poruba, Czech Republic

⁴ OSEVA PRO s.r.o., Grass Research Institute, Rožnov-Zubří, Hamerská 698, 756 54 Zubří, Czech Republic

Correspondence should be addressed to Adéla Hlavsová; adela.hlavsova@vsb.cz

Received 6 March 2014; Revised 9 June 2014; Accepted 13 June 2014; Published 1 July 2014

Academic Editor: Bin Cao

Copyright © 2014 Adéla Hlavsová et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

A pyrolysis of compost for the production of syngas with an explicit $H_2/CO = 2$ or $H_2/CO = 3$ was investigated in this study. The composts were obtained from nonhybrid (perennial) grasses (NHG) and hybrid (perennial) grasses (HG). Discrepancies in H_2 evolution profiles were found between NHG and HG composts. In addition, positive correlations for NHG composts were obtained between (i) H_2 yield and lignin content, (ii) H_2 yield and potassium content, and (iii) CO yield and cellulose content. All composts resulted in $H_2/CO = 2$ and five of the nine composts resulted in $H_2/CO = 3$. Exceptionally large higher heating values (HHVs) of pyrolysis gas, very close to HHVs of feedstock, were obtained for composts made from mountain brome (MB, 16.23 MJ/kg), hybrid Becva (FB, 16.45 MJ/kg), and tall fescue (TF, 17.43 MJ/kg). The MB and FB composts resulted in the highest syngas formation with $H_2/CO = 2$, whereas TF compost resulted in the highest syngas formation with $H_2/CO = 3$.

1. Introduction

The pressing demands for greater generation of energy at a lower cost, associated with a diminution of greenhouse gases (GHG) emission, have compelled researchers to expand their search for an energy source outside conventional and primary energy sources, such as fossil fuels. This pursuit is facilitated by the utilization of renewable energy sources and based on Directive 2001/77/EC of the European Parliament that must consist of 13% of the total energy consumption by 2020 in the Czech Republic [1]. Biomass, specifically energy crops, is of particular interest among these renewable energy resources. It has been predicted that by 2050 energy crops will have the potential to supply around 200–400 EJ/year at a competitive cost [2], and up to 161 EJ/year of the 200–400 EJ/year range will come from projected surplus cropland and grassing areas [3]. The competitive costs are based upon the incentives made

available through the scheme for energy crops according to the Article 88 of Regulation (EC) No. 1782/2003 [4]. The preference of energy crops over other types of biomass for energy generation is due to their (i) higher productivity, (ii) lower investment cost, (iii) low environmental maintenance, (iv) short time between plantation and harvesting, and (v) high energy values [5–7]. Another reason for which energy crops, in particular grasses, are being considered as a source of energy is the overproduction of grass and/or hay from permanent grasslands. This overproduction is a result of a diminution of livestock. According to the Czech Statistical Office, the land used for agriculture reached 959,131 ha with harvest of 3.22 t/ha in 2012 [8]. Comparatively, livestock numbers decreased since 1990 by 60.78% for cattle and 66.74% for pigs reaching 1375 cattle and 1593 pigs in 2012 [9]. Therefore, it is necessary to find an appropriate technology to manage and utilize the excess of grass.

The number of technologies available to convert biomass to energy has developed greatly in recent years and they are focused in general on production of synthesis gas (syngas) [10, 11]. Syngas which is a mixture of hydrogen (H_2) and carbon monoxide (CO) can then be directly converted to energy through combustion or to a variety of fuels: (i) liquid hydrocarbons from methanol, (ii) liquid hydrocarbons through Fischer-Tropsch synthesis, and (iii) synthetic natural gas (SNG) [11, 12]. The selective conversion of syngas to liquid hydrocarbons or SNG requires, however, specific ratios of H_2 to CO in the amount of 2 or 3, respectively [12]. Obtaining those explicit values is not a straightforward task as the yields of produced noncondensable gases depend on several factors such as raw material composition and operating conditions of the converting process [13–15].

Two methods in particular have been reported in the literature that convert biomass to syngas, namely, gasification and pyrolysis. Gasification is a thermochemical method which converts a variety of biomass in an oxygen environment. Typical reactions involved in any gasification process are the reactions using oxygen (O_2) (combustion) represented by (1) and (2), the reverse Boudouard reaction represented by (3), the water-gas reaction represented by (4), and the water-gas shift (WGS) reaction represented by (5) [16, 17]:

Partial oxidation:

Oxidation of carbon:

Reverse Boudouard reaction:

Water-gas reaction:

Water-gas shift reaction:

As a consequence of these reactions, a wide range of H_2 /CO ratios (0.45–2) are obtained [18]. Pyrolysis on the other hand is a process in which biomass undergoes thermal degradation in an oxygen-free atmosphere. The final products are pyrolysis solid, liquid, and gas containing mainly CO, carbon dioxide (CO_2), H_2 , and lower hydrocarbons (C_1 – C_3). The remaining reactions involved in the process apart from previously mentioned reactions (3), (4), and (5) are the following [19]:

Steam reforming of methane:

Steam reforming of tar:

Thermal cracking:

Methanation:

The obtained H_2 /CO ratios are dependent on pyrolysis temperature and increase as the latter increases [15, 20–22]. Their values are, however, somewhat lower (i.e., 0.1–1.42 in the 500–1000°C range) when compared to the values obtained from biomass gasification [15, 20, 22]. In addition, in order to make syngas suitable for commercial application (i.e., reduce economic investment and improve its quality (obtain an appropriate H_2 /CO ratio, *ipso facto* increase H_2 formation)), the obtained gas mixture needs to be cleaned and processed [18, 23]. These requirements can be avoided or minimized by pretreatments of biomass raw material such as composting [10, 24].

Composting is a naturally occurring, biological decomposition process in which bacteria, fungi, and other microorganisms break down the organic matter into a more stable form called compost [10, 24, 25]. The process occurs in two stages. The first stage (i.e., organic matter degradation) results in the formation of CO_2 , NH_3 , H_2O , saccharides, and humic substances (fulvic and humic acids) with emission of heat [23, 26]. The second stage involves the maturation and stabilization of formed material [26]. As a result of both stages, the newly formed organic matter has a different chemical composition, *ipso facto* thermal behavior [10, 23, 24, 27]. Composting reduces the content of two of the major biomass components, namely, cellulose and hemicellulose, while increasing the content of lignin [10, 23, 24]. These changes are of particular importance, since lignin is the component responsible for the highest H_2 and CH_4 formation, hemicellulose is responsible for the highest CO_2 emission, and cellulose is responsible for the highest CO release [28–31]. Yang et al. [29] examined pyrolysis characteristics of lignin, cellulose, and hemicellulose and concluded that the main source of H_2 release was lignin. Lignin resulted in four times more emission of H_2 than cellulose and three times more than hemicellulose [29]. Similar results were obtained by Barneto et al. [31] who extended the investigation of H_2 origin and reported that although most of H_2 is emitted from thermal degradation of lignin, three times more H_2 is released from charring than from volatilization of lignin. In addition, hemicellulose is the least stable from the three biochemical components and, therefore, reacts at the lowest temperatures, followed by cellulose and lignin [32]. Consequently, the changes in the chemical composition due to composting result in the changes in pyrolysis gaseous products. That is, a mixture of H_2 and CO becomes the primary product, not a mixture of CO_2 and CO which are the major products of biomass pyrolysis [21, 28]. For this reason also, the composts obtained from perennial grasses rather than grasses alone are considered as a feedstock for pyrolysis experiments in this research.

TABLE 1: Names and abbreviations of composts.

Grass type	Grass name	Compost abbreviation
Nonhybrid	Redtop-Rožnovský (<i>Agrostis gigantea</i> Roth)	R
	Reed canary grass-Chrastava (<i>Phalaris arundinacea</i> L.)	RC
	Tall fescue-Kora (<i>Festuca arundinacea</i> Schreb.)	TF
	Tall oat grass-Rožnovský (<i>Arrhenatherum elatius</i> L.)	TO
	Mountain brome-Tacit (<i>Bromus marginatus</i> Nees ex Steud.)	MB
	Mixture of clover (<i>Trifolium pratense</i>)	MC
Hybrid	Festulolium Perun	FP
	Festulolium Becva	FB
	Festulolium Lofa	FL

TABLE 2: Proximate and ultimate analyses of composts.

Compost	Ultimate analysis (wt%) ^{a,b}				Moisture ^d	Proximate analysis (wt%)			HHV (MJ/kg)
	C	N	H	O ^c		Volatile matter ^a	Ash ^a	Fixed carbon ^{a,c}	
R	47.24	0.91	6.6	45.25	4.54	74.88	09.83	15.29	17.45
RC	46.43	0.49	6.88	46.2	6.29	76.02	07.6	16.38	17.61
TF	46.39	0.56	7.09	45.97	4.38	74.17	10.3	15.53	17.3
TO	48.84	1.11	6.7	43.34	5.66	72.3	12.72	14.98	17.53
MB	47.9	0.59	7.14	44.37	5.87	73.1	11.42	15.48	17.21
MC	44.43	0.96	5.93	48.68	5.23	71.98	13.3	14.72	16.69
FP	46.5	0.83	6.6	46.07	6.12	73.29	10.52	16.19	18.29
FB	44.64	0.64	6.42	48.3	5.5	75.73	07.95	16.32	18.11
FL	48.11	0.77	6.52	44.6	5.68	74.26	08.94	16.8	18.21

^a Dry basis.^b Ash free.^c Calculated by difference.^d As received.

The purpose of this study was to compare the composition, yields, and evolution of gaseous products from pyrolysis of nine composts. The examined composts were obtained from two types of perennial grasses: nonhybrid and hybrid. The main objective was selective formation of syngas with an explicit H₂/CO ratio in the amount of 2:1 or 3:1.

2. Materials and Methods

2.1. Materials. Nine composts made from perennial grasses (six nonhybrid grasses (NHG) and three hybrid grasses (HG)) were investigated in this study. The grass crops were obtained from OSEVA PRO s.r.o., Grass Research Institute, Rožnov-Zubří, CZ. The names and abbreviation of the composts examined are displayed in Table 1.

2.2. Composting. The composting experiments were carried out at the Institute of Geological Engineering, VŠB-Technical University of Ostrava (VŠB-TU Ostrava), CZ. The nine perennial grasses were finely chopped (<2 cm) and mechanically mixed with sawdust and soil in the ratio of 4:2:1 in order to obtain the appropriate C/N ratio. The composting of each blend (perennial grass, sawdust, and soil) was conducted in a microcomposter (NM125, NatureMill) for

10 days, whereas the maturation of composts was carried out for 14 days.

2.3. Chemical Characterization of Composts. All nine composts were subjected to proximate and ultimate analyses. The following standard test methods were applied: CSN EN 15402 (volatile matter), CSN EN 15403 (ash), CSN EN 15104 (carbon (C), nitrogen (N), and hydrogen (H)), and CSN EN 15400 (higher heating value (HHV)). The summarized results are presented in Table 2. The biochemical components were determined according to the CSN EN ISO 13906 standard test method (lignin) and the method described by Kačík and Solár [33] (cellulose and hemicellulose). Humic acids (HA) and fulvic acids (FA) were extracted from composts according to the method described by Swift [34]. In addition, analysis of water-soluble alkali was conducted according to the EN 15105 standard test method. The summarized results are shown in Table 3.

2.4. Pyrolysis Experiments. The pyrolysis experiments were conducted in a stainless steel fixed bed reactor equipped with an electric heater (Parr). The temperature of the heater was controlled by a temperature controller (Parr, 4836 controller), while the reaction temperature was monitored by a K-type thermocouple. The experiments were carried out in

TABLE 3: Biochemical components, humic to fulvic acids ratio, and water-soluble alkali contents of composts.

Compost	Lignin (wt%)	Cellulose (wt%)	Hemicellulose (wt%)	HA/FA	Na (mg/g)	K (g/kg)
R	37.47	43.07	19.07	2.63	1.4	7.76
RC	34.04	51.71	02.51	2.57	4.92	3.44
TF	36.27	51.49	06.99	2.58	1.16	4.71
TO	38.2	46.2	17.92	3.13	1.51	7.7
MB	30.48	55.41	05.98	2.58	2.09	3.93
MC	38.24	43.62	09.07	3.12	3.01	7.76
FP	34.66	54.75	07.18	2.87	4.42	7.86
FB	36.54	53.47	07.78	2.58	1.35	2.87
FL	34.75	50.28	05.77	2.57	1.12	6.7

FIGURE 1: Experimental setup.

N_2 atmosphere and the flow of gas was controlled by a mass-flow controller (SIERRA C100 Serie, Smart-Trak). The experimental setup is presented in Figure 1. For all pyrolysis experiments, 0.5 g of compost was loaded into the reactor and heated to a final temperature of 700°C. The flow of N_2 was maintained at 20 mL/min for all experiments. The experiments were considered completed when N_2 was the only gas detected by online gas chromatography (GC).

2.5. Analysis of Gas Product. The noncondensable pyrolysis product was analyzed by online 2-channel GC (Agilent 3000) equipped with thermal conductivity detectors. The channels were equipped with the following columns: Molsieve for separation of H_2 , N_2 , CO , and CH_4 and PLOT U for separation of CO_2 , C_2 , and C_3 .

2.6. Statistical Analysis. The relationships between components of chemical analyses and pyrolysis gaseous products yields were tested by bivariate correlation analysis, specifically Pearson's correlations. SPSS 17 statistical software was applied.

3. Results and Discussion

3.1. Gas Yield and Evolution. The yield of gaseous products obtained from pyrolysis of NHG and HG composts referred to as a gram of compost used is presented in Figure 2. The highest yield of pyrolysis gaseous products among NHG composts (328.81 mL/g, also the highest yield among all composts pyrolyzed) was obtained for RC compost, whereas the lowest yield of pyrolysis gaseous products (281.74 mL/g) among NHG composts was obtained for MC compost. The highest pyrolysis gas yield among HG composts was obtained for FL compost (286.41 mL/g), whereas the lowest pyrolysis gas yield was obtained for FP compost (251.77 mL/g) which also exhibited the lowest gas yield among all composts examined. The yield of pyrolysis gas decreased in the following order: RC > R > TF > TO > MB > MC for composts made from nonhybrid grasses and FL > FB > FP for composts made from hybrid grasses.

Figure 3 shows the evolution profiles of released pyrolysis gas as a function of temperature. Figure 3(a) presents the evolution profiles of gas released during pyrolysis of NHG composts, while Figure 3(b) shows the evolution profiles of

FIGURE 2: Total gas yield of composts.

gas released during pyrolysis of HG composts. The emission of noncondensable pyrolysis gases at temperature below 500°C is related in majority to degradation of the biochemical structures of compost as well as humic substances formed during the composting process [21, 23, 35, 36], whereas the release of gases at temperature >500°C is likely associated with secondary reactions of char formed from biochemical components or humic substances [21, 23, 28, 35, 36]. In general, pyrolysis gases began to release at 170°C for all compost samples examined which is equivalent to the beginning of thermal degradation of hemicellulosic fraction [23]. The distinction was only observed for the pyrolysis experiment conducted on compost made from hybrid grass (FB) for which a beginning of gas evolution at 247°C was observed. Apart from TO compost which exhibited a three-stage evolution profile (three peaks were observed), all composts investigated resulted in two-stage evolution profiles (two peaks were observed). The composts made from nonhybrid grasses exhibited the maximum of the first peak at temperature range of 315–430°C which is a typical temperature range of thermal degradation of cellulose fraction [29, 30, 37]. The maximum of the second peak was observed at 472°C for TF compost, 508°C for R, RC, and MC composts, and 539°C for TO and MB composts and can be mainly attributed to thermal degradation of lignin and secondary reactions of chars and liquids [23, 29, 30, 37]. The third peak observed for TO compost was detected at 588°C and is also likely due to thermal degradation of lignin and secondary reactions of chars and liquids [23, 29, 30, 37]. As previously mentioned, composts made from hybrid grasses resulted in two-stage gas evolution profiles as well, although more noticeable shifts in the peaks maximum were observed. Specifically, a shift from maximum at 315°C to maximum at 377°C was observed for FP, FB, and FL composts, respectively, and a shift from maximum at 430°C to maximum at 472°C and to maximum at 539°C for the second peak was observed for FP, FL, and FB composts, correspondingly. The change of peaks maximum noted for the FB composts is likely due to the delay of starting point of pyrolysis gas release.

3.2. Pyrolysis Gas Composition. The yields of major pyrolysis gaseous products (H_2 , CO_2 , CO, and CH_4) from grass

composts are presented in Figure 4. Other products such as short-chain hydrocarbons (i.e., C_2 and C_3) were also detected but in sizably lower amounts (less than 1 vol%) and will not be discussed. Figure 4(a) shows yields of NHG composts gaseous products, whereas Figure 4(b) shows yields of HG composts gaseous products. The yields were calculated at 700°C (after 112 min) and at N_2 free-vol%. Among NHG composts, MC compost resulted in the highest production of H_2 (62.17 vol%), the lowest formation of CO (12.74 vol%) and CH_4 (5.10 vol%), and the second lowest formation of CO_2 (18.93 vol%). The lowest yield of H_2 (48.32 vol%) was observed for MB compost and as expected it also resulted in the highest CO (21.34 vol%) and CH_4 (8.01 vol%) formation and a moderately high formation of CO_2 (20.30 vol%). The majority of these observations are directly related to the biochemical composition of examined composts and the contents of water-soluble alkali. Specifically, lignin, cellulose, and potassium (K) contents were found to be associated with H_2 as well as CO and CH_4 formation. A positive correlation was observed between H_2 yield and lignin ($R = 0.916$, $P < 0.05$), and stronger negative correlations were observed between CO yield and lignin ($R = -0.974$, $P < 0.01$) and between CH_4 yield and lignin ($R = -0.929$, $P < 0.01$). The relationship between H_2 and lignin is consistent with the results obtained by Barneto et al. [10] who examined the effect of *Leucaena* and tagasaste composts on the production of volatiles from pyrolysis and reported 75 wt% production of H_2 from lignin. A positive correlation was also observed between H_2 yield and K content ($R = 0.750$, $P < 0.1$) and negative correlations were obtained between CO and CH_4 yields and K content ($R = -0.901$, $P < 0.05$ and $R = -0.742$, $P < 0.1$, correspondingly). Negative relationships between K content and CO and CH_4 were likewise observed by Couhert et al. [38] who reported that mineral matter can influence pyrolysis reactions occurring inside the component's particle and decrease the formation of aforementioned gases. As previously mentioned, these correlations can also be explained by the occurrence of char gasification reactions ((4) and (5)) which are likely to be a result of combination of lignin and K contents. A higher lignin content is associated with a higher K content (i.e., Pearson's correlation coefficient between lignin and K content was 0.832, $P < 0.05$) [28, 39]. Potassium, on the other hand, is known to be an effective catalyst for char gasification [20, 24, 39]. Both MC and MB composts have shown the highest and the lowest lignin and K contents which would explain their H_2 and CO yields, the highest and lowest for MC compost, and the opposite for MB compost, respectively. As previously noted, the formation of H_2 in majority from charring reactions was also confirmed by Barneto et al. [10]. Opposite correlations to those observed between lignin content and CO, CH_4 , and H_2 yields were found for cellulose. That is, a negative correlation was calculated between H_2 yield and cellulose content ($R = -0.860$, $P < 0.05$), and positive correlations were found between CO yield and cellulose content ($R = 0.952$, $P < 0.01$) and between CH_4 yield and cellulose content ($R = 0.876$, $P < 0.05$). The strong positive relationship between CO yield and cellulose content is directly related to higher content of carbonyl groups in cellulose, which is consistent with results obtained by Qu et al.

FIGURE 3: Evolution of gas released during pyrolysis of composts: (a) NHG and (b) HG as a function of temperature.

FIGURE 4: Yields of individual gaseous products from pyrolysis of (a) NHG composts and (b) HG composts at 700°C and N₂ free-vol%.

[28] and Yang et al. [29]. The exception to the observed correlations was observed for CO₂ yield which was found to be unrelated to either biochemical composition or water-soluble alkali. Instead, a weaker and marginally significant correlation to one of the components of proximate analysis, moisture, was observed ($R = 0.780$, $P < 0.1$), which is a further confirmation of presence of water-gas shift reaction.

The individual products yields trends observed for NHG composts were also observed for two out of three HG composts, namely, FP and FB (Figure 4(b)). The remaining compost, FL, resulted in the highest yield of H₂ (55.43 vol%) and the lowest yields of CO₂ (20.58 vol%), CO (16.95 vol%), and CH₄ (5.60 vol%). The analogy of NHG composts cannot be, however, applied to these samples as the correlation between lignin and K contents was in the opposite direction ($R = -0.983$) with a value which fell just shy of the statistical significance threshold ($P = 0.127$). A negative correlation between lignin and K was also reported by Fahmi et al. [40] who investigated the effect of alkali metals on pyrolysis of *Lolium* and *Festuca* independently. For this reason, the NHG and HG composts samples were also separated in this study

when examining the possible relationships between gaseous product yields and composts composition. In addition, the correlations between individual products' (H₂, CO, and CH₄) yields and lignin content were no longer applicable and insignificant due to the small number of observations. The observed changes may, however, suggest that as much as both lignin and K contents affect the H₂ formation during pyrolysis of NHG composts, in the case of HG composts, it may be K content that has the greatest influence on H₂ production.

Figure 5 presents the evolution profiles of pyrolysis gaseous products of NHG composts (Figure 5(a)) and HG composts (Figure 5(b)) as a function of temperature. The products released at temperature below 450°C consisted mainly of CO₂, CO, and CH₄ which is consistent with the prior literature [21]. A further increase of pyrolysis temperature changed the emission of pyrolysis gases as the yield of CO and CO₂ began to decrease in expense of greater H₂ and CH₄ formation. The greatest discrepancies in the emission profiles of primary noncondensable gases were observed for H₂ profiles. The differences occurred not only in the gas release temperature but in the shape of evolution profiles as

FIGURE 5: Evolution profiles of individual gaseous products from pyrolysis of (a) NHG composts and (b) HG composts.

well. The emission of H₂ during pyrolysis of NHG composts began at 430°C (R, RC, and TF composts), 472°C (MC and MB composts), and 508°C (TO compost), whereas the release of H₂ during pyrolysis of HG composts began at 377°C (FP compost), 430°C (FL compost), and 508°C (FB compost). The majority of NHG composts (R, RC, TO, and MB) exhibited double-peak profiles with some shift of both the first peak maximum (observed in the 508–588°C range) and the second peak maximum (observed in the 624–677°C range). The maximum of the first peak is the highest and is attributed to cracking of C–H bonds of lignin and cellulose and its

shift is a consequence of a change of released temperature [29], whereas the second peak is smaller and is associated with pyrolytic reactions of lignin due to its higher content of aromatic ring (i.e., cracking and deformation of C=C and C–H bonds) and charring reactions [29, 31]. The observed changes are also a further confirmation of the fact that the formation of H₂ at temperature >400°C is mostly contributed by pyrolysis of biochemical components, whereas the release of H₂ at temperature >500°C is mainly attributed to thermal degradation of lignin and the occurrence of charring reactions [21, 35, 36]. As aforementioned, these reactions are

more pronounced in the energy grasses than in other biomass type materials (i.e., wood) due to a greater amount of alkali metals responsible for catalyzing these types of reactions [35, 36]. The remaining NHG composts, MC and TF, resulted in single-peak or no-peak evolution profiles, respectively. Similar H_2 profiles were exhibited by HG compost; specifically, a single-peak profile was obtained for FP and FB composts, whereas a no-peak profile was obtained for FL compost. The resemblance between HG composts corresponds well with the profile obtained for TF compost since HG composts are a cross between *Festuca* (FT) and *Lolium*. The overall yield of formed H_2 in these samples is also related to a combination of both pyrolytic reactions of biochemical compounds and charring reactions.

No significant discrepancies between NHG and HG composts were observed in the emission profiles of the remaining gaseous products. All samples displayed wide single-peak profiles and, in general, a starting point of emission at 170°C . The shift of a starting point of emission to 247°C was only observed for FB compost for CO and CO_2 evolution profiles. The majority of CO_2 release took place in the temperature ranges of $250\text{--}450^\circ\text{C}$ for FP and FL (hybrid grasses) composts, and $300\text{--}500^\circ\text{C}$ for NHG and FB (hybrid grass) composts. This corresponds well with CO_2 release from all biochemical components through cracking and reforming of carboxyl groups [28, 29, 41] and is in agreement with calculated Pearson's correlations (i.e., no single statistically significant relationship towards one particular biochemical component was observed). A reduction of CO_2 emission at temperature $>500^\circ\text{C}$ is likely due to secondary reactions of volatiles as temperature at this point has a limited influence [21, 42]. A minor difference between both types of composts was observed in the emission of CO. That is, a single evolution profile with a release of majority of the product in $300\text{--}500^\circ\text{C}$ range was obtained for RC, MB (nonhybrid grasses), and FB (hybrid grass) composts. The remaining samples exhibited a wider but shorter CO peak at temperature ranges of $300\text{--}500^\circ\text{C}$ and $250\text{--}500^\circ\text{C}$ with a break of possible second peak at $500\text{--}640^\circ\text{C}$ range for R, TF, TO, and MC (nonhybrid grasses) and FP and FL (hybrid grasses) composts, correspondingly. The CO emission is mainly attributed to cracking of carbonyl and carboxyl groups from cellulose [28, 29, 41]. The most constant evolution profile was obtained for CH_4 as its emission focused mainly at a temperature range of $450\text{--}550^\circ\text{C}$ and was attributed to cracking of methoxyl groups [28, 29, 41].

3.3. Syngas Production. The high variability of CO and H_2 yields led to gas mixtures with equally high variability of H_2/CO ratios. Figure 6 presents total yield of formed syngas with respect to the particular H_2/CO ratio, specifically, the total yield of syngas produced with $H_2/\text{CO} = 2$ used in Fischer-Tropsch and methanol syntheses and with $H_2/\text{CO} = 3$ used for synthetic natural gas production. All compost samples investigated resulted in syngas formation with $H_2/\text{CO} = 2$. However, only five composts resulted in the production of syngas with $H_2/\text{CO} = 3$ (i.e., R, TF, TO, and MC composts obtained from nonhybrid grasses and FL

FIGURE 6: Total yield of syngas at $H_2/\text{CO} = 2$ and $H_2/\text{CO} = 3$.

compost from hybrid grass). The highest amount of syngas with $H_2/\text{CO} = 2$ was obtained for MB (nonhybrid grass) and FB (hybrid grass) composts, 67.23 vol% and 67.38 vol%, respectively. These two composts also resulted in the lowest H_2 and the highest CO yields, correspondingly, whereas the highest amount of syngas with $H_2/\text{CO} = 3$ (72.10 vol%) was obtained from pyrolysis of TF (nonhybrid grass) compost.

The change of H_2/CO ratio with pyrolysis temperature is shown in Figure 7. In general, apart from two samples, TO and MC composts, all composts displayed a gradual increase of H_2/CO ratio with a pyrolysis temperature increase up to 650°C . A further increase of pyrolysis temperature resulted in a steep H_2/CO ratio increase which corresponds well with obtained CO evolution profiles and indicates mostly H_2 generation. The TO and MC composts exhibited a more abrupt increase of H_2/CO ratio with a pyrolysis temperature increase, which can indicate a higher rate of charring and cracking reactions for these particular samples. It was not a surprise that in regard to the specific value of H_2/CO ratio, these two composts reached this value at the lowest temperature. That is, a H_2/CO ratio = 2 was obtained at 624 and 639°C , whereas a H_2/CO ratio = 3 was obtained at 673 and 684°C , for MC and TO composts, respectively. Among samples for which H_2/CO ratios increased gradually, only one sample in particular reached the required H_2/CO ratio at a similar temperature range. Specifically, R composts resulted in H_2/CO ratio = 2 at 624°C and in H_2/CO ratio = 3 at 682°C . The remaining samples reached the essential H_2/CO ratio in higher temperature ranges of $660\text{--}700^\circ\text{C}$ and $695\text{--}700^\circ\text{C}$ for H_2/CO ratio = 2 and H_2/CO ratio = 3, correspondingly. The temperature necessary to obtain the specific H_2/CO ratios increased, therefore, in the following composts type order: (i) $H_2/\text{CO} = 2$: R, MC < TO < TF < FL < RC < FP < MB < FB and (ii) $H_2/\text{CO} = 3$: MC < R < TO < TF < FL.

3.4. Pyrolysis Gas HHV. The HHVs of pyrolysis gas with respect to its total yield and syngas yield are displayed in Figure 8. The size of the bubble represents the HHV expressed in $\text{MJ}/\text{kg}_{\text{gas}}$ obtained at a specific pyrolysis temperature at which an explicit H_2/CO ratio was reached. Figure 8(a) shows the HHVs of pyrolysis gas obtained at $H_2/\text{CO} = 2$, and

FIGURE 7: H_2/CO ratio as a function of temperature. FIGURE 8: HHVs of pyrolysis gas with respect to its yield and syngas yield: (a) $H_2/CO = 2$ and (b) $H_2/CO = 3$.

Figure 8(b) shows the HHVs of pyrolysis gas obtained at $H_2/CO = 3$. The HHV was directly associated with pyrolysis temperature; that is, as pyrolysis temperature increased, the HHV increased as well. As a consequence, the optimal HHV was reached at the highest syngas yield, which is consistent with the prior literature [21, 43, 44], but not at the highest gas yield. For example, the highest HHV at $H_2/CO = 2$ in the amount of 16.23 and 16.45 MJ/kg_{gas} was obtained for MB (nonhybrid grass) and FB (hybrid grass) composts, respectively, which also resulted in the highest syngas formation; however, they exhibited one of the lowest total gas yields, whereas the highest HHV at $H_2/CO = 3$ was obtained for TF (nonhybrid grass) and FL (hybrid grass) composts, 16.57 and 17.43 MJ/kg_{gas}, correspondingly, which corresponded to the highest syngas yield and third highest total gas yield for TF compost and the highest total gas yield and second highest syngas yield for FL compost. It is important to note that these values are only marginally lower than the HHVs obtained for raw materials (i.e., by 5.69%, 9.17%, 4.22%, and 4.28% for MB, FB, TF, and FL composts, resp.) and are comparable to those obtained from pyrolysis of wood or coir pith [39, 45]. The HHVs of pyrolysis gas reported in the literature are

significantly lower (4–12 MJ/kg_{gas}) and are given mainly for products obtained from pyrolysis of grasses rather than grass composts [12, 42, 43, 46]. The significant increase of observed pyrolysis gases HHV is likely due to (i) composting process which results in lignin enriched material, *ipso facto* greater H_2 formation, and (ii) sawdust addition to the composting process [47].

4. Conclusions

The syngas generation from pyrolysis of nine composts was investigated in this study. Composts were divided into two groups: composts obtained from nonhybrid perennial grasses and composts obtained from hybrid perennial grasses. The pyrolysis experiments were conducted in a fixed bed reactor to a final temperature of 700 °C. Apart from compost obtained from tall oatgrass which exhibited the evolution gas profile with three peaks, all the remaining materials displayed two-peak evolution profiles indicating formation of gases based on two main processes: (i) thermal decomposition of biochemical components and (ii) secondary reactions of

char. A distinction between NHG and HG composts was observed for the evolution profiles of individual gaseous products, in particular H_2 . HG composts resulted in no-peak evolution profiles, whereas NHG composts displayed two-peak and one-peak distributions. A no-peak distribution was only observed for one of the NHG composts made from tall fescue which belongs to the same genus as hybrid grasses. The remaining gaseous products (CO , CO_2 , and CH_4) did not result in significant changes in emission profiles. It was found that all examined composts resulted in H_2/CO necessary for future utilization in the amount of 2 and only five of the studied composts resulted in $H_2/CO = 3$. A close relationship was established between H_2 , CO , and syngas yields, HHV of pyrolysis gas, and temperature required to obtain the essential H_2/CO ratio. Specifically, composts obtaining the highest H_2 yield resulted in the lowest CO yield, following the lowest syngas yield, HHV, and temperature required to obtain the specific H_2/CO ratio, whereas composts obtaining the lowest H_2 yield resulted in the highest CO yield, following the highest syngas yield, HHV, and temperature required to obtain the essential H_2/CO ratio. It was also found that the formation of H_2 was significantly correlated with lignin and K contents for nonhybrid grass. That is, strong positive correlations were obtained between (i) lignin and K contents, (ii) lignin content and H_2 yield, and (iii) K content and H_2 yield. Comparatively, a negative correlation (that just barely fell outside statistical significance) was observed for HG composts between lignin and K contents. The remaining correlations (i.e. between lignin content and H_2 yield and between K content and H_2 yield) were not statistically significant. Remarkable results were also obtained for HHV of pyrolysis gas. Specifically, values close to the HHVs of raw materials, 16.23, 17.43, and 16.45 MJ/kg, were calculated for composts obtained from mountain brome, tall fescue, and festulolium Becva composts, respectively. The increase was attributed to the composting process (i.e., an increase of lignin content) and sawdust addition. Finally, the composts made from mountain brome grass and hybrid Becva were recognized as the optimal materials for fuel/energy generation due to their (i) highest syngas formation and (ii) highest HHV.

Conflict of Interests

The authors declare that there is no conflict of interests regarding the publication of this paper.

Acknowledgments

This research was supported by the Czech Republic Ministry of Education, Youth and Sport, and the Centre ENET research project, Reg. no. CZ.1.05/2.1.00/03.0069, and the Czech Republic Ministry of Agriculture research project, Reg. no. MZ QI101C246, elaborated in the framework of the project New Creative Teams in Priorities of Scientific Research, Reg. no. CZ.1.07/2.3.00/30.0055, supported by Operational Programme Education for Competitiveness, and cofinanced by the European Social Fund and the state budget of the Czech Republic.

References

- [1] European Commission, *Report from the Commission to the European Parliament, the Council, the European Economic and Social Committee and the Committee of the Regions*, 2013.
- [2] R. E. H. Sims, A. Hastings, B. Schlamadinger, G. Taylor, and P. Smith, "Energy crops: current status and future prospects," *Global Change Biology*, vol. 12, no. 11, pp. 2054–2076, 2006.
- [3] H. Haberl, K. Erb, F. Krausmann et al., "Global bioenergy potentials from agricultural land in 2050: sensitivity to climate change, diets and yields," *Biomass and Bioenergy*, vol. 35, no. 12, pp. 4753–4769, 2011.
- [4] Commission of the European Communities, "Report from the Commission to the Council on the review of the energy crops scheme," 2006, http://iet.jrc.ec.europa.eu/remea/sites/remea/files/files/documents/com_2006_500_energy_crops_scheme.pdf.
- [5] L. Potter, M. J. Bingham, M. G. Baker, and S. P. Long, "The potential of two perennial C_4 grasses and a perennial C_4 sedge as ligno-cellulosic fuel crops in N. W. Europe. Crop establishment and yields in E. England," *Annals of Botany*, vol. 76, no. 5, pp. 513–520, 1995.
- [6] M. Rahman, S. B. Mostafiz, J. V. Paatero, and R. Lahdelma, "Extension of energy crops on surplus agricultural lands: a potentially viable option in developing countries while fossil fuel reserves are diminishing," *Renewable and Sustainable Energy Reviews*, vol. 29, pp. 108–119, 2014.
- [7] C. Wrobel, B. E. Coulman, and D. L. Smith, "The potential use of reed canarygrass (*Phalaris arundinacea* L.) as a biofuel crop," *Acta Agriculturae Scandinavica B: Soil and Plant Science*, vol. 59, no. 1, pp. 1–18, 2009.
- [8] Czech Statistical Office, "Harvest of permanent grassland in hay in 2012 by regions," 2013, [http://www.czso.cz/csu/2013edicni-plan.nsf/eng/1000218C20/\\$File/21021326.pdf](http://www.czso.cz/csu/2013edicni-plan.nsf/eng/1000218C20/$File/21021326.pdf).
- [9] Czech Statistical Office, "Agriculture—3rd quarter of 2013. Meat production at the last year level, agricultural producer prices increased," 2013, [http://www.czso.cz/csu/2013edicni-plan.nsf/eng/1000218C20/\\$File/21021326.pdf](http://www.czso.cz/csu/2013edicni-plan.nsf/eng/1000218C20/$File/21021326.pdf).
- [10] A. G. Barneto, J. A. Carmona, and M. Jesús Díaz Blanco, "Effect of the previous composting on volatiles production during biomass pyrolysis," *Journal of Physical Chemistry A*, vol. 114, no. 11, pp. 3756–3763, 2010.
- [11] R. C. Baliban, J. A. Elia, V. Weekman, and C. A. Floudas, "Process synthesis of hybrid coal, biomass, and natural gas to liquids via Fischer-Tropsch synthesis, ZSM-5 catalytic conversion, methanol synthesis, methanol-to-gasoline, and methanol-to-olefins/distillate technologies," *Computers & Chemical Engineering*, vol. 47, pp. 29–56, 2012.
- [12] A. A. Boateng, K. B. Hicks, and K. P. Vogel, "Pyrolysis of switchgrass (*Panicum virgatum*) harvested at several stages of maturity," *Journal of Analytical and Applied Pyrolysis*, vol. 75, no. 2, pp. 55–64, 2006.
- [13] A. Moutsoglou, "A comparison of prairie cordgrass and switchgrass as a biomass for syngas production," *Fuel*, vol. 95, pp. 573–577, 2012.
- [14] A. Gomez-Barea, S. Nilsson, F. V. Barrero, and M. Campoy, "Devolatilization of wood and wastes in fluidized bed," *Fuel Processing Technology*, vol. 91, no. 11, pp. 1624–1633, 2010.
- [15] S. Li, S. Xu, S. Liu, C. Yang, and Q. Lu, "Fast pyrolysis of biomass in free-fall reactor for hydrogen-rich gas," *Fuel Processing Technology*, vol. 85, no. 8–10, pp. 1201–1211, 2004.
- [16] P. Chaiwatanodom, S. Vivanpatarakij, and S. Assabumrungrat, "Thermodynamic analysis of biomass gasification with CO_2

- recycle for synthesis gas production," *Applied Energy*, vol. 114, pp. 10–17, 2014.
- [17] Y. Bai, Y. Wang, S. Zhu, L. Yan, F. Li, and K. Xie, "Synergistic effect between CO₂ and H₂O on reactivity during coal chars gasification," *Fuel*, vol. 126, pp. 1–7, 2014.
 - [18] M. J. A. Tijmensen, A. P. C. Faaij, C. N. Hamelinck, and M. R. M. Van Hardeveld, "Exploration of the possibilities for production of Fischer Tropsch liquids and power via biomass gasification," *Biomass and Bioenergy*, vol. 23, no. 2, pp. 129–152, 2002.
 - [19] M. Widyawati, T. L. Church, N. H. Florin, and A. T. Harris, "Hydrogen synthesis from biomass pyrolysis with in situ carbon dioxide capture using calcium oxide," *International Journal of Hydrogen Energy*, vol. 36, no. 8, pp. 4800–4813, 2011.
 - [20] A. Domínguez, J. A. Menéndez, Y. Fernández et al., "Conventional and microwave induced pyrolysis of coffee hulls for the production of a hydrogen rich fuel gas," *Journal of Analytical and Applied Pyrolysis*, vol. 79, no. 1-2, pp. 128–135, 2007.
 - [21] D. Neves, H. Thunman, A. Matos, L. Tarelho, and A. Gómez-Barea, "Characterization and prediction of biomass pyrolysis products," *Progress in Energy and Combustion Science*, vol. 37, no. 5, pp. 611–630, 2011.
 - [22] A. Dufour, P. Girods, E. Masson, Y. Rogaume, and A. Zoulalian, "Synthesis gas production by biomass pyrolysis: effect of reactor temperature on product distribution," *International Journal of Hydrogen Energy*, vol. 34, no. 4, pp. 1726–1734, 2009.
 - [23] A. G. Barneto, J. A. Carmona, J. A. Conesa Ferrer, and M. J. Díaz Blanco, "Kinetic study on the thermal degradation of a biomass and its compost: composting effect on hydrogen production," *Fuel*, vol. 89, no. 2, pp. 462–473, 2010.
 - [24] A. G. Barneto, J. A. Carmona, A. Gálvez, and J. A. Conesa, "Effects of the composting and the heating rate on biomass gasification," *Energy & Fuels*, vol. 23, no. 2, pp. 951–957, 2009.
 - [25] M. P. Bernal, J. A. Alburquerque, and R. Moral, "Composting of animal manures and chemical criteria for compost maturity assessment: a review," *Bioresource Technology*, vol. 100, no. 22, pp. 5444–5453, 2009.
 - [26] D. Plachá, H. Raclavská, M. Kučerová, and J. Kuchařová, "Volatile fatty acid evolution in biomass mixture composts prepared in open and closed bioreactors," *Waste Management*, vol. 33, no. 5, pp. 1104–1112, 2013.
 - [27] M. Blanco and G. Almendros, "Maturity assessment of wheat straw composts by thermogravimetric analysis," *Journal of Agricultural and Food Chemistry*, vol. 42, no. 11, pp. 2454–2459, 1994.
 - [28] T. Qu, W. Guo, L. Shen, J. Xiao, and K. Zhao, "Experimental study of biomass pyrolysis based on three major components: hemicellulose, cellulose, and lignin," *Industrial and Engineering Chemistry Research*, vol. 50, no. 18, pp. 10424–10433, 2011.
 - [29] H. Yang, R. Yan, H. Chen, D. H. Lee, and C. Zheng, "Characteristics of hemicellulose, cellulose and lignin pyrolysis," *Fuel*, vol. 86, no. 12-13, pp. 1781–1788, 2007.
 - [30] H. Yang, R. Yan, H. Chen, C. Zheng, D. H. Lee, and D. T. Liang, "In-depth investigation of biomass pyrolysis based on three major components: hemicellulose, cellulose and lignin," *Energy & Fuels*, vol. 20, no. 1, pp. 388–393, 2006.
 - [31] A. G. Barneto, J. A. Carmona, J. E. M. Alfonso, and J. A. C. Ferrer, "Use of thermogravimetry/mass spectrometry analysis to explain the origin of volatiles produced during biomass pyrolysis," *Industrial and Engineering Chemistry Research*, vol. 48, no. 15, pp. 7430–7436, 2009.
 - [32] F. Collard, J. Blin, A. Bensakhria, and J. Valette, "Influence of impregnated metal on the pyrolysis conversion of biomass constituents," *Journal of Analytical and Applied Pyrolysis*, vol. 95, pp. 213–226, 2012.
 - [33] F. Kačík and R. Solár, *Analytická chémia dreva*, Technical University in Zvolen, Zvolen, Slovakia, 2000.
 - [34] R. S. Swift, "Organic matter characterization," in *Methods of Soil Analysis, Part 3 Chemical Methods*, D. L. Sparks, A. L. Page, P. A. Helmke et al., Eds., pp. 1011–1069, Soil Science Society of America and American Society of Agronomy, Madison, Wis, USA, 1996.
 - [35] C. J. Gómez, E. Mészáros, E. Jakab, E. Velo, and L. Puigjaner, "Thermogravimetry/mass spectrometry study of woody residues and an herbaceous biomass crop using PCA techniques," *Journal of Analytical and Applied Pyrolysis*, vol. 80, no. 2, pp. 416–426, 2007.
 - [36] R. A. Khalil, E. Mészáros, M. G. Grønli et al., "Thermal analysis of energy crops: part I: the applicability of a macro-thermobalance for biomass studies," *Journal of Analytical and Applied Pyrolysis*, vol. 81, no. 1, pp. 52–59, 2008.
 - [37] K. Raveendran, A. Ganesh, and K. C. Khilar, "Pyrolysis characteristics of biomass and biomass components," *Fuel*, vol. 75, no. 8, pp. 987–998, 1996.
 - [38] C. Couhert, J. Commandre, and S. Salvador, "Is it possible to predict gas yields of any biomass after rapid pyrolysis at high temperature from its composition in cellulose, hemicellulose and lignin?" *Fuel*, vol. 88, no. 3, pp. 408–417, 2009.
 - [39] K. Raveendran, A. Ganesh, and K. C. Khilar, "Influence of mineral matter on biomass pyrolysis characteristics," *Fuel*, vol. 74, no. 12, pp. 1812–1822, 1995.
 - [40] R. Fahmi, A. V. Bridgwater, L. I. Darvell et al., "The effect of alkali metals on combustion and pyrolysis of *Lolium* and *Festuca* grasses, switchgrass and willow," *Fuel*, vol. 86, no. 10-11, pp. 1560–1569, 2007.
 - [41] L. Jiang, S. Hu, L. Sun et al., "Influence of different demineralization treatments on physicochemical structure and thermal degradation of biomass," *Bioresource Technology*, vol. 146, pp. 254–260, 2013.
 - [42] A. A. Boateng, W. F. Anderson, and J. G. Phillips, "Bermudagrass for biofuels: effect of two genotypes on pyrolysis product yield," *Energy and Fuels*, vol. 21, no. 2, pp. 1183–1187, 2007.
 - [43] A. A. Boateng, H. G. Jung, and P. R. Adler, "Pyrolysis of energy crops including alfalfa stems, reed canarygrass, and eastern gamagrass," *Fuel*, vol. 85, no. 17-18, pp. 2450–2457, 2006.
 - [44] D. Beneroso, J. M. Bermúdez, A. Arenillas, and J. A. Menéndez, "Microwave pyrolysis of microalgae for high syngas production," *Bioresource Technology*, vol. 144, pp. 240–246, 2013.
 - [45] K. Raveendran and A. Ganesh, "Heating value of biomass and biomass pyrolysis products," *Fuel*, vol. 75, no. 15, pp. 1715–1720, 1996.
 - [46] J. A. Conesa and A. Domene, "Synthesis gas production from various biomass feedstocks," *AIMS Energy*, vol. 1, pp. 17–27, 2013.
 - [47] S. M. Troy, T. Nolan, J. J. Leahy, P. G. Lawlor, M. G. Healy, and W. Kwapinski, "Effect of sawdust addition and composting of feedstock on renewable energy and biochar production from pyrolysis of anaerobically digested pig manure," *Biomass & Bioenergy*, vol. 49, pp. 1–9, 2013.