Corrigendum

Corrigendum to “Fuel Cells: A Real Option for Unmanned Aerial Vehicles Propulsion”

Óscar González-Espasandín,¹ Teresa J. Leo,² and Emilio Navarro-Arévalo³

¹*Instituto Nacional de Técnica Aeroespacial “Esteban Terradas” (INTA), Carretera Ajalvir km.4., Torrejón de Ardoz, 28850 Madrid, Spain*

²*Departamento de Sistemas Oceánicos y Navales, ETSI Navales, Universidad Politécnica de Madrid, Avenida Arco de la Victoria 4, 28040 Madrid, Spain*

³*Departamento de Motopropulsión y Termofluidodinámica, ETSI Aeronáuticos, Universidad Politécnica de Madrid, Plaza Cardenal Cisneros 3, 28040 Madrid, Spain*

Correspondence should be addressed to Teresa J. Leo; teresa.leo.mena@upm.es

Received 26 March 2015; Accepted 16 April 2015

Copyright © 2015 Óscar González-Espasandín et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

In “Fuel Cells: A Real Option for Unmanned Aerial Vehicles Propulsion” some unclarities were detected in several figures shown in Table 2. To clarify the table, for the Horizon Energy Systems/AEROPAK, the weight (3.5 kg) has been replaced only by the FC weight (0.47 kg); therefore, the FC power density changes from 57.14 W/kg to 425.53 W/kg. Also, the FC power of PROTONEX/ProCore VI is changed from 800 W (peak power) to 280 W (output power), which implies FC power density of 686.27 W/kg.

We provide the updated Table 2.

TABLE 2: Examples of PEM fuel cells for UAV applications. Specifications from manufacturers' websites and [18].

Fuel type	Manufacturer/model	FC weight (kg)	FC power (W)	FC power density (W/kg)	Application/remarks
Chemical hydride cartridge	Horizon Energy Systems/AEROPAK	0.470	200	425.53	IAI Bird Eye 650 LE UAV 10 A-21 V nominal 600 W with LiPo batteries; cartridge type I: 446 Wh/kg; type II: 607 Wh/kg Also used in Bluebird Boomerang Mini-UAV and Elbit Skylark UAV
Sodium borohydride	Protonex/UAV C-250	1.2	250	208.33	500 W peak power with batteries Fuel 833 Wh/kg hydrated Cartridge 1.8 kg, 1.5 l
Compressed H ₂	Protonex/Spider Lion UAV (NRL)	1.77	95	53.67	Spider Lion Micro-UAV 2005, 3-hour flight
Compressed H ₂	Protonex/Ion Tiger UAV (NRL)	1	550	550	Ion Tiger UAV; 550 W FC (1 kg + 3.6 kg tank 0.5 kg H ₂), 26 h 1 m flight record in 2009 Powerplant total weight (including fuel and cooling) = 6 kg. Specific energy 1300 Wh/kg; 26 h endurance
Compressed H ₂	EnergyOr/EO-310-XLE	3.95	310	78.48	Radiant Coral Technologies demonstrator UAV 1st flight February 25, 2013 Hybrid; the weight includes auxiliary systems
Compressed H ₂	EnergyOr/EO-210-XLE	3.65	250	68.49	The weight includes auxiliary systems
Compressed H ₂	DLR/HyFish UAV	3	1000	333.33	HyFish UAV 2007, 0.5-hour flight
Compressed H ₂	UTRC/Gen1	1.78	1200	674.16	Helicopter UAV (October 11, 2009) FC (675 W/kg) Powerplant (500 W/kg) Minicopter Maxi Joker; 20 m flight
Compressed H ₂	BCS/BCS500	6.35	500	78.74	Georgia Tech University UAV 2006 Powerplant weight 12 kg
Compressed H ₂	Horizon Energy Systems/H-100	1.36	100	73.53	Johannesburg University Piper Cub UAV
Sodium borohydride	Protonex/ProCore VI	0.408	280	686.27	AeroVironment Puma UAV 2008 Endurance 9 h
Compressed H ₂	Horizon Fuel Cell Technologies	5	650	130	Pterosaur Micro-UAV 2008. Oklahoma State and California State Universities 15.5 h endurance; FC 480 Wh/kg
Liquid H ₂	NASA/Sensor Technology/AeroVironment	—	—	—	AeroVironment Global Observer (GO-1); 65,000 ft alt., 7-day endurance; PL 180 kg