Corrigendum

Corrigendum to “High- and Low-Temperature Properties and Thermal Stability of Silica Fume/SBS Composite-Modified Asphalt Mortar”

Cao Kai,¹ Xu Wenyan ,¹ Chen Dan,² and Feng Huimin¹

¹College of Civil Engineering, Northeast Forestry University, Harbin 150040, China

²Beijing Municipal Engineering Design and Research Institute Co., Ltd., Beijing 100082, China

Correspondence should be addressed to Xu Wenyan; xuwenyan@nefu.edu.cn

Received 22 July 2019; Accepted 6 September 2019; Published 24 September 2019

Copyright © 2019 Cao Kai et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

In the article titled “High- and Low-Temperature Properties and Thermal Stability of Silica Fume/SBS Composite-Modified Asphalt Mortar” [1], there were errors in Section 3.1 titled “Cone Penetration” and in Section 3.4 titled “BBR” that should be corrected as follows:

(1) In Section 3.1, the horizontal ordinate of Figures 3 and 4 “Cone penetration (0.1 mm)” should be corrected

to “Cone penetration (mm).” The correct figures are as follows.

(2) In Section 3.4, the data of silica fume/SBS composite modified asphalt mortar in Figures 10 and 11 was mixed up with diatomite/SBS composite modified asphalt mortar. The correct figures are as follows.

FIGURE 3: Influence of the content of silica fume on the cone penetration.

FIGURE 4: Influence of the ratio of filler asphalt on the cone penetration.

FIGURE 10: Influence of the content of silica fume on the creep stiffness.

FIGURE 11: Influence of the content of silica fume on the creep rate.

References

- [1] K. Cao, W. Xu, D. Chen, and H. Feng, "High- and low-temperature properties and thermal stability of silica fume/SBS composite-modified asphalt mortar," *Advances in Materials Science and Engineering*, vol. 2018, Article ID 1317436, 8 pages, 2018.