

```

% MatLab codes for the influence of d_2 value change on the system

clear all
close all
clc
warning ('on')
k0 = [0.05 0.05 5000 5000 0.005 0.005 0.005];
lb = [0.05 0.02 0 0 0.00025 0.00025 0.00108];
ub = [0.12 0.09 70000 70000 0.05 0.05 0.07 ];
x0 = [26908.3 15482.6];
load('data.mat')
load('test.mat')
yexp = data;
[k,fval,flag] =
fmincon(@ObjFunc4Fmincon,k0,[],[],[],[],lb,ub,[],[],x0,yexp);

fprintf('\tr1 = %.9f\n',k(1))
fprintf('\tr2 = %.9f\n',k(2))
fprintf('\tk1 = %.9f\n',k(3))
fprintf('\tk2 = %.9f\n',k(4))
fprintf('\td1 = %.9f\n',k(5))
fprintf('\td2 = %.9f\n',k(6))
fprintf('\tm = %.9f\n',k(7))
fprintf(' The sum of the squares is: %.1e\n\n',fval)
k_fmincon = k;

fprintf('\tr1 = %.9f\n',k(1))
fprintf('\tr2 = %.9f\n',k(2))
fprintf('\tk1 = %.9f\n',k(3))
fprintf('\tk2 = %.9f\n',k(4))
fprintf('\td1 = %.9f\n',k(5))
fprintf('\td2 = %.9f\n',k(6))
fprintf('\tm = %.9f\n',k(7))
k0 = k_fmincon;
[k, resnorm, residual, exitflag, output, lambda, jacobian] = ...
lsqnonlin(@ObjFunc4LNL,k0,lb,ub,[],x0,yexp);
ci = nlparci(k,residual,jacobian);

fprintf('\tr1 = %.9f\n',k(1))
fprintf('\tr2 = %.9f\n',k(2))
fprintf('\tk1 = %.9f\n',k(3))
fprintf('\tk2 = %.9f\n',k(4))
fprintf('\td1 = %.9f\n',k(5))
fprintf('\td2 = %.9f\n',k(6))
fprintf('\tm = %.9f\n',k(7))
tspan1=0:1:90;
r1=k(1);
r2=k(2);
k1=k(3);
k2=k(4);
d1=k(5);
m=k(7);
DyDtAnony = @(d2)@(t,x,k) [ ( r1.*x(1).*(1-x(1)./k1)-m.*x(1)-d1.*x(1) )
( r2.*x(2).*(1-x(2)./k2)+m.*x(1)-d2.*x(2) ) ];
figure(1);h1 = axes;hold on;
figure(2);h2 = axes;hold on;

```

```

tspan1 =0:1:90;
for d2 = [0.0380 0.0480 0.0580 ];
    [t,u] = ode45(DyDtAnony(d2),tspan1,x0,k);
    if d2==0.0380
        plot(h1,t,u(:,1),'--r','linewidth',1);
        plot(h2,t,u(:,2),'--b','linewidth',1);
    elseif d2==0.0480
        plot(h1,t,u(:,1),'-r','linewidth',1);
        plot(h2,t,u(:,2),'-b','linewidth',1);
    elseif d2==0.0580
        plot(h1,t,u(:,1),':r','linewidth',1);
        plot(h2,t,u(:,2),':b','linewidth',1);
    end
end
xlabel(h1,'x(tf@)');
ylabel(h1,'t');
legend(h1, '\itd_2=0.0380', '\itd_2=0.0480', '\itd_2=0.0580');
ylabel(h2,'y(t)');
xlabel(h2,'t');
legend(h2, '\itd_2=0.0380', '\itd_2=0.0480', '\itd_2=0.0580');

%% -----
function f = ObjFunc4Fmincon(k,x0,yexp)
tspan =0:1:81;
[t x] = ode45(@KineticEqs,tspan,x0,[],k);
y = x;
f = sum((y(:,1)-yexp(:,1)).^2) + sum((y(:,2)-yexp(:,2)).^2) ;
end

% -----
function f = ObjFunc4LNL(k,x0,yexp)
tspan = 0:1:81;
[t x] = ode45(@KineticEqs,tspan,x0,[],k);
y = x;
f1 = y(:,1) - yexp(:,1);
f2 = y(:,2) - yexp(:,2);
f = [f1; f2];
end

% -----
function dxdt = KineticEqs(t,x,k)
r1=k(1);
r2=k(2);
k1=k(3);
k2=k(4);
d1=k(5);
d2=k(6);
m=k(7);

dxdt = ...
[ ( r1.*x(1).*(1-x(1)./k1)-m.*x(1)-d1.*x(1) )
  ( r2.*x(2).*(1-x(2)./k2)+m.*x(1)-d2.*x(2) )
];
end

```