

Research Article

Removal of Pb, Cu, Cd, and Zn Present in Aqueous Solution Using Coupled Electrocoagulation-Phytoremediation Treatment

Francisco Ferniza-García,¹ Araceli Amaya-Chávez,¹
Gabriela Roa-Morales,² and Carlos E. Barrera-Díaz²

¹Facultad de Química, Universidad Autónoma del Estado de México, Paseo Colón, Colonia Universidad, 50120 Toluca de Lerdo, MEX, Mexico

²Centro Conjunto de Investigación en Química Sustentable, Km 14.5 Carretera Toluca-Atlacomulco, UAEM, “El Rosedal”, San Cayetano, Toluca de Lerdo, MEX, Mexico

Correspondence should be addressed to Araceli Amaya-Chávez; aamayac@uaemex.mx

Received 26 January 2017; Revised 7 April 2017; Accepted 10 May 2017; Published 2 July 2017

Academic Editor: Sergio Ferro

Copyright © 2017 Francisco Ferniza-García et al. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

This study presents the results of a coupled electrocoagulation-phytoremediation treatment for the reduction of copper, cadmium, lead, and zinc, present in aqueous solution. The electrocoagulation was carried out in a batch reactor using aluminum electrodes in parallel arrangement; the optimal conditions were current density of 8 mA/cm² and operating time of 180 minutes. For phytoremediation the macrophytes, *Typha latifolia* L., were used during seven days of treatment. The results indicated that the coupled treatment reduced metal concentrations by 99.2% Cu, 81.3% Cd, and 99.4% Pb, while Zn increased due to the natural concentrations of the plant used.

1. Introduction

The mining industry in Mexico is an important economic activity that provides 4.9% of the National Gross Domestic Product [1], being mostly metallic extraction of Cu, Pb, Ag, Au, Fe, Zn, Mn, Cd, Mo, Bi, Sb, As, Sn, Se, and so forth, through 902 mining complexes [2]. Although mining is considered an important economic sector, it unfortunately causes a high environmental impact with the emission of high concentrations of toxic pollutants (hydrocarbons, mineral salts, heavy metal leaching, particulate material, and acid drainage), which can be dispersed in air, soil, and water with the consequent dispersion towards surface and underground water sources [3, 4].




In recent years, there has been an increasing interest in the development of low cost and high efficiency technologies for the removal of heavy metals in wastewater, which, because of their varied nature, are difficult to eliminate, complicating their treatment and raising their costs [5]. Currently, the elimination is based on unit processes of physicochemical origin

such as advanced oxidation processes, adsorption, chemical precipitation, ion exchange, membrane filtration, solvent extraction, and oxidation/reduction methods [6]. These treatments are efficient, but some concentrations remain and can be treated by other systems, including biological treatments, especially phytoremediation.

In this context, electrochemical coupled biological systems for metal removals of solutions have the potential to achieve high removal efficiencies [7, 8].

Electrocoagulation “EC” (electrochemically assisted coagulation) is a clean technology that uses an electrolytic cell as the basis for its operation and “electrolysis” as a resultant reaction [9], to destabilize organic and inorganic particles of contaminants that are suspended, emulsified, or dissolved in an aqueous medium. Electrical current is induced in the water through parallel metal plates of iron or aluminum, allowing the generation of in situ species such as Al³⁺, Fe²⁺, Fe³⁺, OH, Al(OH)₃, and Fe(OH)₃, capable of coagulating some soluble or suspended particles forming hydrophobic components that adhere to the “floc,” which

subsequently precipitate, facilitating its removal [10–12]. The aluminum hydroxide $\text{Al}(\text{OH})_{3(s)}$ is an amorphous substance of gelatinous character that exposes a large surface area with absorbent properties and that is propitious for the processes of attraction and absorption of the contaminating particles. This is formed by three reactions that occur within the electrocoagulation reactor [13, 14]:



Phytoremediation is a set of technologies that reduce in situ or ex situ concentrations of various organic and inorganic pollutants from biochemical processes performed by plants and microorganisms associated with them; they act as filters and metabolize substances naturally [15]. Among the plants recognized by their phytoremediation potential we have the genus *Typha* that is commonly called toads, bulrush, tule, or bejuco, which has been recognized for its ability to evapotranspire groundwater, high growth rates, broad root zone, ability to bioaccumulate organic and inorganic contaminants, and tolerance to high and sometimes varied concentrations of contaminants [16–18]. *Typha latifolia* L. offers an effective option to treat heavy metals in water; recent works have verified its effectiveness in the removal of Zn, Mn, Ag, Al, As, B, Cb, Cu, Cr, B, Fe, Ni, Co, and Se [19–22], whether live collected in contaminated sites [23] or using them as bioadsorbents [24].

The objective of the present study was the evaluation of the removal efficiency of a coupled electrocoagulation process using aluminum electrodes with phytoremediation (*Typha latifolia* L.), for the treatment of simulated mining water which has the four heavy metals that are commonly present in mining wastewater.

2. Materials and Methods

2.1. Electrocoagulation

2.1.1. Preparation of Simulated Mining Water. A mining water sample of 2 L was prepared by treatment, based on the average concentrations observed during a year in a body of water adjacent to a mining shaft: Pb (16 ppm), Cu (119 ppm), Cd (75 ppm), and Zn (156 ppm).

Sulphate and nitrate metal salts (Fermont) were dissolved in distilled water; the pH was adjusted with H_2SO_4 to reach a value around 5 ± 0.5 ; this pH value is characteristic in the mining wastewater zone [25].

The purpose to use a simulated sample was to evaluate the optimal conditions for efficiently eliminating the major pollutants from the mining wastewater in study.

2.1.2. Electrochemical Reactor. A “batch” reactor was constructed, taking into account the optimum operating conditions described by Rodríguez et al. [26] and Mercado et al. [27]. This consists of 5 pairs of aluminum ($10 \times 5 \times 0.03$ cm). The electrodes were connected to a power source that supplied a direct current of 4 A and 8 V [28], during 180 minutes and temperature intervals of $24 \pm 4^\circ\text{C}$ [29, 30] and the pH was 5 ± 1.8 [31]. During the treatment period, samples were taken at different times to quantify concentrations of heavy metals by atomic absorption spectrophotometry [29].

2.2. Phytoremediation

2.2.1. Collection and Acclimatization of Plants. The macrophyte, *Typha latifolia* L., was collected in the municipality of Toluca, State of Mexico, at coordinates $19^\circ 16' 04.1''\text{N}$ $99^\circ 41' 14.7''\text{W}$ [32]. The macrophyte was collected manually, placed in plastic containers to be kept in water, and transported to the laboratory, where it was grown in dark plastic containers to prevent the formation of algae, with water and Murashige and Skoog nutrient solution “MS” [33] at pH 6.4 ± 0.5 . The plants were maintained at room temperature of $20 \pm 5^\circ\text{C}$ and light/dark photoperiod. The total period of acclimatization lasted 14 days, after which they were used in phytoremediation systems.

2.2.2. Phytoremediation System. Plastic containers with a capacity of 2 liters of electrocoagulated water were distributed in seven treatments systems: control (electrocoagulated water and *Typha latifolia* + nutritional solution “MS” in water). The remaining treatments had the following conditions: a dilution of 12.5% electrocoagulated water, three plants with a biomass of 90 ± 10 g, pH 6.4 ± 1 , temperature ranges of $23 \pm 3^\circ\text{C}$, and nutrient solution MS. The phytoremediation system lasted 7 days. During the treatment of phytoremediation, the levels of concentration of heavy metals in solution were determined [30] and the translocation factor, bioaccumulation factor [34–36], and removal kinetics were calculated.

2.2.3. Tolerance to Exposure. To determine the health of plants due to manipulation and exposure to the residual concentration of the metals mixture after EC, chlorophyll A, chlorophyll B, and carotenes were determined using the spectrophotometric method established by the United States Environmental Protection Agency [37]. The absorbance was read at 663, 645, and 470 nm, respectively, and the concentrations were calculated by the following:

$$\begin{aligned} & \text{mg/mL (chlorophyll A)} \\ & = (12.7 * \text{Abs } 663) - (2.62 * \text{Abs } 645), \\ & \text{mg/mL (chlorophyll B)} \\ & = (22.9 * \text{Abs } 645) - (4.68 * \text{Abs } 663), \\ & \mu\text{g/mL (carotene)} \\ & = (3.775 * \text{Abs } 470) - (0.21 * \text{chlorophyll b}). \end{aligned} \quad (4)$$

2.2.4. Determination of Metals Concentrations in Water and Biomass. The metals concentration was analyzed by atomic absorption spectrophotometry using Avanta GBC 3000 equipment. The liquid samples were filtered using Whatman filter paper with $0.45\ \mu\text{m}$ of pore size and it acidified with concentrated HNO_3 . The biomass (roots and aerial part) was weighed, dried, and ground to a particle size of 20 mesh and then were digested with $\text{H}_2\text{SO}_4\text{-HClO}_4$ (4:1).

Analyze both the electrocoagulation and phytoremediation treatment (water and biomass) by atomic absorption spectrophotometry using Avanta GBC 3000 equipment. The liquid samples previously were filtered with filter paper with $0.45\ \mu\text{m}$ pore size and acidified with concentrated HNO_3 . Regarding the biomass, the root and aerial part were weighed, dried, and ground to a particle size of 20 mesh and then digested with $\text{H}_2\text{SO}_4\text{-HClO}_4$ (4:1).

Translocation factor (FT) was calculated using (5) proposed by Ali et al. [4] and Pandey et al. [21]. The bioaccumulation factor (BCF) was calculated by (6) [38, 39].

$$\text{FT: } \frac{C_{\text{met aerial part}}}{C_{\text{met root}}}, \quad (5)$$

$$\text{BCF: } \frac{C_{\text{met plant tissue}}}{C_{\text{met water}}}, \quad (6)$$


where C_{met} is concentration of the metal in plant (root and aerial part) and water.

3. Results


3.1. Electrocoagulation

3.1.1. Reactions of Electrocoagulation System with Aluminum Electrodes. During the electrocoagulation process, with aluminum electrodes, we have the in situ formation of the coagulant by the corrosion of the sacrificial anode and the parallel evolution of the hydrogen in the cathode that allows the elimination of contaminants by flotation or sedimentation. All this removal process is carried out in three main reactions [31, 40, 41].

(a) Anodic Oxidation Reaction



(b) Cathode Reduction Reaction



The ions Al^{3+} and OH^- generated on the electrodes surface react with the water to form the coagulating agent: amorphous aluminium hydroxide.

(c) Solution Reaction



3.1.2. Effects of pH during Electrocoagulation. The pH influence is one of the most important parameters in electrocoagulation processes, since this determines the ionic species

that will act as a coagulant [42–44], furthermore influencing the current efficiency in the metal solubility process to form hydroxides [45, 46]. To analyze this variable in the simulated mining sample, the pH value is 5.27, which is characteristic of mining wastewater [25]; pH was monitored throughout the electrochemical treatment.

During the first treatment hour, a decrease in the pH value caused by buffering processes between OH^- production and consumption was observed, in addition to the formation of monomeric species. Through the Hydra-Medusa software [47] the species present in the solution were calculated by means of speciation diagrams from equilibrium constants, pH (2–12), 5–60 minutes, $[\text{NO}_3^-]$: 1.29 mM, $[\text{SO}_4^{2-}]$: 3.14 mM, and $[\text{Al}^{3+}]$: 2 mM. Figure 1(a) shows a chemical predominant speciation diagram at the first 5 minutes of treatment. It is interesting to note that there are 5 species; there are between them Al^{3+} , AlSO_4^- , AlOHSO_4 , $\text{Al}(\text{OH})_{3(s)}$, and $\text{Al}(\text{OH})_4^-$ [46–48]. Figure 1(b) shows the mechanisms in the chemical speciation diagram, when applying 60 minutes of treatment. It can be observed that the predominant species are Al^{3+} and $\text{Al}(\text{OH})_{3(s)}$; according to the diagram the formation of the coagulant agent exhibited a minimum solubility at pH a from 3.5 to 10 [49, 50]. In both figures we can see the formation of another polymorphic compound with values of pH = 10, $\text{Al}(\text{OH})_4^-$, which may cause passivation of the cathode [51].

To obtain the distribution diagrams of species of Figure 1, the mass of Al was calculated with de Faraday Law in the indicated times (see (10)). At the end, $[\text{Al}^{3+}]$ was quantified by atomic absorption in the treated water, obtaining a value below the analytic method quantification limit (0.03 mg/L) which coincides with the diagram, so we would not have practically Al in solution, just in the sludge. In the end of the treatment it loses approximately 10 g of the electrode; well the production of sludge is around 29–30 g associated to $\text{Al}(\text{OH})_3$. Mouedhen et al. [30] reported that during the early stages of electrocoagulation the concentration of aluminum increases and is subsequently reduced due to its precipitation by the formation of polymorphic species that generate $\text{Al}(\text{OH})_{3(s)}$.

$$m = \frac{I * t * M}{Z * F}, \quad (10)$$

where M is molecular weight (g mol^{-1}) of the dissolved metal, I is current (A), t is electrolysis time (s), Z is number of electrons involved in the reaction, and Faraday is F (96,485 C mol^{-1}).

3.1.3. Kinetics of Removal. The removal kinetics for Pb, Cu, Cd, and Zn are presented in Table 1 and are fitted to a pseudo-first-order model, and the equation describing this is

$$C(t) = C_0 e^{-kt}, \quad (11)$$

where C_0 is the rate of removal of heavy metal ions (mg l^{-1}), t is the electrocoagulation time in hours, and k is the rate constant (h^{-1}) [52]. The removal results obtained by electrocoagulation in the simulated mineral water were 78.7 to 100%; for this reason, it is necessary to couple it to another polishing treatment such as phytoremediation.




FIGURE 1: (a) Speciation of polymorphic Al complexes calculated by Medusa-Hydra in the range of pH was of 2 to 12, in 5 min of treatment with concentrations of $[NO_3^-]$ 1.29 mM, $[SO_4^{2-}]$ 3.14 mM, and $[Al^{3+}]$ 2 mM. (b) Speciation of polymorphic Al complexes calculated by Medusa-Hydra in a pH range of 2 to 12, in 60 min of treatment with concentrations of $[NO_3^-]$ 1.29 mM, $[SO_4^{2-}]$ 3.14 mM, and $[Al^{3+}]$ 25 mM.

TABLE 1: Predicted parameters for the pseudo-first-order removal rate of the metal mixture in the electrocoagulation system [52].

Heavy metals	CD (mA/cm ²)	First-order model k (h ⁻¹)
Pb	8	1.080
Cu	8	1.372
Cd	8	0.483
Zn	8	1.658

In the heavy metals removal kinetic (Figure 2), it can be noted that Cu and Zn follow a similar behavior with metal hydroxide precipitation around the cathode [47, 49]. In the case of copper (Figure 2(a)), its removal started from a pH of 5.65 in the form of $Cu(OH)_{2(c)}$ [29]. While the removal of Zn was in 3 h of treatment, the species formed are as follows (Figure 2(b)): Zn^{2+} , $ZnSO_4$, $ZnOH^+$, and $Zn(OH)_{2(c)}$. Works by Adhoum et al. [40] and Al-Shannag et al. [53] report percentages of removal similar to this study [52].

Lead precipitated prior Heidmann and Calmano [47] reported that some metals may exhibit this phenomenon and that the concentration decrease will continue as pH increases during electrochemical treatment. In Figure 2(c) it is observed that the precipitation was present due to the presence of the SO_4 anion with which it becomes complexed. The removal process involved the species formed of Pb^{2+} , $PbSO_{4(c)}$, $PbOH^+$, $Pb(OH)_2$, $Pb(OH)_3^-$, and $Pb(OH)_4^{2-}$.

In the case of cadmium the maximum removal is around 80% (Figure 2(d)) in 3 hours of electrochemical treatment. This can be explained using a Medusa-Hydra chemical program (Figure 3) where it can be observed that $Cd(OH)_{2(c)}$ require to increase the pH until 9.5.

The removal efficiency RE (%) in this system was calculated as a function of electrocoagulation time by the following:

$$RE (\%) = \frac{C_0 - C_f}{C_0} * 100, \quad (12)$$

where C_0 is initial concentration of the metal and C_f is final metal concentration.

Figure 4 shows the percentage of removal of the metal ions (Cu^{2+} , Cd^{2+} , Pb^{2+} , and Zn^{2+}) which was increased with the time of electrocoagulation. Removal efficiencies were obtained up to 98.3% for Cu, 78.7% for Cd, and 100% for Zn in 3 hrs. In the case of Pb, a 96.9% removal was obtained by precipitation prior to the electrocoagulation process and the reduction made by the electrochemical treatment. The concentration of the aluminum generated in the reactor was calculated at 2680 mg/l, which decreases during the treatment; Mouedhen et al. [30] indicate that during the early stages of electrocoagulation the concentration of aluminum increases and subsequently reduces due to its participation in the formation of polymorphic species that give rise to $Al(OH)_{3(s)}$.

The energy consumed by electrochemical treatment was determined using cell voltage (U), current (I), and electrocoagulation time (t) [47, 48, 54]. The energy consumed during the electrocoagulation treatment was 26 Kwh/m³.

$$E = \frac{U * I * t}{V}, \quad (13)$$

where U is cell voltage (8 V), I is current (4 A), t is electrolysis time (3 h), and V is volume of solution (3×10^{-3} m³).

3.2. Phytoremediation

3.2.1. Determination of Exposure Tolerance for *Typha latifolia* L. For the tolerance analysis, the plants were exposed to 100% and dilutions to 75, 50, 25, and 12.5% of electrocoagulated water for 7 and 14 days, making daily observations. Significant differences ($p < 0.05$, U of Mann-Whitney) were obtained for chlorophyll production at 14 days in all treatments. At dilutions of >50% after 7 days, phytotoxic effects on macrophytes were observed (Figures 5(a), 5(b), and 5(c)).




FIGURE 2: Removal of Cu, Zn, Pb, and Cd in simulated water during 180 minutes of the electrocoagulation process with a current density of 8 mA/cm², volume of 2 L, pH: 5.27–5.81, concentrations [NO₃⁻]: 1.29 mM, [SO₄²⁻]: 3.14 mM, [Al³⁺]: 25 mM, [Cu²⁺]: 2.58 mM, [Zn²⁺]: 3.70 mM, [Pb²⁺]: 0.57 mM, and [Cd²⁺]: 0.72 mM [52].




FIGURE 3: Specification diagram for Cd(OH)_{2(c)} by Medusa-Hydra chemical program.

The concentration of the electrocoagulated water metal mixture to which the *Typha* was tolerant was at a dilution at 12.5% (mixture of 1.25 mg/l of Cu, 9 mg/l of Cd, 0.2625 mg/l of Pb, and Zn < the limit of quantification), after 7 days of exposure. The concentrations at which no significant differences were found between the values obtained of chlorophyll,

carotene, and their relation to control plants, ANOVA ($p < 0.05$), are shown in Figures 6(a) and 6(b) [52].

Ruiz et al. [25] reported that *Typha latifolia* is tolerant to concentrations of the mixture of 0.309 mg/l of Cd and 23.60 mg/l of Zn present in the wastewater of a mining company. Anning et al. [55] worked with a mixture of 0.31 mg/l




FIGURE 4: Effects of electrocoagulation time on Cu^{2+} , Cd^{2+} , Pb^{2+} , and Zn^{2+} removal efficiency. Density of current (8 mA/cm^2), volume of 2 L, pH: 5.27 to 5.91, and 180 minutes of treatment [52].




FIGURE 5: *Typha latifolia* phytotoxicity in treatments: (a) 50%, (b) 75%, and (c) 100% [52].




FIGURE 6: (a) Concentration of chlorophylls and carotenes in *Typha latifolia*. *ANOVA $p < 0.05$ and Dunnett's multiple range test [52]. (b) Concentration of chlorophylls/carotenes in *Typha latifolia*. Both analyses were not significant at $p < 0.05$ [52].

of Cu and 0.19 mg/l of Pb present in municipal wastewater and tested the tolerance of *T. latifolia* to these concentrations. Both works indicate the potential of the macrophytes in the removal of these four metals, all without showing any signs of phytotoxicity (chlorosis or wilt).

3.2.2. Kinetics of Heavy Metal Removal. To the metal tolerant mixture for the plant, the kinetics of removal were performed.

Figure 7(a) shows that Cu^{2+} had a reduction of 20% at day 1 and subsequently remained constant; similar results were reported by Anning et al., 2013, with the removal of 33.84% Cu present in wastewater by *Typha latifolia*. The reduction of Pb concentration was gradual, obtaining a total removal at 7 days of 61.9%, close to that observed by Oquendo [56] when removing 62% lead solution at 2 ppm using the same macrophytes.




FIGURE 7: (a) Concentrations of Cu and Pb in phytoremediation systems with *Typha latifolia* [52]. (b) Concentration of Zn and Cd in *Typha latifolia* [52].

In Figure 7(b) increases in concentrations of both Zn and Cd (11 mg/l and 5 mg/l), respectively, are observed; this may be due to desorption processes of both metals by the plant; the days of greatest desorption for both metals were day 5 for zinc and day 7 for cadmium. Probably the increase of the concentration of both metals is because the collect site of the *Typha* was contaminated with these heavy metals; Kabata-Pendias [57] mentions that such metals are associated in the soil with concentration range which can reach up to 4832 mg/kg for Zn and 222 mg/kg for Cd. In the phytoremediation system when exposed to the mixture with other metals the root could be saturated, which would lead to the desorption and increase of Zn-Cd in the water.

3.2.3. Translocation Factor (FT). To evaluate the ability of plants to translocate heavy metals from the root to aerial parts, the FT was calculated by aerial concentration/root concentration [58]; we recall that the criterion for establishing that a plant has the translocation capacity of the metal in the vegetative structure is that $FT > 1$ metals [39]. During the treatment with the electrocoagulated mineral water the plants showed high values of FT (Table 2) showing the following trend of $Pb > Zn > Cu > Cd$ translocation.

The higher values of lead in the treatment indicate an efficient transport capacity of the root metal to the aerial part of the plant and its probable accumulation in the plant [34, 59], while Zn, Cu, and Cd presented a $TF < 1$, indicating that the mechanism of accumulation of these metals is the adsorption in the root [60].

3.2.4. Bioaccumulation Factor in Leaves and Roots (BCF_A and BCF_R). In this study, higher values of BCF than FT were observed, indicating that the plant possesses phytoremediation and phytostabilization potential [61, 62]. The concentrations of BCF > 1 in both leaves and root (Table 2), same behavior as Ye et al. [16] and Sasmaz et al. [34]. The Pb

is the one with the greatest accumulation in the vegetative structure.

The bioaccumulation factor in leaves (BCF_A) of *Typha latifolia* L. presented high accumulation of Pb despite being cataloged of low mobility and accumulation in root [56, 63]. The tendency of observed bioaccumulation was $Pb > Cu > Zn$, very similar to that reported by Lyubenova et al. [64].

The bioaccumulation of the metals in the roots was greater than those observed in the aerial parts, except for Pb (Figure 8), as follows: $Pb > Cu > Cd > Zn$, behavior probably due to a passive adsorption process and metal accumulation in the rhizosphere, as reported by Chandra and Yadav [65] and Hazra et al. [66].

3.3. Electrocoagulation-Phytoremediation Coupled System.

The electrocoagulation process used in the treatment of simulated mineral water showed a good effectiveness in the removal of the metal mixture. Residual concentrations were treated by phytoremediation with *Typha latifolia* L., achieving on average an additional 2% removal (Table 3).

4. Conclusions

The mechanisms present in the removal of the Cu, Cd, Pb, and Zn mixture from the simulated mining solution are as follows: (1) In the cathode a reaction of reduction forming metal hydroxides $Cu(OH)_{2(c)}$, $Cd(OH)_{2(c)}$, $Pb(OH)_3$, and $Zn(OH)_{2(c)}$ is performed, which were formed by electrolysis, and (2) coprecipitated with aluminum hydroxide (flocs). The removal rates during the 180 minutes of electrochemical treatment achieved a 100% efficiency in Zn, 98.3% in Cu, 96.4% in Pb, and 78.7% in Cd at pH 5.27. The slower removal of the Cd in comparison to the rest of the metals present in the solution is attributed to a difference in the pH value (9.5) required for this metal as evidenced in the speciation

TABLE 2: Translocation and bioaccumulation factor of metals in the leaf and root of *Typha latifolia* [52].

	Cu			Cd			Zn			Pb		
	BCF _A	BCF _R	FT									
D1	18	22	0.82	4.25	7	0.61	5.86	6	0.98	1485	1510	0.98
D3	10	29	0.34	3.09	6.27	0.49	2.73	2.80	0.98	1445	1365	1.06
D5	20	18	1.11	2.85	4.85	0.59	1.88	2.12	0.89	2820	2810	1.00
D7	13	22	0.59	2.43	5.07	0.48	1.44	2.38	0.61	2690	2570	1.05
Average	15.25	22.75	0.72	3.15	5.80	0.54	2.98	3.32	0.86	2110	2063	1.02

BCF_A: bioaccumulation factor aerial/medium, BCF_R: bioaccumulation factor root: root/medium, and FT: translocation factor: aerial/root.

TABLE 3: Efficiency in the removal of the heavy metals by the coupled process of electrocoagulation and phytoremediation [52].

Metal	Initial concentration (mg/l)	% removal with Electrocoagulation	% removal with Phytoremediation	% removal of coupled system
Cu	119	98.3	20	99.2
Cd	75	78.7	11	81.3
Zn	156	100	—	Desorption
Pb	16	96.9	43	99.4


FIGURE 8: Bioaccumulation factor of Cu, Zn, Pb, and Cd in leaf and root of *Typha latifolia L.*, during 7 days of treatment [52].

diagram. The electrocoagulation process had a calculated energy consumption of 26 kWh/m³.

In the present study it was shown that *Typha latifolia* L. is tolerant to residual concentrations of the metals mixture present in the electrocoagulated water, as evidenced by the content of pigments (chlorophyll and carotene) in the plant. The translocation factor values showed a tendency of the pass of the metals from the root to the aerial part of the plant in the following order: Pb > Zn > Cu > Cd. Likewise the bioconcentration factor indicates that the root of this macrophyte has the ability to perform the phytostabilization and phytoaccumulation processes of the metals studied.

The coupled process electrochemical-phytoremediation had a high removal efficiency of Cu (99.2%), Cd (82.7 to 89.3%), and Pb (99.4%) to the concentrations present in mining wastewater. In this context such combination of treatments is viable both environmentally and economically.

Conflicts of Interest

The authors declare that they have no conflicts of interest.

Acknowledgments

The present paper is a product of the Master thesis by Francisco Ferniza García, student of the M.S. of Environmental Science of the Chemistry Faculty of the Autonomous University of the Mexico State. The authors are also grateful to CONACyT, Pharmacy Laboratory of the Chemistry Faculty of the Autonomous University of the Mexico State, and Center of Research in Sustainable Chemistry, UAEM-UNAM, for the materials and instrumentation used during the development of this study.

References

- [1] Secretaría de Economía, "La Minería," 2014, <http://www.economia.gob.mx/comunidad-negocios/mineria>.
- [2] Cámara Minera de México, "Informe anual 2013," 2013, <https://camimex.org.mx/index.php/secciones1/publicaciones/informe-anual/informe-anual-2013/>.
- [3] D. Galdamez, "Ingeniería Ambiental y Medio Ambiente," 2000, <http://www.fortunecity.es/expertos/profesor/171/medioambiente.html>.
- [4] H. Ali, E. Khan, and M. A. Sajad, "Phytoremediation of heavy metals—concepts and applications," *Chemosphere*, vol. 91, no. 7, pp. 869–881, 2013.
- [5] N. X. Alvarado and S. L. Domínguez, "Remoción de metales pesados por métodos fisicoquímicos presentes en agua proveniente de una industria minera," *Revista Sistemas Ambientales*, vol. 5, no. 1, pp. 27–40, 2012.
- [6] C. Tejada, A. Villabona, and L. Garcés, "Adsorción de metales pesados en aguas residuales usando materiales de origen biológico," *Tecno Lógicas*, vol. 18, no. 34, pp. 109–123, 2014.
- [7] S. Erentürk and E. Malkoç, "Removal of lead(II) by adsorption onto *Viscum album* L.: effect of temperature and equilibrium isotherm analyses," *Applied Surface Science*, vol. 253, no. 10, pp. 4727–4733, 2007.
- [8] G. M. Gadd, "Biosorption: critical review of scientific rationale, environmental importance and significance for pollution treatment," *Journal of Chemical Technology and Biotechnology*, vol. 84, no. 1, pp. 13–28, 2009.
- [9] S. Chen, "Análisis del tráfico de la red de transmisión de datos de la escuela de ingeniería eléctrica de la universidad de costa rica," *Revista Ingeniería*, vol. 10, no. 1-2, 2013.
- [10] Z. Zaroual, H. Chaair, A. H. Essadki, K. El Ass, and M. Azzi, "Optimizing the removal of trivalent chromium by electrocoagulation using experimental design," *Chemical Engineering Journal*, vol. 148, no. 2-3, pp. 488–495, 2009.
- [11] Y. Meas, J. A. Ramirez, M. A. Villalon, and T. W. Chapman, "Industrial wastewaters treated by electrocoagulation," *Electrochimica Acta*, vol. 55, no. 27, pp. 8165–8171, 2010.
- [12] P. K. Holt, G. W. Barton, and C. A. Mitchell, "The future for electrocoagulation as a localised water treatment technology," *Chemosphere*, vol. 59, no. 3, pp. 355–367, 2005.
- [13] P. Cañizares, M. Carmona, J. Lobato, F. Martínez, and M. A. Rodrigo, "Electrodissolution of aluminum electrodes in electrocoagulation processes," *Industrial and Engineering Chemistry Research*, vol. 44, no. 12, pp. 4178–4185, 2005.
- [14] E. Bazrafshan, A. H. Mahvi, S. Naseri, and A. R. Mesdaghinia, "Performance evaluation of electrocoagulation process for removal of chromium (VI) from synthetic chromium solutions using iron and aluminum electrodes," *Turkish Journal of Engineering and Environmental Sciences*, vol. 32, no. 2, pp. 59–66, 2008.
- [15] C. Cho, M. Y. Corapcioglu, S. Park, and K. Sung, "Effects of grasses on the fate of VOCs in contaminated soil and air," *Water, Air, and Soil Pollution*, vol. 187, no. 1-4, pp. 243–250, 2008.
- [16] Z. H. Ye, A. J. M. Baker, M. H. Wong, and A. J. Willis, "Zinc, lead and cadmium tolerance, uptake and accumulation by *Typha latifolia*," *New Phytologist*, vol. 136, no. 3, pp. 469–480, 1997.
- [17] P. K. Padmavathiamma and L. Y. Li, "Phytoremediation technology: Hyper-accumulation metals in plants," *Water, Air, and Soil Pollution*, vol. 184, no. 1-4, pp. 105–126, 2007.
- [18] A. V. Dordio, C. Duarte, M. Barreiros, A. J. P. Carvalho, A. P. Pinto, and C. T. da Costa, "Toxicity and removal efficiency of pharmaceutical metabolite clofibric acid by *Typha* spp. - Potential use for phytoremediation?" *Bioresource Technology*, vol. 100, no. 3, pp. 1156–1161, 2009.
- [19] A. Klink, A. Macioł, M. Wisłocka, and J. Krawczyk, "Metal accumulation and distribution in the organs of *Typha latifolia* L. (cattail) and their potential use in bioindication," *Limnologica*, vol. 43, no. 3, pp. 164–168, 2013.
- [20] J. Teuchies, S. Jacobs, L. Oosterlee, L. Bervoets, and P. Meire, "Role of plants in metal cycling in a tidal wetland: Implications for phytoremediation," *Science of the Total Environment*, vol. 445–446, pp. 146–154, 2013.
- [21] V. C. Pandey, N. Singh, R. P. Singh, and D. P. Singh, "Rhizoremediation potential of spontaneously grown *Typha latifolia* on fly ash basins: Study from the field," *Ecological Engineering*, vol. 71, pp. 722–727, 2014.
- [22] Z. B. Salem, X. Laffray, A. Ashoour, H. Ayadi, and L. Aleya, "Metal accumulation and distribution in the organs of Reeds and Cattails in a constructed treatment wetland (Etueffont, France)," *Ecological Engineering*, vol. 64, pp. 1–17, 2014.
- [23] J. C. Fernandes and F. S. Henriques, "Metal levels in soils and cattail (*typha latifolia* L.) plants in a pyrites mine area at lousal, portugal," *International Journal of Environmental Studies*, vol. 36, no. 3, pp. 205–210, 1990.

- [24] H.-Y. Lai, K.-W. Juang, and Z.-S. Chen, "Large-area experiment on uptake of metals by twelve plants growing in soils contaminated with multiple metals," *International Journal of Phytoremediation*, vol. 12, no. 8, pp. 785–797, 2010.
- [25] Ruiz, M. R. González, J. A. Barrera, G. Chávez, E. Ramírez, and M. C. Durán, "Remoción de Cd y Zn de una corriente acuosa de una empresa minera usando humedales artificiales," *Tecnología, Ciencia, Educación (IMIQ)*, vol. 25, pp. 27–34, 2010.
- [26] C. T. C. Rodríguez, A. Amaya-Chávez, G. Roa-Morales, C. E. Barrera-Díaz, and F. Ureña-Núñez, "An integrated electrocoagulation-phytoremediation process for the treatment of mixed industrial wastewater," *International Journal of Phytoremediation*, vol. 12, no. 8, pp. 772–784, 2010.
- [27] D. I. Mercado, G. González, and H. Valencia, "Remoción de Níquel y DQO presente en aguas residuales de la industria automotriz mediante electrocoagulación," *Revista EIA*, 2013, Colombia.
- [28] Linares, C. Barrera, G. Roa, and F. Ureña, "Remoción de contaminantes biorefractarios en aguas residuales industriales mediante métodos electroquímicos," *Quimera*, vol. 10, no. 1, pp. 1–15, 2008.
- [29] I. Heidmann and W. Calmano, "Removal of Zn(II), Cu(II), Ni(II), Ag(I) and Cr(VI) present in aqueous solutions by aluminium electrocoagulation," *Journal of Hazardous Materials*, vol. 152, no. 3, pp. 934–941, 2008.
- [30] G. Mouedhen, M. Feki, M. D. P. Wery, and H. F. Ayedi, "Behavior of aluminum electrodes in electrocoagulation process," *Journal of Hazardous Materials*, vol. 150, no. 1, pp. 124–135, 2008.
- [31] B. Merzouk, B. Gourich, A. Sekki, K. Madani, and M. Chibane, "Removal turbidity and separation of heavy metals using electrocoagulation-electroflotation technique. A case study," *Journal of Hazardous Materials*, vol. 164, no. 1, pp. 215–222, 2009.
- [32] Sistema Estatal de Áreas Naturales Protegidas en Estado de México, 2014, http://areasnaturales.edomex.gob.mx/alameda_poniente.
- [33] T. Murashige and F. Skoog, "A revised medium for rapid growth and bioassay with tobacco tissue culture," *Plant Physiology*, vol. 15, pp. 473–497, 1962.
- [34] A. Sasmaz, E. Obek, and H. Hasar, "The accumulation of heavy metals in *Typha latifolia* L. grown in a stream carrying secondary effluent," *Ecological Engineering*, vol. 33, no. 3–4, pp. 278–284, 2008.
- [35] K. D. Medina and Y. Montano, *Determinación del factor de bioconcentración y traslocación de metales pesados en el juncus arcticus willd. y cortaderia rudiusscula stapf, de áreas contaminadas con el pasivo ambiental minero alianza - ancash 2013 [Tesis Ingeniería Ambiental]*, 2014, Peru.
- [36] J. A. Romero-Hernández, A. Amaya-Chávez, P. Balderas-Hernández, G. Roa-Morales, N. González-Rivas, and M. Á. Balderas-Plata, "Tolerance and hyperaccumulation of a mixture of heavy metals (Cu, Pb, Hg, and Zn) by four aquatic macrophytes," *International Journal of Phytoremediation*, vol. 19, no. 3, pp. 239–245, 2016.
- [37] EPA (United States. Environmental Protection Agency, *Protecting Coastal Waters from Nonpoint Source Pollution*, U.S. Environmental Protection Agency, Washington D.C. USA, 1997, 841-F-96-004E.
- [38] H. Deng, Z. H. Ye, and M. H. Wong, "Accumulation of lead, zinc, copper and cadmium by 12 wetland plant species thriving in metal-contaminated sites in China," *Environmental Pollution*, vol. 132, no. 1, pp. 29–40, 2004.
- [39] E. A. Ruiz and M. A. Armienta, "Acumulación de arsénico y metales pesados en maíz en suelos cercanos a jales o residuos mineros," *Revista Internacional de Contaminación Ambiental*, vol. 28, no. 2, pp. 103–117, 2012.
- [40] N. Adhoum, L. Monser, N. Bellakhal, and J.-E. Belgaid, "Treatment of electroplating wastewater containing Cu^{2+} , Zn^{2+} and Cr(VI) by electrocoagulation," *Journal of Hazardous Materials*, vol. 112, no. 3, pp. 207–213, 2004.
- [41] Ö. Hanay and H. Hasar, "Effect of anions on removing Cu^{2+} , Mn^{2+} and Zn^{2+} in electrocoagulation process using aluminum electrodes," *Journal of Hazardous Materials*, vol. 189, no. 1–2, pp. 572–576, 2011.
- [42] M. M. Emamjomeh and M. Sivakumar, "Review of pollutants removed by electrocoagulation and electrocoagulation/flotation processes," *Journal of Environmental Management*, vol. 90, no. 5, pp. 1663–1679, 2009.
- [43] Y. Ş. Yildiz, A. S. Kopal, and B. Keskinler, "Effect of initial pH and supporting electrolyte on the treatment of water containing high concentration of humic substances by electrocoagulation," *Chemical Engineering Journal*, vol. 138, no. 1–3, pp. 63–72, 2008.
- [44] M. M. S. G. Eiband, K. C. De A. Trindade, K. Gama, J. V. D. Melo, C. A. Martínez-Huitle, and S. Ferro, "Elimination of Pb^{2+} through electrocoagulation: Applicability of adsorptive stripping voltammetry for monitoring the lead concentration during its elimination," *Journal of Electroanalytical Chemistry*, vol. 717–718, pp. 213–218, 2014.
- [45] M. Piña, M. Domínguez, R. González, F. Prieto, A. Guevara, and J. E. García, "Revisión de variables de diseño y condiciones de operación en la electrocoagulación," *Revista Mexicana de Ingeniería Química*, vol. 10, no. 2, 2011.
- [46] J. Lu, Y. Li, M. Yin, X. Ma, and S. Lin, "Removing heavy metal ions with continuous aluminum electrocoagulation: A study on back mixing and utilization rate of electro-generated Al ions," *Chemical Engineering Journal*, vol. 267, pp. 86–92, 2015.
- [47] I. Puigdomenech, "Hydrochemical Equilibrium Constants Database (MEDUSA)," 1997.
- [48] I. Heidmann and W. Calmano, "Removal of Ni, Cu and Cr from a galvanic wastewater in an electrocoagulation system with Fe and Al-electrodes," *Separation and Purification Technology*, vol. 71, no. 3, pp. 308–314, 2010.
- [49] A. De Mello Ferreira, M. Marchesiello, and P.-X. Thivel, "Removal of copper, zinc and nickel present in natural water containing Ca^{2+} and HCO_3^- ions by electrocoagulation," *Separation and Purification Technology*, vol. 107, pp. 109–117, 2013.
- [50] G. J. Rincón and E. J. La Motta, "Simultaneous removal of oil and grease, and heavy metals from artificial bilge water using electro-coagulation/flotation," *Journal of Environmental Management*, vol. 144, pp. 42–50, 2014.
- [51] E. Bazrafshan, A. H. Mahvi, and M. A. Zazouli, "Removal of zinc and copper from aqueous solutions by electrocoagulation technology using iron electrodes," *Asian Journal of Chemistry*, vol. 23, no. 12, pp. 5506–5510, 2011.
- [52] G. Ferniza, *Eficiencia de un sistema acoplado Electrocoagulación-Fitorremediación para la remoción de Pb, Cu, Cd y Zn, presentes en efluentes mineros [Tesis de Maestría en Ciencias Ambientales de la Facultad de Química de la Universidad Autónoma del Estado de México, Toluca, Estado de México]*, 2017.
- [53] M. Al-Shannag, Z. Al-Qodah, K. Bani-Melhem, M. R. Qtaishat, and M. Alkasrawi, "Heavy metal ions removal from metal plating wastewater using electrocoagulation: kinetic study and process performance," *Chemical Engineering Journal*, vol. 260, pp. 749–756, 2015.

- [54] F. Akbal and S. Camcı, "Copper, chromium and nickel removal from metal plating wastewater by electrocoagulation," *Desalination*, vol. 269, no. 1–3, pp. 214–222, 2011.
- [55] A. K. Anning, P. E. Korsah, and P. Addo-Fordjour, "Phytoremediation of Wastewater with *Limnocharis Flava*, *Thalia Geniculata* and *Typha Latifolia* in Constructed Wetlands," *International Journal of Phytoremediation*, vol. 15, no. 5, pp. 452–464, 2013.
- [56] R. Oquendo, *Evaluación de Typha latifolia en la absorción de plomo y propuesta de fitorremediación de aguas residuales con metales pesados en la laguna de Yahuarcocha [Tesis Maestría Gestión ambiental en la industria]*, 2016, Ecuador.
- [57] A. Kabata-Pendias, *Trace Elements in Soils and Plants*, Taylor and Francis Group, New York, NY, USA, 4th edition, 2011.
- [58] M. Maddison, T. Mairing, K. Remm, M. Lesta, and Ü. Mander, "Dynamics of *Typha latifolia* L. populations in treatment wetlands in Estonia," *Ecological Engineering*, vol. 35, no. 2, pp. 258–264, 2009.
- [59] L. Lyubenova and P. Schröder, "Plants for waste water treatment—Effects of heavy metals on the detoxification system of *Typha latifolia*," *Bioresource Technology*, vol. 102, no. 2, pp. 996–1004, 2011.
- [60] R. Chandra and S. Yadav, "Potential of *Typha angustifolia* for phytoremediation of heavy metals from aqueous solution of phenol and melanoidin," *Ecological Engineering*, vol. 36, no. 10, pp. 1277–1284, 2010.
- [61] A. Samecka-Cymerman and A. J. Kempers, "Heavy metals in aquatic macrophytes from two small rivers polluted by urban, agricultural and textile industry sewages SW Poland," *Archives of Environmental Contamination and Toxicology*, vol. 53, no. 2, pp. 198–206, 2007.
- [62] E. Grisey, X. Laffray, O. Contoz, E. Cavalli, J. Mudry, and L. Aleya, "The bioaccumulation performance of reeds and cattails in a constructed treatment wetland for removal of heavy metals in landfill leachate treatment (Etuefont, France)," *Water, Air, and Soil Pollution*, vol. 223, no. 4, pp. 1723–1741, 2012.
- [63] S. M. Gallego, L. B. Pena, R. A. Barcia et al., "Unravelling cadmium toxicity and tolerance in plants: insight into regulatory mechanisms," *Environmental and Experimental Botany*, vol. 83, pp. 33–46, 2012.
- [64] L. Lyubenova, P. Pongrac, K. Vogel-Mikuš et al., "The fate of arsenic, cadmium and lead in *Typha latifolia*: A case study on the applicability of micro-PIXE in plant ionomics," *Journal of Hazardous Materials*, vol. 248–249, no. 1, pp. 371–378, 2013.
- [65] R. Chandra and S. Yadav, "Phytoremediation of Cd, Cr, Cu, Mn, Fe, Ni, Pb and Zn from aqueous solution using *Phragmites communis*, *Typha angustifolia* and *Cyperus esculentus*," *International Journal of Phytoremediation*, vol. 13, no. 6, pp. 580–591, 2011.
- [66] M. Hazra, K. Avishek, and G. Pathak, "phytoremedial potential of *typha latifolia*, *eichornia crassipes* and *monochoria hastata* found in contaminated water bodies across Ranchi city (India)," *International Journal of Phytoremediation*, vol. 17, no. 9, pp. 835–840, 2015.

