

High-output wearable flow ring-based triboelectric nanogenerator via opposite charging intermediate layer

Seh-Hoon Chung^{1,†}, Yu Ha Jang^{1,†}, Dongchang Kim¹, Joon-seok Lee¹, Sunghan Kim¹, Joong Yull Park¹, Jinkee Hong^{2,*}, and Sangmin Lee^{1,*}

¹ School of Mechanical Engineering, Chung-ang University,
84, Heukseok-ro, Dongjak-gu, Seoul, Republic of Korea


² Department of Chemical & Biomolecular Engineering, College of Engineering, Yonsei University, 50 Yonsei-ro, Seodaemun-gu, Seoul 03722, South Korea

[†] These authors contributed equally to this work


* E-mail: slee98@cau.ac.kr

*E-mail: jinkee.hong@yonsei.ac.kr


Supplementary Information




Supplementary Information 1 | Schematic illustration of FR-TENG with nylon-based substrate and PTFE patterned layer




Supplementary Information 2 | Simulation result of FR-TENG without and with PTFE pattern




Supplementary Information 3 | Schematic illustration of FR-TENG with different dielectric film and electrode number




Supplementary Information 4 | V_{oc} output of FR-TENG with different dielectric film and electrode number



Supplementary Information 5 | I_{CC} output of FR-TENG with different dielectric film and electrode number



Supplementary Information 6 | V_{oc} graph of rectified sleeve-type FR-TENG



Supplementary Information 7 | I_{CC} graph of rectified sleeve-type FR-TENG

Supplementary Video 1|

<https://www.dropbox.com/s/vsv1y4cxdvoahaay/Supplementary%20Video%201.mp4?dl=0>