

## Research Article

# Analytical Approximant to a Quadratically Damped Duffing Oscillator

Alvaro H. Salas S 

Universidad Nacional de Colombia, Fizmako Research Group, Bogotá, Colombia

Correspondence should be addressed to Alvaro H. Salas S; ahsalass@unal.edu.co

Received 15 November 2021; Accepted 17 January 2022; Published 7 February 2022

Academic Editor: Syed Abbas

Copyright © 2022 Alvaro H. Salas S. This is an open access article distributed under the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

The Duffing oscillator of a system with strong quadratic damping is considered. We give an elementary approximate analytical solution to this oscillator in terms of exponential and trigonometric functions. We compare the analytical approximant with the Runge–Kutta numerical solution. We also solve the oscillator by means of He’s homotopy method and the famous Krylov–Bogoliubov–Mitropolsky method. The approximant allows estimating the points at which the solution crosses the horizontal axis.

## 1. Introduction

In the standard textbooks, usually the systems with linear damping are considered. Due to their simplicity and the existence of an exact analytical solution, the problem is discussed in details. Unfortunately, in reality, the systems and damping are usually not linear. In recent times, a number of articles have appeared in the literature which deal with the phenomenon of a linear oscillator subject to a quadratic damping force [1–7]. Most elementary textbooks deal with viscous damping for the obvious reason that it involves a linear dependence on the velocity of the oscillator and presents the simplest situation where an exact analytical treatment is possible. In general, this involves the analysis of a second-order ordinary differential equation (ODE) of the Liénard type, namely,

$$\ddot{x} + f(x)\dot{x} + g(x) = 0. \quad (1)$$

Nonlinear equations of motion such as this are seldom addressed in intermediate instruction in classical dynamics; this one is problematic because it cannot be solved in terms of elementary functions. The principal feature associated

with quadratic damping is a discontinuous jump of the damping force in the equation of motion whenever the velocity vanishes such that the frictional force always opposes the motion. In this paper, we will consider the following quadratically damped Duffing oscillator ( $f(x) = \varepsilon|\dot{x}|$  and  $g(x) = \alpha x + \beta x^3$ ):

$$\ddot{x} + \varepsilon\dot{x}|\dot{x}| + \alpha x + \beta x^3 = 0, \quad x(0) = x_0 \text{ and } x'(0) = \dot{x}_0. \quad (2)$$

The quadratically damped oscillator (2) is never critically damped or overdamped, and that to first order in the damping constant, the oscillation frequency is identical to the natural frequency. In the absence of damping, we obtain the Duffing equation

$$\ddot{x} + \alpha x + \beta x^3 = 0, \quad x(0) = x_0 \text{ and } x'(0) = \dot{x}_0. \quad (3)$$

Equation (3) admits the exact analytical solution [8].

$$x(t) = \frac{x_0 \operatorname{cn}(\sqrt{\omega} t|m) + \dot{x}_0 |\sqrt{\omega} \operatorname{sn}(\sqrt{\omega} t|m) \operatorname{dn}(\sqrt{\omega} t|m)}{1 + b \operatorname{sn}(\sqrt{\omega} t|m)^2}, \quad (4)$$

where

$$\omega = \sqrt{\Delta}, \quad \lim_{t \rightarrow \infty} x(t) = 0. \tag{6}$$

$$m = \frac{1}{2} \left( 1 - \frac{\alpha}{\sqrt{\Delta}} \right), \tag{5}$$

$$b = \frac{1}{2} \left( \frac{\alpha + \beta x_0^2}{\sqrt{\Delta}} - 1 \right),$$

$$\Delta = (\alpha + \beta x_0^2)^2 + 2\beta x_0^2 \neq 0.$$

Our aim is to give an approximate analytical solution to the i.v.p. (2). The residual function  $R = R(t)$  is defined as follows:

$$R(t) = \ddot{x} + \varepsilon \dot{x}|\dot{x}| + \alpha x + \beta x^3 = \ddot{x} + \delta \varepsilon \dot{x}^2 + \alpha x + \beta x^3, \quad \delta = \pm 1. \tag{7}$$

**2. Solution Procedure**

In what follows, we will assume that if  $x = x(t)$  is a solution to the i.v.p. (2), then

2.1. *First Approach.* The ansatz is assumed as

$$x(t) = c_0 e^{-\rho t} \cos \left( \sqrt{\omega} t + \cos^{-1} \left( \frac{x_0}{c_0} \right) \right). \tag{8}$$

We have

$$R(t) = \frac{1}{4} c_0 \cos(\theta) e^{-\rho t} (4\alpha + 3\beta c_0^2 e^{-2\rho t} + 4\rho^2 - 4\omega) + \frac{1}{4} \beta c_0^3 \cos(3\theta) e^{-3\rho t} + \frac{1}{2} c_0^2 \delta \varepsilon \cos(2\theta) (\rho^2 - \omega) e^{-2\rho t} + c_0^2 \delta \varepsilon \rho \sqrt{\omega} \sin(2\theta) e^{-2\rho t} + \frac{1}{2} c_0^2 \delta \varepsilon (\rho^2 + \omega) e^{-2\rho t} + 2c_0 \rho \sqrt{\omega} \sin(\theta) e^{-\rho t}, \quad \delta = \pm 1. \tag{9}$$

Since for small  $t$ ,  $e^{-2\rho t} \approx 1$ , we will choose the value of  $\omega$  so that

$$\omega = \alpha + \frac{3}{4} \beta c_0^2 + \rho^2. \tag{11}$$

$$4\alpha + 3\beta c_0^2 + 4\rho^2 - 4\omega = 0. \tag{10}$$

The value of  $c_0$  is found from the initial condition  $x'(0) = \dot{x}_0$ , and it reads

Then,

$$c_0 = \pm \sqrt{\frac{3\beta x_0^2 - 4\alpha - 4\rho^2 \pm \sqrt{16(\alpha + \rho^2)^2 + 3\beta(8x_0^2(\alpha + 3\rho^2) + 3\beta x_0^4 + 32\rho \dot{x}_0 x_0 + 16\dot{x}_0^2)}}{6\beta}}. \tag{12}$$

In the case when  $\beta \rightarrow 0$ , we define

where

$$c_0 = \pm \sqrt{\frac{x_0^2(\alpha + 2\rho^2) + 2\rho \dot{x}_0 x_0 + \dot{x}_0^2}{\alpha + \rho^2}}. \tag{13}$$

$$r_0 = -\frac{(\sqrt{3} - 3)M}{3\sqrt{6}} \varepsilon,$$

$$r_1 = \frac{\sqrt{2/3}(8\sqrt{3} - 9)}{3M} \varepsilon, \tag{15}$$

$$r_2 = -\frac{4\sqrt{2/3}(2\sqrt{3} - 3)}{3M^3} \varepsilon.$$

The number  $\rho$  is a free parameter that is chosen in order to minimize the residual error.

2.2. *Second Approach*

2.2.1. *He's Homotopy Method.* We will approximate the expression  $\varepsilon \dot{x}|\dot{x}|$  by means of the formula

The homotopy equation is defined as

$$\varepsilon \dot{x}|\dot{x}| \approx r_0 \dot{x} + r_1 \dot{x}^3 + r_2 \dot{x}^5, \quad |\dot{x}| \leq M, \tag{14}$$

$$H(x, p) = \ddot{x} + \alpha x + p[r_0 \dot{x} + r_1 \dot{x}^3 + r_2 \dot{x}^5 + \beta x^3]. \tag{16}$$

Following He's approach [9-16], we assume the solution in the ansatz form

$$x(t) = \exp(-\mu pt) (r_0 \cos(\omega t + B) + p y_1(\omega t + B)), \quad \text{where } \omega = \sqrt{\alpha + p\omega_1}. \tag{17}$$

Let  $\tau = \omega t + B$ . Then,

$$H(x, p) = \frac{1}{16} \left( \begin{array}{l} -2\sqrt{\alpha} r_0 (8r_0 + 5\alpha^2 r_0^4 r_2 + 6\alpha r_0^2 r_1 - 16\mu) \sin(\tau) + \\ 4r_0 (3r_0^2 \beta - 4\omega_1) \cos(\tau) + \\ (5\alpha^{5/2} r_0^5 r_2 + 4\alpha^{3/2} r_0^3 r_1) \sin(3\tau) + 4r_0^3 \beta \cos(3\tau) - \\ \alpha^{5/2} r_0^5 r_2 \sin(5\tau) + 16\alpha y_1(\tau) + 16\alpha y_1''(\tau). \end{array} \right) p + \dots \tag{18}$$

We define

Then,

$$\begin{aligned} \omega_1 &= \frac{3r_0^2 \beta}{4}, \\ \mu &= \frac{1}{16} (8r_0 + 5\alpha^2 r_0^4 r_2 + 6\alpha r_0^2 r_1). \end{aligned} \tag{19}$$

$$\begin{aligned} H(x, p) &= (5\alpha^{5/2} r_0^5 r_2 + 4\alpha^{3/2} r_0^3 r_1) \sin(3\tau) + 4r_0^3 \beta \cos(3\tau) \\ &\quad - \alpha^{5/2} r_0^5 r_2 \sin(5\tau) + 16\alpha y_1(\tau) + 16\alpha y_1''(\tau). \end{aligned} \tag{20}$$

Solving the ode  $H(x, p) = 0$  for  $y_1 = y_1(\tau)$  gives

$$y_1(\tau) = \frac{12r_0^3 \beta \cos(3\tau) + 3\alpha^{3/2} r_0^3 (5\alpha r_0^2 r_2 + 4r_1) \sin(3\tau) - \alpha^{5/2} r_0^5 r_2 \sin(5\tau)}{384\alpha}. \tag{21}$$

The first-order homotopy approximation will then be

$$\begin{aligned} &\left( r_0 \cos(\omega(t)) + \frac{1}{384\alpha} \left( \begin{array}{l} 12r_0^3 \beta \cos(3\omega(t)) + 3\alpha^{3/2} r_0^3 (5\alpha r_0^2 r_2 + 4r_1) \sin(3\omega(t)) \\ \sin(3\omega(t)) - \alpha^{5/2} r_0^5 r_2 \sin(5\omega(t)) \end{array} \right) \right), \quad \text{where} \\ \omega(t) &= \sqrt{\alpha + \frac{3\beta}{4} r_0^2 t} + B, \quad x(t) = \exp\left(-\frac{1}{16} (8r_0 + 6\alpha r_1 r_0^2 + 5\alpha^2 r_2 r_0^4) t\right). \end{aligned} \tag{22}$$

The constants  $r_0$  and  $r_1$  are determined from the initial conditions

$$\begin{aligned} x(0) &= x_0, \\ x'(0) &= \dot{x}_0. \end{aligned} \tag{23}$$

The Krylov–Bogoliubov–Mitropolsky Method (KBM) is a technique to give an approximate analytical solution to the weakly nonlinear second-order equation

$$\frac{d^2 u}{dt^2} + \omega_0^2 u = \varepsilon f\left(u, \frac{du}{dt}\right). \tag{24}$$

When  $\varepsilon = 0$ , the solution of (24) may be expressed as

$$u = a \cos(\omega_0 + \theta), \tag{25}$$

### 2.3. Third Approach

#### 2.3.1. The Krylov–Bogoliubov–Mitropolsky Method (KBM).

where  $a$  and  $\theta$  are constants. For the case when  $\varepsilon > 0$  is small, Krylov and Bogoliubov (1947) assumed that the solution is still given by (25) but with time-varying  $a$  and  $\theta$  and subject to the condition

$$\frac{du}{dt} = -a\omega_0 \sin \phi, \quad \phi = \omega_0 t + \theta. \tag{26}$$

In the general case, the solution is assumed in the ansatz form

$$u = a \cos \psi + \sum_{n=1}^N \varepsilon^n u_n(a, \psi) + O(\varepsilon^{N+1}), \tag{27}$$

where each  $u_n$  is a periodic function of  $\psi$  with a period  $2\pi$  and  $a$  and  $\psi$  are assumed to vary with time according to

$$\frac{da}{dt} = \sum_{n=1}^N \varepsilon^n A_n(a) + O(\varepsilon^{N+1}), \tag{28}$$

$$\frac{d\psi}{dt} = \omega_0 + \sum_{n=1}^N \varepsilon^n \psi_n(a) + O(\varepsilon^{N+1}).$$

In order to uniquely determine  $A_n$  and  $\psi_n$ , we require that no  $u_n$  contains  $\cos \psi$ . Let  $N = 3$ . Then,

---


$$\begin{aligned} \frac{du}{dt} &= -a\omega_0 \sin(\psi) + (\omega_0 u_{1,\psi} - a\psi_1 \sin(\psi) + A_1 \cos(\psi))\varepsilon \\ &\quad + (A_1 u_{1,a} + \omega_0 u_{2,\psi} + \psi_1 u_{1,\psi} - a\psi_2 \sin(\psi) + A_2 \cos(\psi))\varepsilon^2 \\ &\quad + (A_2 u_{1,a} + A_1 u_{2,a} + \omega_0 u_{3,\psi} + \psi_2 u_{1,\psi} + \psi_1 u_{2,\psi} - a\psi_3 \sin(\psi) + A_3 \cos(\psi))\varepsilon^3 + \dots, \\ \frac{d^2u}{dt^2} &= -a\omega_0^2 \cos(\psi) + (\omega_0^2 u_{1,\psi\psi} - 2a\psi_1 \omega_0 \cos(\psi) - 2A_1 \omega_0 \sin(\psi))\varepsilon \\ &\quad + \left( \begin{aligned} &2A_1 \omega_0 u_{1,a\psi} + 2\psi_1 \omega_0 u_{1,\psi\psi} + \omega_0^2 u_{2,\psi\psi} + \sin(\psi)(-aA_1 \dot{\psi}_1 - 2A_1 \psi_1 - 2A_2 \omega_0) + \\ &\cos(\psi)(A_1 \dot{A}_1 - a(2\psi_2 \omega_0 + \psi_1^2)) \end{aligned} \right) \varepsilon^2 \\ &\quad + \left( \begin{aligned} &\dot{A}_1 A_1 u_{1,a} + A_1^2 u_{1,aa} + 2A_1 \psi_1 u_{1,a\psi} + 2A_1 \omega_0 u_{2,a\psi} + 2A_2 \omega_0 u_{1,a\psi} + \\ &A_1 \dot{\psi}_1 u_{1,\psi} + 2\psi_2 \omega_0 u_{1,\psi\psi} + 2\psi_1 \omega_0 u_{2,\psi\psi} + \psi_1^2 u_{1,\psi\psi} + \omega_0^2 u_{3,\psi\psi} + \\ &\sin(\psi)(-aA_2 \dot{\psi}_1 - aA_1 \dot{\psi}_2 - 2A_2 \psi_1 - 2A_1 \psi_2 - 2A_3 \omega_0) + \\ &\cos(\psi)(-2a\psi_3 \omega_0 - 2a\psi_1 \psi_2 + A_2 \dot{A}_1 + A_1 \dot{A}_2) \end{aligned} \right) \varepsilon^3 + \dots. \end{aligned} \tag{29}$$

Here,

$$\begin{aligned} \dot{\psi}_1 &= \psi_1'(t), \\ u_{2,\psi} &= \frac{\partial u_2}{\partial \psi}, \\ u_{2,\psi\psi} &= \frac{\partial^2 u_2}{\partial \psi^2}, \\ u_{1,a\psi} &= \frac{\partial^2 u_1}{\partial \psi \partial a}, \text{ etc.} \end{aligned} \tag{30}$$

Let us consider the i.v.p.

---


$$\ddot{x} + r_0 \dot{x} + r_1 \dot{x}^3 + r_2 \dot{x}^5 + \alpha x + \beta x^3 = 0, \quad x(0) = x_0, x'(0) = \dot{x}_0 \text{ for } 0 \leq t \leq T. \tag{31}$$

The values for  $r_0$ ,  $r_1$ , and  $r_2$  are given by (15). Using KBM, we obtain the following odes for determining  $a = a(t)$  and  $\psi = \psi(t)$ :

$$\begin{aligned} \dot{a} = & -\frac{1}{2}\varepsilon s_0 a + \frac{3\varepsilon(\beta s_0 - 2\alpha^2 s_1)}{16\alpha} a^3 + \frac{\varepsilon(-195\beta^2 s_0 - 96\alpha^2 \beta s_1 - 99^2 \alpha^3 \varepsilon^2 s_0 s_1^2 - 320\alpha^4 s_2 + 160^2 \alpha^3 \varepsilon^2 s_0^2 s_2)}{1024\alpha^2} a^5 \\ & - \frac{\varepsilon(189\beta^2 s_1 + 117\alpha^3 \varepsilon^2 s_1^3 + 720\alpha^2 \beta s_2 + 370\alpha^3 \varepsilon^2 s_0 s_1 s_2)}{8192\alpha} a^7 - \frac{\varepsilon s_2(1701\beta^2 + 1782\alpha^3 \varepsilon^2 s_1^2 + 2170\alpha^3 \varepsilon^2 s_0 s_2)}{73728} a^9 \\ & - \frac{29875\alpha^4 \varepsilon^3 s_1 s_2^2}{196608} a^{11} - \frac{34625\alpha^5 \varepsilon^3 s_2^3}{589824} a^{13}. \end{aligned} \tag{32}$$

$$\begin{aligned} \dot{\psi} = & \frac{8\alpha - \varepsilon^2 s_0^2}{8\sqrt{\alpha}} + \frac{3\beta(8\alpha - \varepsilon^2 s_0^2)}{64\alpha^{3/2}} a^2 + \frac{-15\beta^2 - 57\alpha\beta\varepsilon^2 s_0 s_1 + 9\alpha^3 \varepsilon^2 s_1^2 + 40\alpha^3 \varepsilon^2 s_0 s_2}{256\alpha^{3/2}} a^4 \\ & + \frac{3(41\beta^3 - 223\alpha^3 \beta \varepsilon^2 s_1^2 - 310\alpha^3 \beta \varepsilon^2 s_0 s_2 + 400\alpha^5 \varepsilon^2 s_1 s_2)}{8192\alpha^{5/2}} a^6 \\ & + \frac{\alpha^{3/2} \varepsilon^2 s_2(-471\beta s_1 + 2200\alpha^2 s_2)}{24576} a^8 + \frac{13091\alpha^{5/2} \beta \varepsilon^2 s_2^2}{196608} a^{10}. \end{aligned} \tag{33}$$

$$\begin{aligned} s_0 = & \frac{(\sqrt{3} - 3)M}{3\sqrt{6}}, \\ s_1 = & \frac{\sqrt{2/3}(8\sqrt{3} - 9)}{3M}, \\ s_2 = & \frac{4\sqrt{2/3}(2\sqrt{3} - 3)}{3M^3}, \quad \text{where } M = \max_{0 \leq t \leq T} |\dot{x}(t)|. \end{aligned} \tag{34}$$

The expression for the KBM solution is

$$\begin{aligned} x = x(t) = & a \cos(\psi) \\ & + \frac{a^3 \left( \begin{aligned} & 3072\alpha^2 \beta - 2016a^2 \alpha \beta^2 + 1251a^4 \beta^3 - 576\alpha\beta\varepsilon^2 s_0^2 + 2304\alpha^3 \varepsilon^2 s_0 s_1 - \\ & 3456a^2 \alpha^2 \beta \varepsilon^2 s_0 s_1 + 2592a^2 \alpha^4 \varepsilon^2 s_1^2 - 477a^4 \alpha^3 \beta \varepsilon^2 s_1^2 - 4756a^4 \alpha^3 \beta \varepsilon^2 s_0 s_2 + \\ & 4080a^4 \alpha^5 \varepsilon^2 s_1 s_2 + 321a^6 \alpha^4 \beta \varepsilon^2 s_1 s_2 + 2000a^6 \alpha^6 \varepsilon^2 s_2^2 + 1300a^8 \alpha^5 \beta \varepsilon^2 s_2^2 \end{aligned} \right)}{98304\alpha^3} \cos(3\psi) \\ & + \frac{a^3 \varepsilon \left( \begin{aligned} & 884736\alpha\beta s_0 - 1741824a^2 \beta^2 s_0 + 1179648\alpha^3 s_1 + 884736a^2 \alpha^2 \beta s_1 - \\ & 943488a^4 \alpha \beta^2 s_1 - 221184a^2 \varepsilon^2 s_0^2 s_1 + 580608a^2 \alpha^3 \varepsilon^2 s_0 s_1^2 + \\ & 383616a^4 \alpha^4 \varepsilon^2 s_1^3 + 1474560a^2 \alpha^4 s_2 + 1787904a^4 \alpha^3 \beta s_2 - 257184a^6 \alpha^2 \beta^2 s_2 - \\ & 552960a^2 \alpha^3 \varepsilon^2 s_0^2 s_2 + 2572800a^4 \alpha^4 \varepsilon^2 s_0 s_1 s_2 + 1939680a^6 \alpha^5 \varepsilon^2 s_1^2 s_2 + \\ & 2790400a^6 \alpha^5 \varepsilon^2 s_0 s_2^2 + 2912400a^8 \alpha^6 \varepsilon^2 s_1 s_2^2 + 1226125a^{10} \alpha^7 \varepsilon^2 s_2^3 \end{aligned} \right)}{37748736\alpha^{5/2}} \sin(3\psi) \\ & - \frac{a^7 \left( \begin{aligned} & -144\beta^3 + 3024\alpha^3 \beta \varepsilon^2 s_1^2 + 2672\alpha^3 \beta \varepsilon^2 s_0 s_2 - 3840\alpha^5 \varepsilon^2 s_1 s_2 \\ & + 7548a^2 \alpha^4 \beta \varepsilon^2 s_1 s_2 - 5200a^2 \alpha^6 \varepsilon^2 s_2^2 + 285a^4 \alpha^5 \beta \varepsilon^2 s_2^2 \end{aligned} \right)}{4718592\alpha^3} \cos(7\psi) \end{aligned}$$

$$\begin{aligned}
 & \frac{a^7 \varepsilon \left( \begin{aligned} & -1440\beta^2 s_1 + 1728\alpha^3 \varepsilon^2 s_1^3 + 3072\alpha^2 \beta s_2 - 1362a^2 \alpha \beta^2 s_2 + 9040\alpha^3 \varepsilon^2 s_0 s_1 s_2 \\ & + 16530a^2 \alpha^4 \varepsilon^2 s_1^2 s_2 + 9200a^2 \alpha^4 \varepsilon^2 s_0 s_2^2 + 30065a^4 \alpha^5 \varepsilon^2 s_1 s_2^2 + 15900a^6 \alpha^6 \varepsilon^2 s_2^3 \end{aligned} \right) \sin(7\psi)}{4718592\alpha^{3/2}} \\
 & + \frac{(a^9 \alpha \varepsilon^2 s_2 (2268\beta s_1 - 400\alpha^2 s_2 + 2477a^2 \alpha \beta s_2)) \cos(9\psi)}{7864320} \\
 & + \frac{a^9 \varepsilon s_2 \left( \begin{aligned} & -450\beta^2 + 954\alpha^3 \varepsilon^2 s_1^2 + 784\alpha^3 \varepsilon^2 s_0 s_2 + 3417a^2 \alpha^4 \varepsilon^2 s_1 s_2 \\ & + 2580a^4 \alpha^5 \varepsilon^2 s_2^2 \end{aligned} \right) \sin(9\psi)}{4718592\sqrt{\alpha}} \\
 & - \frac{(1177a^{11} \alpha^2 \beta \varepsilon^2 s_2^2) \cos(11\psi)}{47185920} - \frac{(a^{11} \alpha^{7/2} \varepsilon^3 s_2^2 (3564s_1 + 4915a^2 \alpha s_2)) \sin(11\psi)}{113246208} \\
 & + \frac{(1175a^{13} \alpha^{9/2} \varepsilon^3 s_2^3) \sin(13\psi)}{792723456}.
 \end{aligned} \tag{35}$$

The odes (32) and (33) may be solved numerically. However, since we are interested in obtaining analytical

solutions, we may limit ourselves to the following approximate solutions:

$$\begin{aligned}
 a &= a(t) = \frac{2A\sqrt{r_0}}{\sqrt{4r_0 e^{r_0 t} + 3\alpha r_1 A^2 (e^{r_0 t} - 1)}} \\
 \psi &= \psi(t) = \sqrt{\alpha}t + B - \frac{\beta}{2\alpha^{3/2}r_1} \left( r_0 t + \log \left( e^{r_0 t} + \frac{3A^2 (e^{r_0 t} - 1)\alpha r_1}{4r_0} \right) \right),
 \end{aligned} \tag{36}$$

where the values for  $r_0$ ,  $r_1$ , and  $r_2$  are given by (15). The constants  $A$  and  $B$  are determined from the initial conditions.

$$x(t) = c_0 e^{-\rho t} \cos \left( f(t) + \cos^{-1} \left( \frac{x_0}{c_0} \right) \right), \quad f(0) = 0. \tag{37}$$

We have

2.4. Fourth Approach. We assume the ansatz

$$\begin{aligned}
 R(t) &= \frac{1}{4}c_0 \exp(-3\rho t) \\
 & \left[ \begin{aligned} & (4e^{2\rho t} \alpha + 3c_0^2 \beta + 4e^{2\rho t} \rho^2 - 4e^{2\rho t} f'(t)^2) \cos(\theta) + \\ & 2c_0 e^{\rho t} \delta \varepsilon \rho^2 + c_0^2 \beta \cos(3\theta) + 2c_0 e^{\rho t} \delta \varepsilon f'(t)^2 + 2c_0 e^{\rho t} \delta \varepsilon \cos(2\theta) (\rho^2 - f'(t)^2) + \\ & 4e^{2\rho t} (2\rho f'(t) - f''(t)) \sin(\theta) + 4c_0 e^{\rho t} \delta \varepsilon \rho f'(t) \sin(2\theta) \end{aligned} \right],
 \end{aligned} \tag{38}$$

$\delta = \pm 1$ .

We will choose the function  $f = f(t)$  so that

$$4e^{2\rho t} \alpha + 3c_0^2 \beta + 4e^{2\rho t} \rho^2 - 4e^{2\rho t} f'(t)^2 = 0, \quad f'(t) > 0. \tag{39}$$

Then,

$$f(t) = F(t) - F(0),$$

$$F(t) = -\frac{\sqrt{4(\alpha + \rho^2) + 3\beta c_0^2} e^{-2\rho t}}{2\sqrt{\beta} c_0 \rho \sqrt{4(\alpha + \rho^2) e^{2\rho t} / \beta c_0^2} + 3} \quad (40)$$

$$\left( \sqrt{\beta} c_0 \sqrt{\frac{4(\alpha + \rho^2) e^{2\rho t}}{\beta c_0^2} + 3} - 2\sqrt{\alpha + \rho^2} e^{\rho t} \sinh^{-1} \left( \frac{2\sqrt{\alpha + \rho^2} e^{\rho t}}{\sqrt{3} \sqrt{\beta} c_0} \right) \right).$$

The value of  $c_0$  is found from the initial condition  $x'(0) = \dot{x}_0$ , and it reads

$$c_0 = \pm \sqrt{\frac{3\beta x_0^2 - 4\alpha - 4\rho^2 \pm \sqrt{16\rho^4 + 8\rho^2(4\alpha + 9\beta x_0^2) + (4\alpha + 3\beta x_0^2)^2 + 96\beta\rho x_0 \dot{x}_0 + 48\beta \dot{x}_0^2}}{6\beta}}. \quad (41)$$

In the case when  $\beta \rightarrow 0$ , we define

$$c_0 = \pm \sqrt{\frac{1}{2} \left( x_0^2 + \frac{x_0^2(\alpha + 3\rho^2) + 4\rho \dot{x}_0 x_0 + 2\dot{x}_0^2}{|\alpha + \rho^2|} \right)}. \quad (42)$$

### 3. Analysis and Discussion

In this section, we will compare the accuracy of the solution methods using the different approaches described in the previous section.

*Example 1.* Let us consider the i.v.p.

$$\ddot{x} + 0.2\dot{x}|\dot{x}| + x + 2x^3 = 0, \quad x(0) = 0, \quad x'(0) = 0.1. \quad (43)$$

The approximate analytical solution using the first approach (see formula (8)) for  $\rho = 0.007191$  is

$$x_{\text{approx}}(t) = 0.0992665e^{-0.007191t} \sin(1.00739t). \quad (44)$$

It is shown in Figure 1.

The solution obtained by means of He's homotopy method (see Figure 2) equals

$$x_{\text{He}}(t) = e^{-0.0089515t} \left( \begin{array}{l} -0.0000427888 \sin(3.00025(t + 7.85294)) - 3.49e - \\ 6 \sin(5.00041(t + 7.85294)) - 0.0999944 \cos(1.00008(t + 7.85294)) \\ -1.03e - 6 \cos(3.00025(t + 7.85294)) - 6.9e - 8 \cos(5.00041(t + 7.85294)) \end{array} \right). \quad (45)$$

Using the KBM, we obtained the following solution (Figure 3):

$$\begin{aligned}
 & 6.736e - 9 \sin \left( \frac{-1.89144 \log(0.850343 - 1.e^{0.00345092t}) +}{(4.2634 + 5.94212i) - 4.99347t} \right) + (1.32e - 6 - 1.43e - 6e^{0.00345092t}) \\
 & - \sin(-1.13486 \log(0.850343 - 1.e^{0.00345092t}) + (2.55804 + 3.56527i) - 2.99608t) \\
 & (1.1e - 6e^{0.00345092t} - 9.2e - 7) \cos \left( \frac{-1.13486 \log(0.850343 - 1.e^{0.00345092t}) +}{(2.55804 + 3.56527i) - 2.99608t} \right) + \\
 & (0.00844854 - 0.0198709e^{0.00345092t} + 0.0116841e^{0.00690184t}), \\
 x_{\text{KBM}}(t) = & \frac{\cos(-0.378287 \log(0.850343 - 1.e^{0.00345092t}) + (0.85268 + 1.18842i) - 0.998695t)}{\sqrt{0.0922354e^{0.00345092t} - 0.0784317(0.850343 - e^{0.00345092t})^2}}.
 \end{aligned} \tag{46}$$

Now, using the fourth approach, we get the solution (see Figure 4)

$$x_{\text{trig}}(t) = -0.0992665e^{-0.00719t} \sin \left( \frac{69.541 \sqrt{4.00021 + 0.0591231e^{-0.01438t}} - 4.8811e^{0.00719t} \sqrt{202.977e^{0.01438t} + 3} \sqrt{4.00021 + 0.0591231e^{-0.01438t}} \sinh^{-1}(8.22551e^{0.00719t})}{0.01478 + 1.e^{0.01438t}} + 249.895 \right). \tag{47}$$

Example 2. Let us consider the i.v.p.

$$\ddot{x} + 0.2\dot{x}|\dot{x}| + x + 10x^3 = 0, \quad x(0) = 0, \quad x'(0) = 0.1. \tag{48}$$

The approximate analytical solution for  $\rho = 0.0084$  using the fourth approach is

$$x_{\text{approx}}(t) = 0.097e^{-0.0084t} \sin \left( \left( \frac{59.5231 - 2.067 - \sqrt{4.0003 + 0.280334e^{-0.017t}} - 0.611395 \left( \frac{6.672 - e^{0.0084t} \sqrt{42.81e^{0.017t} + 3} \sqrt{4.0003 + 0.28e^{-0.017t}} \sinh^{-1}(3.778e^{0.0084t})}{0.28 + 4.0003e^{0.017t}} \right) \right) \right). \tag{49}$$

It is shown in Figure 5.

The obtained results may be applied to solve the pendulum equation with quadratic damping

$$\ddot{x} + \varepsilon\dot{x}|\dot{x}| + \omega^2 \sin x = 0, \quad x(0) = x_0, \quad x'(0) = \dot{x}_0. \tag{50}$$

Indeed, we may use the approximation

$$\sin x \approx x - \frac{3}{19}x^3 \text{ for } |x| \leq \frac{\pi}{3}, \tag{51}$$

and then, we replace i.v.p. (43) with the i.v.p.

$$\ddot{x} + \varepsilon\dot{x}|\dot{x}| + \omega^2 x - \frac{3\omega^2}{19}x^3 = 0, \quad x(0) = x_0, \quad x'(0) = \dot{x}_0. \tag{52}$$






FIGURE 1: Comparison between the analytical approximant (44) (formula (8)) and the Runge–Kutta numerical solution for the i.v.p (43).




FIGURE 2: He's homotopy method-error comparison with the Runge–Kutta numerical solution.




FIGURE 3: KBM-error comparison with the Runge–Kutta numerical solution.




FIGURE 4: Method using the fourth approach-error comparison with the Runge–Kutta numerical solution.




FIGURE 5: Comparison between the analytical approximant (49) and the Runge-Kutta numerical solution for the i.v.p (48).

#### 4. Conclusions

We have obtained approximate analytical solutions to the quadratically damped Duffing oscillator equation by means of an elementary approach. We introduced a  $\rho$ -parameter technique that allowed us to optimize the obtained solution. The results are also valid for the linear quadratically damped oscillator  $\ddot{x} + \varepsilon\dot{x}|x| + \alpha x = 0$ . A similar approach may be employed to study the quadratically damped cubic-quintic oscillator  $\ddot{x} + \varepsilon\dot{x}|x| + \alpha x + \beta x^3 + \gamma x^5 = 0$ . Also, a more general quadratically damped oscillator  $\ddot{x} + \varepsilon\dot{x}|x| + h(x) = 0$  may be solved for any odd parity function  $h(x)$ . In future work, we will study quadratically damped forced oscillators having the form  $\ddot{x} + \varepsilon\dot{x}|x| + h(x) = F(t)$  for any continuous functions  $h(x)$  and  $F(t)$ .

#### Data Availability

No data were used to support this study.

#### Conflicts of Interest

The author declares no conflicts of interest.

#### References

- [1] A. Pandey, A. G. Choudhury, and P. Guha, "Cheillini integrability and quadratically damped oscillators," *International Journal of Linear Mechanics*, vol. 92, 2017.
- [2] B. R. Smith, "The quadratically damped oscillator: a case study of a non-linear equation of motion," *American Journal of Physics*, vol. 80, no. 9, pp. 816–824, 2012.
- [3] L. Cveticanin, "Oscillator with strong quadratic damping force," *Publications de l'Institut Mathématique*, vol. 85, no. 99, Article ID 119130, 2009.
- [4] L. Cveticanin, "Analysis techniques for the various forms of the duffing equation in the duffing equation," in *Nonlinear Oscillators and Their Behaviour*, I. Kovacic and M. J. Brennan, Eds., p. 81137, Wiley, Chichester, 2011.
- [5] T. H. Fay, "Quadratic damping," *International Journal of Mathematical Education in Science and Technology*, vol. 43, no. 6, pp. 789–803, 2012.
- [6] K. Klotter, "Free oscillations of systems having quadratic damping and arbitrary restoring forces," *Journal of Applied Mechanics*, vol. 22, no. 4, pp. 493–499, 1955.
- [7] I. Kovacic and Z. Rakaric, "Study of oscillators with a non-negative real-power restoring force and quadratic damping," *Nonlinear Dynamics*, vol. 64, no. 3, pp. 293–304, 2011.
- [8] A. H. Salas, J. E. C. Hernandez, and L. J. M. Hernandez, "The duffing oscillator equation and its applications in physics," *Mathematical Problems in Engineering*, vol. 2021, Article ID 9994967, 16 pages, 2021.
- [9] J. H. He and Y. O. El-Dib, "A tutorial introduction to the two-scale fractal calculus and its application to the fractal Zhiber-Shabat oscillator," *Fractals*, vol. 2021, 2021.
- [10] J.-H. He, D. Nurakhmetov, P. Skrzypacz, and D. Wei, "Dynamic pull-in for micro-electromechanical device with a current-carrying conductor," *Journal of Low Frequency Noise, Vibration and Active Control*, vol. 40, no. 2, pp. 1059–1066, 2021.
- [11] J.-H. He, T. S. Amer, S. Elnaggar, and A. A. Galal, "Periodic property and instability of a rotating pendulum system," *Axioms*, vol. 10, no. 3, p. 191, 2021.
- [12] J.-H. He, Q. Yang, C.-H. He, and Y. Khan, "A simple frequency formulation for the tangent oscillator," *Axioms*, vol. 10, no. 4, p. 320, 2021.
- [13] D. Tian, Q.-T. Ain, N. Anjum, C.-H. He, and B. Cheng, "Fractal N/MEMS: from pull-in instability to pull-in stability," *Fractals*, vol. 29, no. 02, Article ID 2150030, 2021.
- [14] D. Tian and C.-H. He, "A fractal micro-electromechanical system and its pull-in stability," *Journal of Low Frequency Noise, Vibration and Active Control*, vol. 40, no. 3, pp. 1380–1386, 2021.
- [15] C.-H. He, D. Tian, G. M. Moatimid, H. F. Salman, and M. H. Zekry, "Hybrid Rayleigh-van der pol-duffing oscillator: stability analysis and controller," *Journal of Low Frequency Noise, Vibration and Active Control*, vol. 2021, Article ID 146134842110264, 2021.
- [16] C.-H. He and Y. O. El-Dib, "A heuristic review on the homotopy perturbation method for non-conservative oscillators," *Journal of Low Frequency Noise, Vibration and Active Control*, Article ID 146134842110592, 2021.